



BOOK OF ABSTRACTS

Editors

Zbigniew Czyż, Mirosław Szala, Monika Kulisz,
Justyna Kujawska, Wojciech Cel, Marcin Badurowicz,
Katarzyna Falkowicz, Jakub Pizoń

Polish Air Force University
Dęblin 2026

XI International Conference of Computational Methods in Engineering Science
– CMES'26
November 18th-20th, 2026, Kielce, Poland

Book of Abstracts

Editors:

Zbigniew Czyż
Mirosław Szala
Monika Kulisz
Justyna Kujawska
Wojciech Cel
Marcin Badurowicz
Katarzyna Falkowicz
Jakub Pizoń

Technical editor:

Zbigniew Czyż

Cover design:

.....

© Copyright by Lotnicza Akademia Wojskowa, Dęblin 2026 r.

All rights reserved. Copying, reprinting, and dissemination of all or parts of this work without the consent of the publisher is prohibited.

Printed in Poland

ISBN 978-83-68629-17-0

TABLE OF CONTENTS

ABOUT THE CONFERENCE	17
CMES’26 SCIENTIFIC COMMITTEE	21
CMES’26 ORGANIZING COMMITTEE	25
ORGANIZERS	27
HONORARY PATRONAGES	27
PATRONAGES	29
ASSOCIATED EVENTS	31
CMES’26 KEYNOTE SPEAKERS	33
Hasilova Kamila	33
DATA AND MODELS USED IN MILITARY ENGINEERING	
Rafal M. Wojciechowski, Dominik Gawle	35
MULTIPHYSICS ANALYSIS OF ELECTROMAGNETIC-THERMAL COUPLING IN CST STUDIO SUITE AND CO-SIMULATION WITH ABAQUS	
Marcin Badurowicz	37
APPLICATION OF MACHINE LEARNING METHODS IN TRIBOLOGICAL STUDIES OF ION-IMPLANTED MATERIALS	
Jakub Pizoń	39
THE POWER OF DECISION-LEVEL FUSION: ENHANCING CLASSIFICATION THROUGH INTELLIGENT AGGREGATION	
Przemysław Turoś	41
EVALUATION OF THE EFFECTIVENESS OF RADAR DRONE DETECTION: THE APPLICATION OF COMPUTER SIMULATIONS	
ABSTRACTS	43
<u>ANALYSIS OF ENGINEERING PROCESSES</u>	43
Tomasz Milek	43
THEORETICAL AND EXPERIMENTAL ASPECTS OF PLASTIC FORMING – A REVIEW OF RESEARCH RESULTS	
Magdalena Lebiocka, Jerzy Montusiewicz, Agnieszka Montusiewicz, Aleksandra Szaja	44
EVALUATING HYDRODYNAMIC CAVITATION FOR INCREASE OF BIODEGRADABILITY OF HERBAL WASTE: A MULTI-CRITERIA APPROACH	
Wojciech Cel	45
ASSESSMENT OF THE CARBON FOOTPRINT OF BIOCHAR PRODUCTION FROM SEWAGE SLUDGE USING CALCULATION METHODS	

Weronika Wiatrowska, Aleksandra Świadek, Bartosz Wieczorek, Łukasz Warguła	46
VERIFICATION OF FOREARM GRID GENERATION METHODS FOR EMG ELECTRODE PLACEMENT DURING WHEELCHAIR PROPULSION STUDIES	
Łukasz Sobaszek, Bartłomiej Stadnik	47
AI-BASED OPERATOR BEHAVIOR PREDICTION ALGORITHM FOR HUMAN-ROBOT COOPERATION	
Aidana Ussenova, Bakhtiyar Rzayev, Mukhtarbek Kakimov, Bauyrzhan Iskakov, Serik Tokayev, Gulnazym Ospankulova, Roza Abisheva, Michal Bembenek	48
DEVELOPMENT OF TECHNOLOGY AND OPTIMIZATION OF AERODYNAMIC PARAMETERS OF WHEAT FLOUR BY DRY METHOD FOR STARCH AND PROTEIN FRACTIONS	
Konrad Pietrykowski, Paweł Magryta, Rafał Kliza, Zbigniew Czyż	50
WIND TUNNEL AERODYNAMIC EXPERIMENTAL RESULTS OF THE LUBLIN R-XIIID AIRCRAFT MODEL	
Grzegorz Rybak, Dariusz Wójcik, Tomasz Rymarczyk	51
A FORMAL GRAPH MODEL OF AN EMBODIED DATA PUMP FOR IOT-MIXED REALITY INTEGRATION	
Mateusz Waśkowicz, Marek Borowiec, Marcin Fronc, Magdalena Przybylska – Fronc	52
EXPERIMENTAL INVESTIGATION OF NONLINEAR DYNAMICS AND PIEZOELECTRIC RESPONSE OF AN AIRFLOW-INDUCED VIBRATING BEAM	
Marcin Fronc, Krzysztof Kolano, Grzegorz Litak, Magdalena Przybylska – Fronc, Mateusz Waśkowicz	53
MATHEMATICAL MODELLING AND EXPERIMENTAL INVESTIGATION OF A BLDC-BASED ENERGY HARVESTER UNDER NONLINEAR MECHANICAL EXCITATION	
Magdalena Przybylska – Fronc, Grzegorz Litak, Marek Borowiec, Marcin Fronc, Mateusz Waśkowicz	54
NUMERICAL AND EXPERIMENTAL INVESTIGATION OF THE DYNAMICS OF COUPLED ELASTIC BEAMS SUBJECTED TO MECHANICAL EXCITATION	
<u>APPLICATION OF COMPUTER PROGRAMS IN TECHNOLOGY</u>	55
Patryk Organiściak, Paweł Kuraś, Alicja Gerka, Krzysztof Demidowski, Mateusz Salach, Karolina Kisala	55
SCALABILITY ANALYSIS AND PERFORMANCE EVALUATION OF WEBRTC SYSTEMS USING THE INFRASTRUCTURE AS CODE PARADIGM AND CONTAINERIZED TRAFFIC GENERATORS	
Weronika Henzler - Grzywna, Jacek Czarnigowski, Łukasz Grabowski	57
SIMULATION STUDIES OF THE SPRAY WASHING PROCESS	

Grzegorz Koziel, Marta Dziuba-Koziel, Damian Harasim, Piotr Kisala, Sylwester Nowocień LOW-COST MEASUREMENT OF LIGHT POLARISATION PLANE ROTATION USING DOUBLE TFBG SENSORS WITH POWER-BASED INTERROGATION	58
Marcin Matczuk, Łukasz Grabowski, Grzegorz Koziel, Marta Dziuba-Koziel, Dominik Strzałka, Piotr Jakliński, Kamil Żyła, Jacek Kęsik MACHINE LEARNING-BASED ALGORITHM FOR ESTIMATING ENERGY EFFICIENCY OF PHOTOVOLTAIC PANELS IN PUBLIC TRANSPORT: CASE STUDY OF LUBLIN	59
Bartosz Wieczorek, Łukasz Warguła IMAGE-BASED CONTACT PATCH CHARACTERIZATION OF WHEELCHAIR TIRE-ROLLER INTERACTION USING CONVEX HULL AND ALPHA SHAPE ALGORITHMS	60
Beata Tyszkiewicz, Anastasiia Tarnavska, Barbara Buraczyńska PASSWORD SECURITY AMONG INTERNET USERS: AN ANALYSIS OF KNOWLEDGE, ATTITUDES, AND PRACTICES	61
Joanna Szulżyk-Cieplak, Barbara Buraczyńska, Bogdan Basisty IMPACT OF WEBSITE INTERACTIVITY AND PERFORMANCE ON USER EXPERIENCE: AN ANALYSIS OF SELECTED WEBSITES	62
Jarosław Tatarczak, Justyna Baran-Tatarczak MULTI-CRITERIA OPTIMIZATION OF UAV MEDICAL TRANSPORT CORRIDORS IN URBAN ENVIRONMENTS BASED ON COST SURFACE ANALYSIS	63
Karol Łazaruk, Małgorzata Plechawska-Wójcik, Marek Miłosz, Piotr Tokarski, Sergio Luján-Mora COMPARATIVE ANALYSIS OF MEDICAL MOBILE APPLICATIONS USING THE MAQMA METHODOLOGY	64
Andrzej Paszkiewicz, Dariusz Rączka GEOMETRY-BASED DUAL-GRID CLUSTERING ALGORITHM (G2LEACH) FOR ENERGY-EFFICIENT WIRELESS SENSOR NETWORKS FOR IOT ENVIRONMENT	65
Dominik Ożóg, Wojciech Łabuński, Natalia Jajko, Eryk Sęk, Bartosz Stala EVALUATION OF DISTANCE METRICS FOR HUMAN POSE- LANDMARK TRAJECTORIES EXTRACTED WITH DIFFERENT POSE ESTIMATION MODELS	66
Paweł Dymora, Mirosław Mazurek, Bartosz Nycz ANOMALY DETECTION IN MAVLINK TELEMETRY LOGS OF UNMANNED AERIAL VEHICLES USING DATA ANALYTICS METHODS	67
Stanisław Piotr Skulimowski AUDITABLE OFFLINE SPATIOTEMPORAL ALIGNMENT OF HETEROGENEOUS TELEMETRY AND MOTION TRACKING LOGS	68

Dawid Tatarynow ANALYSIS OF THE POTENTIAL FOR MODIFYING SELECTED COMBUSTION PARAMETERS OF RAPESEED OIL–N-HEXANE BLENDS IN A DIESEL ENGINE BY VARYING THE START-OF- INJECTION ANGLE	69
Edyta Wojtaś MONITORING STORM SEWER DISCHARGES AND ASSESSING THE QUALITY OF RECEIVING WATERS USING MULTI-PARAMETER AND ELECTROCHEMICAL PROBES	70
Grzegorz Budzik, Andrzej Paszkiewicz, Lucjan Śnieżek, Mirosław Surowaniec, Kamil Burczy, Dariusz Rączka A MULTI-LAYER CYBER-PHYSICAL 3D PRINTING SECURITY FRAMEWORK FOR THE AEROSPACE AND DEFENSE INDUSTRY	71
Imed El Fray, Julia Stępień DETECTION OF ATTACKS ON COMPUTER NETWORKS USING MACHINE LEARNING - PREDICTIVE MODEL	72
Magdalena Pilat-Rożek, Grzegorz Łagód MACHINE LEARNING MODELS TRAINED ON MULTIDIMENSIONAL GAS SENSOR SIGNALS WITH EXPLAINABLE AI INTERPRETATION FOR SURFACE WATER AND WASTEWATER CLASSIFICATION	73
Aleksandra Kozłowska, Michał Staniszewski, Roman Babko, Grzegorz Łagód ENTROPY-BASED ANALYSIS OF ACTIVATED SLUDGE PARAMETERS	74
Michał Styła, Przemysław Adamkiewicz AMPLITUDE-RANGE REFLECTANCE TOMOGRAPHY FOR ENERGY- EFFICIENT INDOOR OBJECT TRACKING	75
Dariusz Majerek, Dariusz Wójcik, Tomasz Rymarczyk PHYSICS-CONSTRAINED UNROLLED RECONSTRUCTION OF SLOWNESS MAPS IN ULTRASOUND TRANSMISSION TOMOGRAPHY	76
Dariusz Wójcik, Tomasz Rymarczyk, Michał Gołębek, Barbara Stefaniak, Oleksii Hyka MATRIX-FREE RECONSTRUCTION FOR PORTABLE 3D ULTRASONIC NDE	77
Bartłomiej Ambrożkiewicz, Maciej Czarnacki PHYSICS-INFORMED IDENTIFICATION OF RADIAL CLEARANCE IN A NONLINEAR 4-DOF ROLLING BEARING MODEL	78
Krzysztof Skiba, Robert Bąbel, Zbigniew Czyż, Paweł Krpiński, Bartłomiej Ambrożkiewicz DESIGN AND DEVELOPMENT OF AN INTEGRATED TEST BENCH FOR VIBRATION ENERGY HARVESTING WITH A MEASUREMENT AND CONTROL SYSTEM DEVELOPED IN LABVIEW	79

<u>ARTIFICIAL AND COMPUTATIONAL INTELLIGENCE</u>	80
Lukasz Kański EXPLAINABLE CNN-BASED BOTTLENECK DIAGNOSIS IN HUMAN-COBOT MANUFACTURING USING PROCESS HEATMAPS: AN OPERATIONS AND QUALITY MANAGEMENT PERSPECTIVE	80
Patryk Organiściak, Paweł Kuraś, Arkadiusz Stęchły, Adam Masłoń, Anna Turek A HYBRID MACHINE LEARNING AND GENETIC ALGORITHM APPROACH FOR WEATHER-INFORMED BIOGAS PROCESS OPTIMIZATION	81
Justyna Kujawska, Monika Kulisz FORECASTING CO ₂ EMISSIONS FROM SOILS AMENDED WITH SEWAGE SLUDGE BIOCHAR USING ARTIFICIAL NEURAL NETWORKS	82
Mateusz Gogola A DETERMINISTIC MEMORY ARCHITECTURE FOR LARGE LANGUAGE MODELS (LLM) WITH KNOWLEDGE LIFECYCLE MANAGEMENT (KLM)	83
Marta Dziuba-Kozieł INVERSE DESIGN OF MULTIRING OPTICAL FIBRES USING MACHINE LEARNING FOR BEAM SHAPING APPLICATIONS	84
Krzysztof Dziedzic CUSTOM RECURRENT-BASED FRICTION PREDICTION IN A WEAR-RESISTANT HARDFACING ALLOY	85
Krzystian Czajkowski, Maria Skublewska-Paszkowska, Paweł Powroźnik, Marcin Barszcz, Krzysztof Dziedzic, Sylwester Korga TRAINING MACHINE LEARNING AGENT BEHAVIORS IN UNITY: PROXIMAL POLICY OPTIMIZATION VS. SOFT ACTOR-CRITIC ALGORITHMS	86
Kamil Żelazowski, Wojciech Wojciechewicz, Maria Skublewska-Paszkowska, Paweł Powroźnik AUTOMATIC METHODS FOR 3D MOTION TRAJECTORIES GAP FILLING: CUSTOM-BASED KALMAN VS. BILSTM	87
Lukasz Gierz, Dominik Ryder, Łukasz Warguła, Murat Köklu ADVANCES IN AUTOMATIC SEEDLING DETECTION AND LOCALIZATION USING CNN-BASED COMPUTER VISION FOR PRECISION WEED CONTROL IN PRECISION AGRICULTURE	88
Lukasz Rykała, Arkadiusz Rubiec, Karol Cieślík, Mirosław Przybysz PARAMETER IDENTIFICATION OF A DYNAMIC SYSTEM UNDER RANDOM EXCITATION USING NEURAL NETWORKS	89

Tomasz Szymczyk, Marcin Badurowicz ANALYSIS OF THE IMPACT OF NATURAL LANGUAGE SELECTION IN LARGE LANGUAGE MODELS (LLMS) ON ENERGY CONSUMPTION	90
Maria Skublewska-Paszkowska, Paweł Powroźnik, Katarzyna Nowomiejska, Robert Rejdak, Paweł Karczmarek, Kamil Jonak TRUSTWORTHY DEEP LEARNING-BASED ARCHITECTURES FOR THE EVALUATION PROGRESSION OF RETINITIS PIGMENTOSA	91
Tomasz Kobus, Jakub Kopacki, Marcin Barszcz, Krzysztof Dziedzic, Maria Skublewska-Paszkowska, Paweł Powroźnik, Sylwester Korga LOCAL DEPLOYMENT OF OPEN-SOURCE LARGE LANGUAGE MODELS FOR ENTERPRISE AUTOMATION: PERFORMANCE, EFFICIENCY AND DATA SOVEREIGNTY ANALYSIS	92
Mariusz Kamiński MACHINE LEARNING CLASSIFICATION OF ION-IMPLANTED INCONEL 718	94
Bartłomiej Chmielewski, Ireneusz Mrozek, Andrzej Chmielewski ADAPTIVE NEIGHBORHOOD SELECTION IN TOLERANT V- DETECTOR FOR ANOMALY AND INTRUSION DETECTION	95
Aleksandra Prus, Kamil Jonak, Przemysław Krakowski, Robert Karpiński EFFECT OF BODY MASS INDEX ON KNEE JOINT VIBROARTHROGRAPHIC SIGNAL PARAMETERS	96
Katarzyna Mróz RESTING-STATE EEG ACTIVITY AND ITS ASSOCIATIONS WITH SELECTED DIMENSIONS OF PSYCHOLOGICAL FUNCTIONING	97
Katarzyna Baran, Kamil Pietrak THCS-VIT: A HYBRID LIGHTWEIGHT VISION TRANSFORMER WITH MULTI-SCALE FEATURE FUSION FOR THERMAL FACIAL EMOTION RECOGNITION	98
Mateusz Walo, Dariusz Majerek A FINE-TUNED MULTI-AGENT LARGE LANGUAGE MODEL PLATFORM WITH RETRIEVAL-AUGMENTED GENERATION FOR CLINICAL CASE REPORT ANALYSIS	99
Grzegorz Łagód, Dariusz Majerek, Michał Staniszewski, Edyta Wojtaś, Aleksandra Kozłowska, Konrad Jamka APPLICATION OF AUTOMATED IMAGE ANALYSIS IN THE BIOINDICATIVE ASSESSMENT OF ACTIVATED SLUDGE PARAMETERS AND THE IMPACT OF TREATMENT PLANTS ON RECEIVING WATERS	100
Michał Maj, Tomasz Cieplak, Damian Pliszczyk, Jakub Pizoń MULTIMODAL AI AND EDGE INTELLIGENCE FOR CONTEXT- AWARE CUSTOMER RELATIONSHIP MANAGEMENT	101

Lukasz Maciura, Michał Maj, Tomasz Cieplak, Jakub Pizoń CROSS-SIGNER GENERALIZATION OF VISION-LANGUAGE EMBEDDINGS FOR POLISH FINGERSPELLING RECOGNITION	102
Michał Maj, Tomasz Cieplak, Damian Pliszczyk, Jakub Pizoń EXPLAINABLE LOCAL EVALUATION OF FACTUAL CONSISTENCY IN AUTOMATED CLINICAL SUMMARIES AGAINST SOAP REFERENCES	103
Grzegorz Jabłoński, Mariusz Michalski, Norbert Grzesik, Marcin Markiewicz FUZZY LOGIC CONTROLLER FOR AUTONOMOUS OBSTACLE AVOIDANCE IN A QUADROTOR UNMANNED AERIAL VEHICLE	104
<u>COMPUTATIONAL FLUID DYNAMICS (CFD)</u>	105
Paweł Capała, Monika Ruszak, Zbigniew Czyż, Anna Rudawska NUMERICAL CFD ANALYSIS OF CATALYTIC BASKETS IN DUAL-BED CATALYTIC REACTORS	105
Armin Alavi, Kamil Urbanowicz A 1D-3D COUPLED NUMERICAL APPROACH TO INVESTIGATE WATER HAMMER IN A RESERVOIR PIPE VALVE SYSTEM USING REALISTIC VALVE CLOSURE MECHANISM	106
Robert Bąbel CFD-BASED ANALYSIS OF LIFT AND DRAG CHARACTERISTICS OF A UAV SEAPLANE IN TRANSITIONAL FLOW REGIMES	107
Izabela Żaczek, Bernadetta Kowalczyk DESIGN AND EXPERIMENTAL VALIDATION OF A PROPELLER FOR AN UNMANNED AERIAL VEHICLE WITH MTOW UP TO 25 KG	108
Anna Olszewicz, Jakub Kordowski MODELING AND ANALYSIS OF WING ICING ON A BOEING 737-800 AIRCRAFT USING ANSYS	109
Amar Kouadri, Embarek Douroum, Mokhtar Zaitri, Sofiane Khelladi, Samir Laouedj, Juan Pedro Solano CFD INVESTIGATION OF THERMAL MIXING ENHANCEMENT OF SHEAR-THINNING FLUIDS IN SHORT PASSIVE TLCCM MICROMIXERS	110
Embarek Douroum, Amar Kouadri, Sofiane Khelladi, Samir Llaouedj, Abdelylah Benazza, Mokhtar Zaitri, Juan Pedro Solano COMPARATIVE ANALYSIS OF PASSIVE PLANAR MICROMIXERS FOR NEWTONIAN AND NON-NEWTONIAN FLUID MIXING: A NUMERICAL STUDY	111
Aleksandra Zarubajko, Łukasz Omen, Maciej Majcher, Andrzej J. Panas CFD MODELING OF WATER AEROSOL FLOW IN AN ICING WIND TUNNEL	112

Aneta Misiak-Zawadzka, Maciej Majcher ANALYSIS OF THE INFLUENCE OF THE GROUND EFFECT ON THE BASIC AERODYNAMIC CHARACTERISTICS OF A WIG CRAFT WING	113
Rafał Kliza, Zbigniew Czyż, Konrad Pietrykowski, Paweł Magryta NUMERICAL INVESTIGATION OF THE AERODYNAMIC CHARACTERISTICS OF THE LUBLIN R-XIIID AIRCRAFT	114
<u>COMPUTER SIMULATIONS OF PROCESSES AND PHENOMENA</u>	115
Łukasz Grabowski, Jan Pytka, Zbigniew Czyż, Krzysztof Skiba MACHINE LEARNING-BASED PREDICTION OF AERODYNAMIC CHARACTERISTICS OF AN ELECTRIC UAV PROPULSION SYSTEM	115
Michał Cioch, Arkadiusz Gola ANALYSIS OF FACTORS AFFECTING PRODUCT PRICE MARGINS IN THE DISTRIBUTION CHAIN	116
Paweł Suchorab, Ewa Jakowiecka RESILIENCE ANALYSIS OF A WATER DISTRIBUTION NETWORK UNDER FAILURE SCENARIOS IN THE AQUARDIS VIRTUAL CITY	117
Łukasz Rykała, Karol Cieślík, Marcin Dejewski, Mirosław Przybysz ULTRA-WIDEBAND-BASED VELOCITY ESTIMATION WITH KALMAN FILTERING FOR FOLLOW-ME UNMANNED GROUND VEHICLE APPLICATIONS	118
Dariusz Kalinko, Marian Łopatka, Piotr Krogul, Rafał Typiak, Jarosław Duda APPARATUS FOR FIELD TESTING AND VALIDATION OF NUMERICAL MODELS OF MINE-SOIL INTERACTION UNDER WHEEL OR TRACK PRESSURE	119
Marcin Dejewski, Tomasz Muszyński, Lucjan Śnieżek, Dariusz Kalinko VALIDATION STUDIES OF EQUIVALENT STIFFNESS REPRESENTATION IN A SIMULATION MODEL OF A RIBBON PONTOON BRIDGE	120
Monty J Singh, Balwinder Sodhi A DOMAIN-AGNOSTIC FRAMEWORK FOR UNCERTAINTY-GUIDED HYBRID SIMULATION IN DIGITAL TWINS	121
Damian Bańkowski, Piotr Młynarczyk, Tomasz Milek THE USE OF DIGITAL VOLUME CORRELATION WITH COMPUTED TOMOGRAPHY TO ANALYZE DISPLACEMENT AND WALL THICKNESS OF MULTI-OPERATIONAL PRESSING OF CYLINDRICAL ALUMINUM EXTRUSIONS	122
Piotr Młynarczyk STUDY OF THE INFLUENCE OF ESD PROCESS PARAMETERS AND A COMPARATIVE ANALYSIS OF MICROSCOPY AND COMPUTED TOMOGRAPHY IN THE QUALITATIVE ASSESSMENT OF COPPER COATINGS ON AN ALUMINIUM SUBSTRATE.	123

Daniel Plisau, Grzegorz Łagód ENTROPY-BASED INDICES IN ECONOMIC AND SOCIAL RESEARCH	124
Albert Raczekiewicz, Magdalena Pilat-Rożek, Aleksandra Kozłowska, Grzegorz Łagód ANALYSIS OF MULTIDIMENSIONAL DATA CONTAINING PRECIPITATION VARIABILITY AND THE PRESENCE OF MICROORGANISMS IN THE BYSTRZYCA RIVER FOR ENVIRONMENTAL MONITORING PURPOSES	125
Michał Stanisławski, Aleksandra Kozłowska, Roman Babko, Grzegorz Łagód RECOGNIZING TESTACEA USING AUTOMATIC IMAGE ANALYSIS ALGORITHMS – EUGLYPHA AS AN EXAMPLE	126
Beata Surma, Grzegorz Łagód GIS-BASED AUTOMATION OF INPUT DATA PREPARATION FOR HYDRODYNAMIC STORMWATER SYSTEM MODELING	127
Diana Morzhak, Magdalena Pilat-Rożek, Aleksandra Kozłowska, Grzegorz Łagód THE USE OF SELECTED DEEP LEARNING METHODS FOR THE DETECTION AND CLASSIFICATION OF BIOLOGICAL OBJECTS ON DIGITAL IMAGES	128
Barbara Stefaniak, Dariusz Wójcik, Tomasz Rymarczyk STABLE CLASS-CONDITIONED QUANTISED VAE FOR SYNTHETIC LUNG DISEASE VOLUMES	129
Tomasz Rymarczyk, Paweł Kaleta, Marcin Dziadosz, Dariusz Wójcik, Michał Oleszek, Michał Styła AOA SENSORS AND CLUSTER TRIANGULATION FOR 3D INDOOR LOCALIZATION	130
Tomasz Rymarczyk, Marcin Dziadosz, Dariusz Wójcik, Mariusz Mazurek, Paweł Tchórzewski MONTE CARLO MODELLING OF LIGHT TRANSPORT FOR OPTICAL TOMOGRAPHY IN HETEROGENEOUS MEDIA	131
<u>FINITE ELEMENT METHOD (FEM)</u>	132
Jan Górecki, Krzysztof Wałęsa THE EFFECT OF TRANSITION RADIUS ON DRY ICE FLOW AND BOUNDARY FORCE DURING THE EXTRUSION PROCESS: AN ANALYTICAL-NUMERICAL-EXPERIMENTAL STUDY	132
Michał Rogala COMPOSITE FOAM BASED SANDWICH STRUCTURE SUBJECTED TO LOW-VELOCITY IMPACT	133
Radosław Kiciński, Bogdan Szturomski, Jamal Hamoud, Michał Grylewicz MODEL SIMPLIFICATIONS INFLUENCE ON A SMALL-CALIBRE PROJECTILE ARMOUR PENETRATION SIMULATIONS RESULTS	134

Daniel Bronisław Nycz, Rafał Gajda, Jacek Kühnl-Kinell, Adam Spurtacz FANCY FENCE - A NEW TYPE OF ANTI-TERRORIST RETRACTABLE GATE - DESIGN AND REAL CRASH TEST	135
Małgorzata Iwanek FEM-BASED ANALYSIS OF SOIL SUFFUSION TRIGGERED BY PIPELINE LEAKAGE	136
Quirino Estrada, Jose Manuel Cuenca Delgado, Eladio Martinez Rayon, Elva Reynoso, Alejandro Rodriguez-Mendez, Aztlan Bastarrachea, Jesus Silva, Manuel Nandayapa EFFECT OF THE CROSS-SECTION ON THE ENERGY ABSORPTION AND BENDING BEHAVIOR OF BENT TUBES	137
Jarosław Zubrzycki, Quirinio Estrada, Magda Wlazło EQUIVALENT STATIC FINITE ELEMENT ANALYSIS OF HUMAN SKULL LOADING UNDER CONDITIONS REPRESENTATIVE OF MOTORCYCLE COLLISIONS	139
Bartosz Łata, Jacek Czarnigowski, Miłosz Chwiejczak, Wiktor Iskra, Iga Kopeć DESIGNING VEHICLE STRUCTURES USING MATERIALS WITH A LOW CARBON FOOTPRINT	140
Paweł Wysmulski, Konrad Pietrykowski, Hubert Dębski, Michał Rogala, Jakub Paśnik, Mirosław Ferdynus, Kuba Rosłaniec DEVELOPMENT OF A DIGITAL CAD MODEL OF THE LUBLIN R- XIIID AIRCRAFT	141
<u>MATERIAL PROPERTIES AND STRUCTURE RESEARCH</u> <u>METHODS</u>	143
Robert Szczepaniak, Zuzanna Wilkosz, Robert Bąbel, Grzegorz Woroniak THE ROLE OF CARBON ADDITIVES IN SHAPING THE MECHANICAL PROPERTIES OF ABS AND ASA POLYMER FILAMENTS IN THE FDM PROCESS	143
Damian Jokiel, Jan Górecki PRELIMINARY RESEARCH OF DENSITY INFILL INFLUENCE ON THE TENSILE STRENGTH OF THERMOPLASTIC POLYURETHANE (TPU) 3D PRINTED ELEMENTS IN FUSED DEPOSITION MODELING (FDM) METHOD	144
Żaneta Anna Mierzejewska, Nataša Trtić, Radmila Arbutina DEGRADATION BEHAVIOR OF RESIN-BASED COMPOSITES UNDER SIMULATED ORAL CONDITIONS: A COMPARATIVE STUDY OF MICROHARDNESS, SURFACE ROUGHNESS, AND WATER-RELATED PROPERTIES	145
Piotr Maciak, Eryc Witkowski INFLUENCE OF SKIN MATERIAL AND SURFACE TREATMENT ON AERODYNAMIC PERFORMANCE	146

Wiktorykowsk, Łukasz Gierz RESULTS OF LABORATORY TESTS OF THE STATIC AND DYNAMIC FRICTION COEFFICIENTS OF FERTILIZER GRANULES AGAINST THE STRUCTURAL MATERIALS OF SEED DRILLS USING A ROTARY TEST STAND	147
Jacek Janiszewski, Andrzej Komorek, Rafał Bieńczyk, Daniel Śliwiński THE INFLUENCE OF THE MOLD SIZE ON PROPERTIES OF GFRP MADE BY INFUSION METHOD	148
Filip Wątarek, Patryk Lorenc, Ireneusz Dominik NON-DESTRUCTIVE ANCHOR CONDITION CLASSIFICATION IN UNDERGROUND MINING USING FFT ANALYSIS AND TRANSFER LEARNING	149
Magdalena Pańnikowska-Łukaszuk, Zbigniew Suchorab EVALUATION OF MOISTURE CONTENT IN 600 AERATED CONCRETE USING TDR SENSORS WITH POLYLACTIDE HOUSING	150
Jacek Czarnigowski, Jakub Jarosz, Magda Drożdżel-Jurkiewicz, Adrian Wróbel MECHANICAL PROPERTIES OF FLAX FIBRE-REINFORCED BIO- COMPOSITES	151
Maciej Kowalski, Łukasz Omen, Andrzej J. Panas NUMERICAL ANALYSIS OF HEAT TRANSPORT IN DISPERSIVE COMPOSITES WITH MICROENCAPSULATED PCMS: INFLUENCE OF VOLUME FRACTION, ELEMENTARY CELL SIZE AND MODEL DIMENSIONALITY	152
Żaneta Anna Mierzejewska, Stanisław Dzielak, Anna Falkowska MICROHARDNESS–TOUGHNESS TRADE-OFF AND ANISOTROPY REDUCTION IN DMLS Ti6Al4V INDUCED BY POST-PROCESSING HEAT TREATMENT	153
Szymon Karski, Dariusz Chocyk, Mirosław Szala INFLUENCE OF DEPOSITION RATE ON MICROSTRUCTURE AND MECHANICAL PROPERTIES OF TIN LAYERS: EXPERIMENT AND SIMULATION	154
Michał Cajzner, Leszek Łatka APPLICATION OF IMAGE ANALYSIS FOR THE ASSESSMENT OF CAVITATION EROSION PHENOMENA FOR THE THERMAL SPRAYED COATINGS	155
Wojciech Pudło, Grzegorz Kozłowski, Mateusz Mucha EFFECTIVENESS OF SELECTED NDT METHODS FOR INSPECTION OF A 12-PLY AEROSPACE CFRP LAMINATE	156
Barbara Stefaniak, Michał Gołąbek, Dariusz Wójcik, Monika Kulisz, Tomasz Rymarczyk PORTABLE MULTICHANNEL ULTRASONIC TOMOGRAPHY FOR THREE-DIMENSIONAL IMAGING OF CONCRETE DEFECTS	157

Michał Sasiadek, Maciej Niedziela, Waldemar Woźniak, Tomasz Jachowicz, Jarosław Jajczyk, Arkadiusz Koziół, Tomasz Tramś EFFECT OF MATERIAL COMPOSITION AND EMBOSsing PROCESS PARAMETERS ON THE PUNCTURE RESISTANCE OF THREE-LAYER POLYETHYLENE FILMS WITH RECYCLED CONTENT	158
Waldemar Woźniak, Maciej Niedziela, Michał Sasiadek, Tomasz Jachowicz, Jarosław Jajczyk, Arkadiusz Koziół, Tomasz Tramś DIRECTIONAL ANISOTROPY OF TEAR RESISTANCE IN EMBOSSED THREE-LAYER POLYETHYLENE FILMS CONTAINING RECYCLED MATERIAL	159
Maciej Niedziela, Waldemar Woźniak, Michał Sasiadek, Tomasz Jachowicz, Jarosław Jajczyk, Arkadiusz Koziół, Tomasz Tramś IDENTIFICATION OF A ROBUST EMBOSsing PROCESS WINDOW FOR THREE-LAYER RECYCLED POLYETHYLENE FILMS BASED ON MULTIPLE MECHANICAL PERFORMANCE CRITERIA	160
Mariusz Klonica, Oskar Sarnecki IMPLEMENTATION OF ADDITIVE MANUFACTURING TECHNOLOGY IN THREADED FASTENERS	161
Jarosław Piątkowski LASER SURFACE TREATMENT OF ALSI11CUN1MG PISTON ALLOY	162
Mikołaj Sowa, Mirosław Szala STAINLESS STEEL WELD OVERLAYS PROPERTIES AND ABRASIVE WEAR RESISTANCE	163
<u>PRODUCTION ENGINEERING, MANAGEMENT AND QUALITY CONTROL</u>	164
Jakub Pizoń AN AUDITABLE LLM-RAG DIGITAL QUALITY TWIN SUPPORTING SIMULATION-BASED VALIDATION AND SAFER DEFECT CONTROL IN INDUSTRY 4.0 AND 5.0 FOR PRODUCTION AND TECHNOLOGY MANAGEMENT	164
Adam Deptuła, Patryk Machnik AN INTEGRATED BWM- FUZZY TOPSIS MODEL FOR STEEL STRUCTURE MANUFACTURER SELECTION: A CASE STUDY	165
Jarosław Mądro, Hubert Dębski THE LUBLIN R-XIIID AIRCRAFT – HISTORICAL BACKGROUND AND STRUCTURAL CHARACTERISTICS	166
Michał Styła, Przemysław Adamkiewicz ENERGY-EFFICIENT UWB LOCALIZATION WITH MULTILATERATION FOR WAREHOUSE ASSET TRACKING	167
Mariusz Mazurek, Krzysztof Król, Tomasz Rymarczyk, Monika Kulisz, Edward Kozłowski, Grzegorz Kłosowski NAR AND LSTM-DEPENDENT PREDICTION FOR EARLY WARNING OF ERRORS IN PROCESS TOMOGRAPHY	168

<u>TECHNOLOGY MANAGEMENT IN ENERGY ACQUISITION PROCESSES</u>	169
Aleksandra Świadek, Łukasz Warguła, Weronika Wiatrowska, Bartosz Wieczorek	169
REVIEW OF THE USE OF EMG SIGNALS IN ENGINE CONTROL SYSTEMS FOR ENERGY EFFICIENCY IMPROVEMENT	
Olga Orynycz	170
SEASONAL VARIATIONS OF RENEWABLE ENERGY IN POLAND	
Adam Kuśmierowski, Krzysztof Skiba, Dariusz Kuś, Jarosław Sikora	171
EXPERIMENTAL ANALYSIS OF CURRENT-VOLTAGE CHARACTERISTICS AND STATISTICAL PARAMETERS OF THE EMISSION CURRENT AS A FUNCTION OF TEMPERATURE AND ANODE WORK FUNCTION IN A THERMIONIC ENERGY CONVERTER	
<u>COMPUTER SIMULATIONS AND APPLICATIONS IN ELECTRICAL ENGINEERING</u>	172
Jakub Drzał, Daniel Kleczyński, Bartosz Pawłowicz	172
ADAPTIVE TRAFFIC SIGNAL CONTROL WITH A PPO-TRANSFORMER ARCHITECTURE IN COMPLEX TRAFFIC SYSTEMS	
Mariusz Mazurek, Krzysztof Król, Edward Kozłowski, Monika Kulisz, Konrad Niderla, Grzegorz Kłosowski, Tomasz Rymarczyk	173
ADAPTIVE INDUSTRIAL TOMOGRAPHIC RECONSTRUCTION THROUGH BIDIRECTIONAL LSTM-GUIDED ENSEMBLE SELECTION	
Grzegorz Kłosowski, Tomasz Rymarczyk, Monika Kulisz, Konrad Niderla, Michał Oleszek, Paweł Olszewski	174
MEASUREMENT-CONSISTENT HYBRID NEURAL RECONSTRUCTION FOR ELECTRICAL IMPEDANCE TOMOGRAPHY	
Monika Kulisz, Grzegorz Kłosowski, Tomasz Rymarczyk, Konrad Niderla	175
MULTI-HEAD NEURAL RECONSTRUCTION OF 2D EIT IMAGES FOR INDUSTRIAL REACTOR MONITORING	
Mariusz Mazurek, Tomasz Rymarczyk, Marcin Dziadosz, Dariusz Wójcik, Michał Oleszek	176
DIRECT NEURAL RECONSTRUCTION OF URINARY BLADDER IMAGES FROM WEARABLE ELECTRICAL IMPEDANCE TOMOGRAPHY DATA	
Mariusz Mazurek, Tomasz Rymarczyk, Dariusz Wójcik, Marcin Dziadosz	177
MULTIMODAL NEURAL RECONSTRUCTION FOR HYBRID ULTRASOUND-IMPEDANCE TOMOGRAPHY OF THE LOWER URINARY TRACT	

Dominik Gnaś, Tomasz Rymarczyk, Dariusz Wójcik, Michał Oleszek
MULTIMODAL EITS AND OPTICAL SENSING FOR NON-INVASIVE
GLUCOSE MONITORING

178

CMES'26 draft version

ABOUT THE CONFERENCE

The XI International Conference on Computational Methods in Engineering Science (CMES’26) continues the tradition of bringing together researchers and practitioners to exchange knowledge and discuss advances in computational methods and their applications in engineering. The eleventh edition will be held on November 18–20, 2026, for the second time in Cedzyna near Kielce, Poland. The conference is jointly organized by the Polish Society for the Promotion of Knowledge, Polish Society of Engineering Sciences, Lublin University of Technology (Faculty of Mechanical Engineering, Faculty of Electrical Engineering and Computer Science, Faculty of Management, and Faculty of Environmental Engineering) and the Polish Air Force University (Faculty of Aviation).

A Decade of Growth and Achievements

Over ten editions, the CMES Conference has gradually broadened its thematic scope and attracted participants from an increasing number of academic and research centers in Poland and abroad. The event has been held in various cities across the Lublin Voivodeship — including Lublin, Kazimierz Dolny, Zamość, and Puławy/Dęblin — as well as in the Świętokrzyskie Voivodeship (Sandomierz), as shown in Figure 1. In 2020, due to the COVID-19 pandemic, the conference was held online for the first time, rather than in Lviv (Ukraine). Until then, the conference will be held in a hybrid form – scientific committee members and other participants can attend it remotely via an online platform. The choice of locations for individual editions was intended to highlight the cultural and historical richness of the Lublin Voivodeship and its surroundings.




Figure 1. Timeline of the decade of CMES conference locations

From year to year, not only did the number of participants increase, but also the academic quality and international profile of the event. The total number of participants over the decade of CMES is approximately 900, and the annual counts of participants and presented topics (oral and poster presentations) are shown in Figure 2. Considering the 770 subjects presented over the decade of CMES, 38% were oral presentations. Moreover, the scientific

committee of CMES has increased over the decade, as shown in Figure 3, and the average number of foreign members is 39%. The current international CMES community, comprising both participants and scientific committee members from Poland and foreign countries, is shown in Figure 4. The first edition, held in 2016, attracted only a few dozen participants, mainly from Polish academic institutions. In the following years, the number of attendees steadily increased, expanding the CMES community not only from Polish technical universities, but also from scientists from five continents: Africa, Asia, Europe, South America, and North America (see Figure 4).




Figure 2. Statistics of CMES 2016-2025 participants and presented titles (orals + posters)




Figure 3. Statistics of CMES 2016-2025 Polish and foreign Scientific Committee Members




Figure 4. CMES community represented by CMES scientific committee members and conference participants over the 2016-2025 period [created with Datawrapper]

The decade of CMES tradition is, above all, a story of a worldwide community of young scientists, experienced researchers, and engineers who have co-created this event by sharing their knowledge, experience, and passion for science. The conference has become a place to integrate the scientific community and an inspiration for collaboration among universities, research centers, and industry.

Scientific Scope and Vision

The 2026 edition is expected to bring together around 150 experts, including keynote speakers from abroad and industry representatives. As in previous years, the conference covers a wide spectrum of topics, including but not limited to:

- analysis and modeling of engineering processes,
- computer-aided design, simulation, and optimization,
- artificial and computational intelligence,
- Computational Fluid Dynamics (CFD),
- Finite Element Method (FEM) and related numerical approaches,
- experimental and computational methods in materials and structural research,
- production engineering and quality control,
- technology management in energy and sustainable processes.

The program of CMES’26 will include plenary lectures, thematic sessions, and industry presentations.

The primary goal of CMES is to highlight emerging trends in computational engineering methods and to enhance the visibility of ongoing research results. Throughout its history, the conference has contributed to the dissemination of knowledge through its proceedings and subsequent publications in reputable scientific journals. After a positive peer-review process, selected papers from CMES’26 will be considered for publication in journals such as:

- Advances in Science and Technology Research Journal
- Acta Mechanica et Automatica
- Archives of Electrical Engineering
- Applied Computer Science
- Journal of Ecological Engineering
- Management Systems in Production Engineering
- Advances in Materials Science

Towards the Future

The 10th anniversary of CMES is both a celebration of the past and a commitment to the future. Over the past decade, the conference has established itself as an interdisciplinary platform that bridges research fields and fosters cooperation between academia and industry — both nationally and internationally.

In the coming years, the CMES Organizing Committee plans to further strengthen the international character of the conference by attracting an even greater number of participants. Particular emphasis will be placed on developing closer cooperation with industry, so that the conference becomes a platform for dialogue and the initiation of projects with significant practical impact. These efforts are expected to result in an increase in the number of high-quality scientific publications as well as the establishment of lasting relationships between universities, research institutes, and companies. CMES enters its second decade with the ambition of continued growth and development.

More information about CMES'26 and previous editions is available on the official website:

 www.cmes.pl

Follow us:

 Facebook: www.facebook.com/ConferenceCMES

 LinkedIn: www.linkedin.com/company/conference-cmes/

CMES’26 SCIENTIFIC COMMITTEE

Honorary Committee

Professor Zbigniew PATER – Rector of Lublin University of Technology, Poland

Brig. Gen. Pilot Krzysztof SZYMANIEC, PhD, Eng. – Rector-Commandant of the Polish Air Force University, Poland

Scientific Committee

Bartłomiej Ambrożkiewicz, Lublin University of Technology, Poland

Michał Awtoniuk, Warsaw University of Life Sciences, Poland

Önder Ayer, Trakya University, Turkey

Paweł Baranowski, Military University of Technology, Poland

Paul Bere, Universitatea Tehnica Cluj-Napoca, Romania

Jarosław Bieniaś, Lublin University of Technology, Poland

Gabriel Borowski, Lublin University of Technology, Poland

Ricardo Branco, University of Coimbra, Portugal

Piotr Budzyński, Lublin University of Technology, Poland

Paweł Chojnacki, Polish Society of Mechanical Engineers and Technicians, Poland

Tomasz Cieplak, Lublin University of Technology, Poland

Tomasz Czerwiński, Polish Air Force University, Poland

Hubert Dębski, Lublin University of Technology, Poland

Kazimierz Drozd, Lublin University of Technology, Poland

Marta Dziuba-Kozieł, Lublin University of Technology, Poland

Łukasz Grabowski, Lublin University of Technology, Poland

Quirino Estrada-Barbosa, Autonomous University of Ciudad Juarez, Mexico

Daniele Fanteria, University of Pisa, Italy

Gabriel Fedorko, Technical University of Košice, Slovakia

Dariusz Fydrych, Gdańsk University of Technology, Poland

Dominik Gawle, Dassault Systemes sp. z o.o., Poland

Łukasz Gierz, Poznań University of Technology, Poland

Arkadiusz Gola, Lublin University of Technology, Poland

Paweł Golda, Polish Air Force University, Poland

Muharrem Hilmi Aksoy, Konya Technical University, Turkey

Gürkan İrsel, Trakya University, Turkey

Józef Jonak, Lublin University of Technology, Poland

Ewa Jonda, Silesian University of Technology, Poland

Jerzy Józwik, Lublin University of Technology, Poland

Mariusz Kamiński, Lublin University of Technology, Poland

Paweł Karczmarek, Lublin University of Technology, Poland

Paweł Karpiński, University of Life Sciences in Lublin, Poland

Radosław Kiciński, Polish Naval Academy, Poland

Mariusz Klonica, Lublin University of Technology, Poland
Grzegorz Kłosowski, Lublin University of Technology, Poland
Grzegorz Koziel, Lublin University of Technology, Poland
Michał Kuciej, Białystok University of Technology, Poland
Paweł Kuraś, Rzeszów University of Technology, Poland
Sergio Luján-Mora, University of Alicante, Spain
Grzegorz Łagód, Lublin University of Technology, Poland
Leszek Łatka, Wrocław University of Science and Technology, Poland
Edyta Łukasik, Lublin University of Technology, Poland
Wojciech Macek, Gdańsk University of Technology, Poland
Tomasz Milek, Kielce University of Technology, Poland
Marek Miłosz, Lublin University of Technology, Poland
Vieroslav Molnár, Technical University of Košice, Slovakia
Łukasz Omen, Military University of Technology, Poland
Olga Orynycz, Białystok University of Technology, Poland
Dogus Ozkan, Turkish Naval Academy, Turkey
Małgorzata Pawłowska, Lublin University of Technology, Poland
Dariusz Perkowski, Białystok University of Technology, Poland
Jarosław Piątkowski, Silesian University of Technology, Poland
Adam Piechna, Symkom sp. z o.o., Poland
Jakub Pizoń, Lublin University of Technology, Poland
Paweł Powroźnik, Lublin University of Technology, Poland
Bartosz Przysucha, Lublin University of Technology, Poland
Michał Rogala, Lublin University of Technology, Poland
Patryk Różyło, Lublin University of Technology, Poland
Tomasz Rymarczyk, Netrix S.A., Poland
Dariusz Rzońca, Rzeszów University of Technology, Poland
Sylwester Samborski, Lublin University of Technology, Poland
Petra Sauer, Beuth Hochschule für Technik Berlin, Germany
Andrzej Seweryn, Gdańsk University of Technology, Poland
Jashanpreet Singh, Thapar Institute of Engineering and Technology, India
Łukasz Skowron, Lublin University of Technology, Poland
Maria Skublewska-Paszkowska, Lublin University of Technology, Poland
Egemen Sulukan, Istanbul Gedik University, Turkey
Maciej Sulowicz, Cracow University of Technology, Poland
Robert Szczepaniak, Polish Air Force University, Poland
Bogdan Szturomski, Polish Naval Academy, Poland
Tomasz Szymczyk, Lublin University of Technology, Poland
Jakub Takosoglu, Kielce University of Technology, Poland
Ualsher Tukeyev, Al-Farabi Kazakh National University, Kazakhstan
Paolo Sebastiano Valvo, University of Pisa, Italy
Łukasz Warguła, Poznań University of Technology, Poland
Mirosław Wendeker, Lublin University of Technology, Poland

Bartosz Wieczorek, Poznań University of Technology, Poland

Bogdan Wit, Polish Information Processing Society, Poland

Rafał Wojciechowski, Poznań University of Technology, Poland

Paweł Wysmulski, Lublin University of Technology, Poland

Tomasz Zahorski, Polish Air Force University, Poland

CMES'26 draft version

CMES'26 draft version

CMES’26 ORGANIZING COMMITTEE

Zbigniew Czyż, **Chair**

Monika Kulisz, Vice Chair

Mirosław Szala, Vice Chair

Marcin Badurowicz

Wojciech Cel

Katarzyna Falkowicz

Justyna Kujawska

Jakub Pizoń



CMES’26 Organizing Committee structure and team members

from the left: J. Pizoń, W. Cel, J. Kujawska, Z. Czyż,
K. Falkowicz, M. Szala, M. Kulisz, M. Badurowicz

CMES'26 draft version

ORGANIZERS



POLITECHNIKA
LUBELSKA
LUBLIN UNIVERSITY
OF TECHNOLOGY



POLISH AIR FORCE UNIVERSITY



POLISH
ASSOCIATION FOR
KNOWLEDGE
PROMOTION



Polskie Stowarzyszenie
Nauk Inżynieryjnych
Polish Society
of Engineering Sciences

HONORARY PATRONAGES



HONOROWY PATRONAT
POLITECHNIKI
LUBELSKIEJ



Rector-Commandant PAFU
Brig. Gen. Pilot Krzysztof SZYMANIEC, PhD, Eng.

CMES'26 draft version

PATRONAGES



CMES'26 draft version

ASSOCIATED EVENTS

RECONSTRUCTION AND AERODYNAMIC INVESTIGATION OF THE LUBLIN R-XIIID AIRCRAFT – CURRENT PROGRESS AND PROJECT DEVELOPMENT

This year's edition of CMES'26 will feature a special session entitled "Application of Numerical Methods in the Reconstruction of the Lublin R-XIIID Aircraft – Current Progress and Project Development," dedicated to presenting the current progress of the project and the application of numerical and experimental methods in the aircraft reconstruction process.

CMES'26 draft version

CMES’26 KEYNOTE SPEAKERS



DATA AND MODELS USED IN ENGINEERING APPLICATIONS

Hasilova Kamila, Ph.D.

Department of Quantitative Methods,
University of Defence,
Brno, Czech Republic

ABSTRACT

Data and models present one of the first steps in statistical modelling, which is then followed by applications in decision-making or maintenance processes. With a focus on the non-parametric methods for the assessment, modelling and simulation of data in the fields of military and civil protection, we present models that are used to solve critical infrastructure and systems of physical protection tasks. Some problems require new perspectives to solve, including the type of data involved. Therefore, we provide an introduction to the so-called circular data and functional data, which have different characteristics. The overview of the models and data types demonstrates the wide range of possibilities in statistical modelling. Statistical methods are viewed as a tool that makes it possible to extract meaningful information from available data drawn from various areas of the field. This information can then be used for modelling and simulating the processes under study.

SPEAKER BIOGRAPHY

Kamila Hasilová works at the University of Defence in Brno, Czech Republic. She received her Ph.D. degree in Probability, Statistics and Mathematical Modelling from Masaryk University in 2012, and the habilitation degree in the field of Military and Civil Protection in 2020. She specialises in the statistical methods and mathematical modelling in defence and protection areas, focusing on data analysis, non-parametric statistical methods and statistical modelling. She has presented her results in peer-reviewed journal, about 70 papers, and at international conferences, about 40 oral and poster presentations.

CMES'26 draft version

MULTIPHYSICS ANALYSIS OF ELECTROMAGNETIC- THERMAL COUPLING IN CST STUDIO SUITE AND CO-SIMULATION WITH ABAQUS



Rafał M. Wojciechowski,
D.Sc., Technia, Poland



Dominik Gawle, M.Eng.
SIMULIA Sales Representative
at Dassault Systèmes

ABSTRACT

The continuous push for higher power density and miniaturization in modern electromechanical systems—ranging from high-frequency electronics to high-power electrical machines—requires a rigorous approach to Multiphysics modelling. Thermal management is considered a critical bottleneck in the design process, as electromagnetic losses directly impact temperature distribution, which in turn alters material properties and structural integrity. In this presentation, the advanced capabilities of **CST Studio Suite** in simulating coupled electromagnetic (EM) and thermal phenomena are analysed, alongside its integration with **Abaqus FEA** for comprehensive structural analysis.

In the first part of the study, the **EM-Thermal coupling** within the CST Studio Suite environment is examined. By utilizing integrated Multiphysics Solvers, bi-directional simulations are performed, where electromagnetic losses (such as surface losses, volumetric losses, or eddy currents) are treated as heat sources for the thermal solver. The workflow accounts for temperature-dependent material properties, ensuring that high fidelity is maintained in predicting the thermal behavior of components under various operating conditions.

The second part of the work highlights the synergy between **CST Studio Suite** and **Abaqus** within the Dassault Systèmes SIMULIA portfolio. While CST is recognized for its excellence in EM and thermal analysis, certain applications—such as induction heating,

power electronics cooling, or transformer design—demand a more profound investigation into mechanical effects. The **SIMULIA Co-Simulation Engine** is presented as a solution that facilitates the transfer of temperature fields and electromagnetic forces from CST to Abaqus. Through this coupling, several key analyses are enabled:

- Precise calculation of thermal stresses induced by electromagnetic heating.
- Structural deformation analysis of components subject to high-intensity fields.
- Optimization of cooling systems through combined CFD and mechanical assessments.

It is demonstrated by the authors how this integrated Multiphysics workflow allows for the reduction of physical prototyping and minimizes the risk of over-design. By leveraging the unified power of CST and Abaqus, the gap between electromagnetic performance and mechanical reliability is bridged, ultimately accelerating the time-to-market for innovative products.

SPEAKER BIOGRAPHY

Assoc. Prof. Rafal M. Wojciechowski received the MSc degree in Electrical Engineering from the Poznan University of Technology in 2005, PhD and D.Sc. degrees in 2010 and 2017, respectively. His scientific interests are focused on numerical modeling and analysis of electrical machines and devices using the multi-stage approach of the finite elements method (FEM). Over 70 papers on electrical machines, electrical and electronic devices, and systems of wireless transmission power have been published by him. He is a co-author of 3 international patents and 9 patent applications. For 3 years, he has cooperated with Technia Poland as a Simulation expert in the EM field.

Dominik Gawle has been associated with the CAD/SIM/CAM/PDM software market for engineers for 20 years. Extensive knowledge of Dassault Systèmes solutions has been acquired by him through various technical and sales roles. He is a graduate of Cracow University of Technology in the field of Automation and Robotics, as well as a postgraduate of AGH University of Science and Technology in Project Management. Currently, he is responsible for leading projects and developing sales in the SIMULIA domain, supporting Dassault Systèmes clients and partners in Poland.



LIVING ON THE EDGE: EDGE AI FOR SPEED, PRIVACY, AND SELF-GOVERNANCE

Marcin Badurowicz, PhD, Eng.
Lublin University of Technology

ABSTRACT

Edge computing is an approach to data processing in which computation is moved closer to where data is generated, rather than relying exclusively on centralized infrastructure. This shift enables devices to process, analyze, or act on data locally, reducing the need to continuously transmit large amounts of data to remote servers. With the growing capabilities of embedded hardware and AI models, this approach also enables Edge AI, running machine learning and artificial intelligence algorithms directly on edge devices.

In this plenary lecture, it will be shown how edge processing is being applied to data processing in various applications, what challenges and limitations can be encountered, and why this approach is becoming increasingly interesting. The lecture will focus on two main pillars: the first is speed and latency, where edge processing and Edge AI can outperform traditional approaches by enabling fast, local decision-making, even when more accurate or computationally powerful solutions are available in the cloud; the second is privacy and self-governance: in today's world, transferring and sharing data can introduce significant business, regulatory, and legal risks.

The lecture will also highlight the trade-offs involved in moving computation to the edge, including limited computational and energy resources, model complexity, reliability, scalability, and the challenges of deploying and maintaining distributed AI systems.

SPEAKER BIOGRAPHY

Marcin Badurowicz works at the Lublin University of Technology in Poland. He received his Ph.D. in computer science in 2019 from the Polish-Japanese Academy of Information Technology for his work on pothole detection in road transport with the usage of mobile devices and on-device processing. He is the author or co-author of more than 30 papers, and his work concentrates on various aspects of anomaly detection, language processing, and XR technologies.

CMES'26 draft version



COMPUTATIONAL INTELLIGENCE FOR MANAGING MODERN PRODUCTION SYSTEMS

Jakub Pizoń, PhD, Eng.
Lublin University of Technology

ABSTRACT

The aim of this plenary lecture is to show how computational intelligence is currently applied to support the management of modern production systems and to identify areas where these solutions can create practical value and new research opportunities. The lecture focuses on specific production processes, including planning and scheduling, quality control, maintenance, intralogistics and human-machine collaboration.

For each area, selected real-world examples will illustrate what operational problem is addressed, what data are used, which computational methods are applied and what decisions or activities they support. Particular attention will be given to artificial intelligence, predictive methods, digital twins and intelligent decision-support systems.

The lecture will also discuss practical implementation conditions, including data availability, integration with existing production systems, model reliability and organisational adoption. By linking computational methods with concrete production processes and managerial decisions, the presentation aims to provide participants with an application-oriented perspective and inspire further research into emerging uses of computational intelligence in manufacturing.

SPEAKER BIOGRAPHY

Experienced Business Solutions Architect, researcher and academic lecturer with over fourteen years of experience delivering business system solutions for enterprises and public institutions. Demonstrated history of successfully supporting public procurement processes and implementing advanced technologies. Skilled in business architecture, project management, data analysis and leading cross-functional teams, with a proven ability to deliver strategic solutions in complex environments.

Active in research and teaching in process management, artificial intelligence and modern information technologies for Industry 4.0 and 5.0. Leads R&D projects applying large language models (LLMs) in medical transcription and project management. Author of more than forty academic publications on integrating technology with business processes and a regular speaker at industry conferences.

Certified in project management (IPMA Level D, PSM I, AgilePM Foundation), business analysis (ECBA by IIBA) and software estimation (COSMIC Foundation). Holds a PhD in Mechanical Engineering focused on business and technology integration. Combines the perspectives of an IT practitioner, R&D innovator and educator to address the real-world challenges organisations face in the era of digital transformation.

CMES'26 draft version



EVALUATION OF THE EFFECTIVENESS OF RADAR DRONE DETECTION: THE APPLICATION OF COMPUTER SIMULATIONS

Przemysław Turos,
Symkom Sp. z o.o.

ABSTRACT

The evolving threat landscape on NATO's eastern flank highlights the critical necessity of adapting air defense capabilities to counter Unmanned Aerial Vehicles (UAVs). Small and medium-sized drones present significant detection challenges due to reduced radar cross-sections (RCS), complex material compositions, low-altitude flight profiles, and rapidly evolving operational tactics. The presentation introduces a multidisciplinary methodology utilizing advanced engineering computer simulations to evaluate and optimize radar detection performance against low-observable UAV targets without relying solely on costly field testing.

The proposed framework integrates a multi-stage workflow: first, detailed 3D electromagnetic target modeling, high-frequency RCS prediction via Shooting and Bouncing Ray method, mission-level operational simulations incorporating topography, atmospheric attenuation, dynamic flight trajectories, and electronic warfare (EW) conditions and finally, flight-test data analysis for radar calibration.

The results demonstrate that mission-level digital simulations effectively identify coverage gaps, quantify detection probabilities, evaluate jamming resilience, and enable optimized radar placement and signal parameters. This integrated virtual testing approach serves as a cost-effective, scalable decision-support tool for modern air defense design, threat forecasting, and tactical doctrine development against evolving unmanned aerial systems.

SPEAKER BIOGRAPHY

Przemysław Turos, graduated from Warsaw University, the Geography and Regional Studies Department. He completed postgraduate studies in Aviation Management at the National Defense Academy in Warsaw. He has wide, long term experience in Remote

Sensing and Geographical Information Systems applications, data mining, processing and analysis, as well as in the field of Digital Mission Engineering.

Previously held the position of the Chief Operating Officer in GEOSYSTEMS Polska. Since 2016 runs Topologic Consulting, specialized in advisory and implementation in the field of aerial and satellite monitoring systems and data fusion in various domains. In 2019 the company become the Polish Agent of Analytical Graphics Inc., producer of DME solutions, currently part of Ansys Inc., a producer of engineering simulation software. Closely cooperates with Symkom Sp. z o.o. an Ansys Channel Partner in Poland as sub-distributor.

CMES'26 draft version

ABSTRACTS

ANALYSIS OF ENGINEERING PROCESSES

THEORETICAL AND EXPERIMENTAL ASPECTS OF PLASTIC FORMING – A REVIEW OF RESEARCH RESULTS

Tomasz Milek, Faculty of Mechatronics and Mechanical Engineering, Kielce University of Technology, tmatm@tu.kielce.pl

Abstract: This paper is a review and presents the results and analysis of the author's extensive research into the metal forming of sheet metal, rods, and tubes using various technological parameters. The research utilized both its own laboratory stands and commercial computer software. Test@Motion (from the LaborTech company) and POM16 were used for the experiments. However, QFORM-2D software was used for modeling processes in the field of volumetric metal forming (such as extrusion, pushing, and die forging). The experimental investigations were conducted on testing machines: an electric press with a maximum load of 20 kN (0.5 metrological class for force and displacement measurement), a hydraulic press with a load of 200 kN (1 metrological class), and a hydraulic press with a load of 1 MN (1 metrological class). Additionally, rolling mills were used: a laboratory mill for longitudinal rolling and an industrial mill for perpendicular rolling, respectively. The analysis of the results covers the following tube forming processes: hydroforming (hydromechanical bulge forming), perpendicular rolling with internal shaping tools, bulge forming, and necking; sheet metal forming processes: deep drawing, redrawing, flanging, ironing, blanking, longitudinal rolling; and bar forming processes: pushing, forward extrusion, backward extrusion, die forging. The conclusions from the research are utilitarian in nature and may be helpful in designing the discussed metal forming processes in industrial practice.

Keywords: metal forming, technological parameters, forming processes from metal sheets, pipes and bars

EVALUATING HYDRODYNAMIC CAVITATION FOR INCREASE OF BIODEGRADABILITY OF HERBAL WASTE: A MULTI-CRITERIA APPROACH

Magdalena Lebiocka, Faculty of Environmental Engineering and Energy, Lublin
University of Technology, m.lebiocka@pollub.pl

Jerzy Montusiewicz, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, j.montusiewicz@pollub.pl

Agnieszka Montusiewicz, Faculty of Environmental Engineering and Energy, Lublin
University of Technology, a.montusiewicz@pollub.pl

Aleksandra Szaja, Faculty of Environmental Engineering and Energy, Lublin
University of Technology, a.szaja@pollub.pl

Abstract: This paper is focused on the issue of selecting the operational parameters of the hydrodynamic cavitation (HC) that provide a maximum increase in the biodegradability of herbal waste with possibly low energy demand. To achieve this goal, the Multi-criteria Determination of Recommended Variants (MCDRV) method was applied, which allows for selecting the most advantageous HC conditions taking into account a variety of, sometimes conflicting, indicators of the process evaluation. The typical inference methods proved useless in determining which of the runs could be recommended due to the complexity of the experimental data, as well as the plethora of evaluation criteria expressed in different units, as the best solution. Using MCDRV, a multi-criteria analysis was performed for 21 detailed variants in order to select the optimal HC conditions that fulfill prior assumptions of the study. For searching for the best variant or variants of HC, the following criteria were defined: BOD/COD, SCOD/COD, and SCOD, which were maximized, and the others, i.e., COD, BOD, phenols concentration, and energy consumption, which were minimized. Both the seven-criteria and five-criteria evaluations of 21 variants obtained in the experiment showed that when adopting the same and different values of the importance of individual criteria, some variants are never selected as a compromise. The variant that was repeatedly selected as a compromise solution, independent of the values of the weight of individual criteria and the number of criteria, was the variant for which the HC time was 10 minutes and the cavitation inlet pressure was 3.5 bar. The multi-criteria assessment indicated that such operational conditions should be recommended for the efficient HC process of herbal waste.

Keywords: hydrodynamic cavitation, herbal waste, biodegradability, multi-criteria analysis

ASSESSMENT OF THE CARBON FOOTPRINT OF BIOCHAR PRODUCTION FROM SEWAGE SLUDGE USING CALCULATION METHODS

Wojciech Cel, Faculty of Environmental Engineering and Energy, Lublin University
of Technology, w.cel@pollub.pl

Abstract: Producing biochar from sewage sludge is one option for sludge management; however, assessing the climate-related viability of this solution requires accounting for emissions associated with feedstock preparation and processing. This study aims to present a methodology for calculating the carbon footprint of biochar production and to compare variants that differ in pyrolysis temperature and energy supply methods. The proposed methodology is based on a material and energy balance and the use of greenhouse gas emission factors. The functional unit adopted is the processing of 1 Mg of sewage sludge dry matter, with results also calculated per 1 kg of dry biochar. The system boundaries encompass the transport of dewatered sludge, drying, feedstock preparation, pyrolysis, product cooling, and the management of process residues. The model accounts for electricity and heat consumption, inert gas usage, and direct emissions. The analysis compares pyrolysis temperatures of 400, 500, and 600°C, factoring in variable biochar yields and energy requirements. A sensitivity analysis regarding initial sludge moisture content, transport distance, and the electricity emission factor complements the study. Internal energy recovery is accounted for by reducing the demand for external energy. Potential carbon sequestration in the biochar is considered separately, depending on carbon stability and the product's intended application. The proposed approach enables the identification of the stages that contribute most significantly to emissions and the assessment of the impact of process parameters on the carbon footprint. It can serve as a tool to support the selection of biochar production conditions and the evaluation of sewage sludge management options.

Keywords: carbon footprint, biochar, sewage sludge, pyrolysis, material and energy balance, sensitivity analysis

VERIFICATION OF FOREARM GRID GENERATION METHODS FOR EMG ELECTRODE PLACEMENT DURING WHEELCHAIR PROPULSION STUDIES

Weronika Wiatrowska, Faculty of Mechanical Engineering, Poznań University of Technology, veronika.wiatrowska@put.poznan.pl

Aleksandra Świadek, Faculty of Mechanical Engineering, Poznań University of Technology, aleksandra.swiadek@put.poznan.pl

Bartosz Wieczorek, Faculty of Mechanical Engineering, Poznań University of Technology, bartosz.wieczorek@put.poznan.pl

Lukasz Wargula, Faculty of Mechanical Engineering, Poznań University of Technology, lukasz.wargula@put.poznan.pl

Abstract: The lack of a standardized and reproducible method for placing surface electromyography (sEMG) electrodes on the forearm leads to increased variability and limited comparability of results in biomechanical analyses. The aim of this study was to evaluate methods for generating grids on the forearm for sEMG studies during wheelchair propulsion. The analysis considered three grid variants based on different assumptions: a grid with a fixed linear spacing, a grid defined based on anthropometric points, and a grid drawn using a forearm template. A multi-criteria evaluation of the methods under consideration and experimental sEMG studies was conducted. The analysis took into account criteria such as participant discomfort, time required to prepare the grid, alignment of grid fields with electrode size, ease of use, versatility of the method, EMG signal amplitude, and degree of muscle coverage. The results of the multi-criteria evaluation made it possible to identify the solution with the highest efficiency based on the established criteria. The most advantageous method turned out to be generating a mesh according to the principle of constant linear spacing. This method received the highest final score, demonstrating a particular advantage in key criteria such as muscle coverage and versatility. The result obtained was 16.84% higher compared to the second-best solution. The analysis indicates that the placement of measurement electrodes significantly affects the quality of the recorded sEMG signal. The results underscore the need to develop a methodology that enables the repeatable positioning of electrodes, particularly in the context of long-term biomechanical studies related to wheelchair propulsion.

Keywords: surface grid, EMG grid, electrodes location, electrodes arrangement, arm grid generation, grid generation methods

AI-BASED OPERATOR BEHAVIOR PREDICTION ALGORITHM FOR HUMAN-ROBOT COOPERATION

Lukasz Sobaszek, Faculty of Mathematics and Information Technology, Lublin
University of Technology, l.sobaszek@pollub.pl

Bartłomiej Stadnik, Lublin University of Technology, bartlomiejstadnik98@gmail.com

Abstract: The use of industrial robots are increasingly being utilized in processes carried out in cooperation with humans. A wide range of studies have focused on advancing novel approaches aimed at enhancing the level of interaction. However, the existing solutions typically rely on the integration of multiple hardware components, with the consequent high costs and complexity. In response to the outlined problems, this paper presents an AI-based algorithm designed to anticipate operator actions within a human–industrial robot collaborative framework. The developed algorithm has been verified based on experimental data, with the obtained outcomes confirming the validity and practical applicability of the developed method. Utilized the research workstation for operator behavior analysis, implemented the algorithm by means of the Python language, and, through simulation of the robot’s operation within a computational simulation framework, the approach was successfully verified. Based on the conducted tests for each operator, a decrease in the execution time of the pick and place task was observed. The achieved reduction varied between 4% and 12.4%.

Keywords: prediction, artificial intelligence, industrial robot, efficiency

DEVELOPMENT OF TECHNOLOGY AND OPTIMIZATION OF AERODYNAMIC PARAMETERS OF WHEAT FLOUR BY DRY METHOD FOR STARCH AND PROTEIN FRACTIONS

Aidana Ussenova, Saken Seifullin Kazakh Agrotechnical University,
ussenova.aidana@mail.ru

Bakhtiyar Rzayev, Saken Seifullin Kazakh Agrotechnical University,
Bahtiyar_9128@mail.ru

Mukhtarbek Kakimov, Saken Seifullin Kazakh Agrotechnical University,
muhtarbek@mail.ru

Bauyrzhan Iskakov, Saken Seifullin Kazakh Agrotechnical University,
baissemey@bk.ru

Serik Tokayev, Saken Seifullin Kazakh Agrotechnical University, tokaev_sd@mail.ru

Gulnazym Ospankulova, Saken Seifullin Kazakh Agrotechnical University,
saule_aru@list.ru

Roza Abisheva, Saken Seifullin Kazakh Agrotechnical University, ard1967@mail.ru

Michał Bembenek, Faculty of Mechanical Engineering and Robotics, AGH University
of Kraków, bembenek@agh.edu.pl

Abstract: Pneumatic centrifugal classification is a sustainable dry fractionation technology for cereal flours, avoiding water use and preserving native functionality. This study provides a mathematical analysis of how the adjustable slot opening degree (φ) influences efficiency, yield distribution, purity, and selectivity in wheat flour processing. A key innovation is a two-phase gas-solid flow model incorporating the material loading coefficient (μ), validated against experimental data at 500 kg/h. Based on force mechanics, the aerodynamic drag force follows a quadratic dependence on air velocity ($F_d \sim V^2$). Critical velocity criteria derived from momentum balance define threshold conditions for particle separation: lighter protein-rich particles entrain into the light fraction, while denser starch-rich particles migrate outward. Engineering calculations show that the optimal operating window occurs at φ between 0.30 and 0.40. Within this range, protein purity in the light fraction reaches 91–93%, while starch purity in the heavy fraction attains approximately 96%. The intermediate middlings fraction is minimized to 80–100 kg/h. The selectivity coefficient peaks at $S_{int} = 3.94$ at $\varphi = 0.30$, confirming strong preferential separation. Additional validation criteria are satisfied within the optimal range: the residence time condition ($t_{res} \geq t_{need}$) ensures sufficient differential migration, while the heavy particle retention criterion ($v_{s*} < V_{st}$) confirms that starch-rich particles are effectively directed to the heavy fraction. Taken together, these findings establish a quantitative predictive framework for rational design and optimization of pneumatic centrifugal classifiers, offering engineers and food processors clear operating guidelines to maximize protein and starch purity while minimizing mixed intermediate fractions. This work advances energy-efficient, water-free fractionation technologies for plant-based ingredients.

Keywords: air classification, dry fractionation, pneumatic classification, protein–starch separation, selectivity coefficient, two-phase flow, wheat flour fractionation

CMES'26 draft version

WIND TUNNEL AERODYNAMIC EXPERIMENTAL RESULTS OF THE LUBLIN R-XIIID AIRCRAFT MODEL

Konrad Pietrykowski, Faculty of Mechanical Engineering, Lublin University of Technology, k.pietrykowski@pollub.pl

Paweł Magryta, Faculty of Mechanical Engineering, Lublin University of Technology, p.magryta@pollub.pl

Rafał Kliza, Faculty of Production Engineering, University of Life Sciences in Lublin, Poland, rafal.kliza@up.edu.pl

Zbigniew Czyż, Faculty of Aviation, Polish Air Force University, z.czyz@law.mil.pl

Abstract: This paper presents the methodology and results of wind tunnel aerodynamic testing conducted on a scaled model of the Lublin R-XIIID aircraft. The experimental campaign was carried out in the closed-circuit wind tunnel at the Lublin University of Technology. The primary objective was to determine the complete aerodynamic characteristics of the airframe and to evaluate the structural configuration regarding aerodynamic performance and static stability. The 1:14 scale model was manufactured using 3D printing (PLA) based on CAD geometry previously validated through computational fluid dynamics (CFD). Due to test section dimensions and 3D printing build volume constraints, the model was constructed from 20 modular, glueless elements reinforced with carbon fiber, brass, and threaded steel rods. Aerodynamic forces and moments were measured using an FMT 625 six-component internal balance coupled with a QuantumX MX440B data acquisition system at flow velocities up to 50 m/s. The experimental program comprised seven test series encompassing 1,779 measurement points across angles of attack ranging from -22° to $+22^\circ$, sideslip angles, and various control surface deflections (elevator, rudder, ailerons, and horizontal stabilizer). Measured loads were converted into dimensionless aerodynamic coefficients (C_x , C_y , C_z , C_m , C_n) referenced to the center of gravity located at 1/4 of the mean aerodynamic chord. The analysis confirmed a linear longitudinal stability behavior with a static margin of approximately 0.25 within the usable angle-of-attack range, verifying the aerodynamic integrity of the aircraft design and the effectiveness of its control surfaces.

Keywords: blin R-XIIID, wind tunnel testing, aerodynamic characteristics, 3D printing, aerodynamic balance

A FORMAL GRAPH MODEL OF AN EMBODIED DATA PUMP FOR IOT–MIXED REALITY INTEGRATION

Grzegorz Rybak, Research and Development Center, Netrix S.A.,
grzegorz.rybak@netrix.com.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A., Institute of Computer Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A., Institute of Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Abstract: Distributed industrial applications increasingly combine heterogeneous data sources with operator-facing mixed-reality interfaces, yet their communication and control relationships are difficult to specify consistently. This paper proposes a formal graph-based model of an Embodied Data Pump (EDP) that integrates database access and IoT messaging based on MQTT, Kafka, and WebSocket communication with a HoloLens 2 environment. The architecture is represented as a directed labeled graph $G = (V, E, l)$. Its vertices capture data clients, protocol connectors, the EDP, the Tomoverse broker and management services, the HoloLens device, and scene-level visualization and interaction components. Edges encode message-flow and control dependencies, while the labeling function records the communication protocol, endpoint pair, and directionality. The formalization links an abstract extract–transform–load process with computation, communication, and spatial interaction in a single representation. Its feasibility is illustrated by mapping the model onto a prototype in which sensor and broker data are exposed through mixed-reality panels, indicators, connectors, and configurable pump plug-ins. The proposed model provides a traceable basis for comparing architecture with implementation and for designing subsequent experiments on throughput, reliability, task comprehension, and system configuration time. Rather than reporting completed performance validation, the work establishes the formal and prototypical foundation required to evaluate embodied data interfaces in industrial IoT and digital-twin environments.

Keywords: embodied data pump, Internet of Things, mixed reality, directed graph model, data integration, HoloLens 2, MQTT, Kafka

EXPERIMENTAL INVESTIGATION OF NONLINEAR DYNAMICS AND PIEZOELECTRIC RESPONSE OF AN AIRFLOW-INDUCED VIBRATING BEAM

Mateusz Waśkowicz, Lublin University of Technology, Faculty of Mechanical Engineering, m.waskowicz@pollub.pl

Marek Borowiec, Lublin University of Technology, Faculty of Mechanical Engineering, m.borowiec@pollub.pl

Marcin Fronc, Lublin University of Technology, Faculty of Electrical Engineering and Computer Science, m.fronc@pollub.pl

Magdalena Przybylska – Fronc, Lublin University of Technology, Faculty of Mechanical Engineering, m.przybylska@pollub.pl

Abstract: This study presents an experimental investigation of the dynamic response of a cantilever beam subjected to airflow excitation and its associated piezoelectric response. The research focuses on identifying changes in the vibration characteristics of the beam with increasing airflow velocity and determining how these changes are reflected in the electrical signal generated by a piezoelectric patch attached to the structure. Experiments are conducted in an aerodynamic wind tunnel for airflow velocities. The mechanical response of the beam is measured using a laser Doppler vibrometer, while the voltage generated by the piezoelectric element is recorded simultaneously. The obtained signals are analyzed in both the time and frequency domains using statistical measures, root mean square values, and Fourier transform analysis. In addition, experimental bifurcation diagrams and phase-space representations are employed to investigate changes in the dynamical state of the system as a function of airflow velocity. The comparison of mechanical and electrical responses enables the assessment of the relationship between airflow-induced vibrations and piezoelectric energy conversion. The proposed approach provides an experimental framework for identifying changes in the nonlinear dynamic behavior of airflow-excited structures and evaluating their potential for vibration-based energy harvesting.

Keywords: piezoelectric element, beam, energy harvesting, bluff body, electrical signal

MATHEMATICAL MODELLING AND EXPERIMENTAL INVESTIGATION OF A BLDC-BASED ENERGY HARVESTER UNDER NONLINEAR MECHANICAL EXCITATION

Marcin Fronc, Lublin University of Technology, Faculty of Electrical Engineering and Computer Science, m.fronc@pollub.pl

Krzysztof Kolano, Lublin University of Technology, Faculty of Electrical Engineering and Computer Science, k.kolano@pollub.pl

Grzegorz Litak, Lublin University of Technology, Faculty of Mechanical Engineering, g.litak@pollub.pl

Magdalena Przybylska – Fronc, Lublin University of Technology, Faculty of Mechanical Engineering, m.przybylska@pollub.pl

Mateusz Waśkiewicz, Lublin University of Technology, Faculty of Mechanical Engineering, m.waskowicz@pollub.pl

Abstract: This study investigates the dynamic behaviour and electrical response of a vibration energy harvesting system incorporating a brushless DC (BLDC) machine operating as a generator under nonlinear mechanical excitation. The objective is to determine how excitation parameters and electromechanical interactions affect the system response and the amount of electrical energy harvested. The research combines mathematical modelling, numerical simulations, and experimental investigation. The mathematical model describes the coupled mechanical and electrical dynamics, accounting for inertia, damping, nonlinear excitation, and the interaction between rotor motion and electromagnetic torque. Numerical simulations are used to examine the influence of excitation frequency and amplitude, as well as electrical loading, on rotor motion, induced voltage, and generated power. Particular attention is paid to identifying operating conditions that support effective energy conversion and assessing changes in the dynamic response across the investigated parameter range. Experimental measurements are performed under controlled mechanical excitation. Mechanical and electrical signals are recorded and analysed in the time and frequency domains using root mean square values, spectral analysis, and phase-space representations. Electrical power is evaluated to assess the relationship between the mechanical response and energy harvesting performance. Comparing numerical predictions with experimental measurements enables model validation and assessment of its ability to reproduce the behaviour of the physical system. The proposed approach provides a framework for understanding nonlinear electromechanical interactions and selecting excitation and loading parameters that improve the performance of BLDC-based vibration energy harvesters.

Keywords: vibration energy harvesting, nonlinear excitation, mathematical modelling, electromechanical coupling, experimental investigation

NUMERICAL AND EXPERIMENTAL INVESTIGATION OF THE DYNAMICS OF COUPLED ELASTIC BEAMS SUBJECTED TO MECHANICAL EXCITATION

Magdalena Przybylska – Fronc, Lublin University of Technology, Faculty of Mechanical Engineering, m.przybylska@pollub.pl

Grzegorz Litak, Lublin University of Technology, Faculty of Mechanical Engineering, g.litak@pollub.pl

Marek Borowiec, Lublin University of Technology, Faculty of Mechanical Engineering, m.borowiec@pollub.pl

Marcin Fronc, Lublin University of Technology, Faculty of Electrical Engineering and Computer Science, m.fronc@pollub.pl

Mateusz Waśkowicz, Lublin University of Technology, Faculty of Mechanical Engineering, m.waskowicz@pollub.pl

Abstract: This study investigates the dynamic response of a system of coupled elastic beams subjected to mechanical vibration excitation. The objective is to determine how excitation and coupling parameters affect the vibration characteristics of the system, with particular emphasis on resonance phenomena and interactions between individual components. The research includes mathematical modelling, numerical simulations, and experimental validation. The system model accounts for the inertial and elastic properties of the beams, damping, and coupling interactions. Numerical simulations are used to determine the system response under varying excitation frequencies and amplitudes, as well as coupling parameters. The experimental investigation involves measuring the vibrations of individual beams under controlled mechanical excitation. The acquired signals are analysed in the time and frequency domains using root mean square values, spectral analysis, and amplitude–frequency response curves. A comparison of vibration amplitudes and phase relationships enables the assessment of vibration synchronisation and the distribution of the dynamic response among the beams. Comparing simulation results with experimental measurements allows the agreement between the model and the behaviour of the physical system to be assessed and the model's range of applicability to be determined. The proposed approach aims to identify conditions leading to vibration amplification or suppression and to evaluate the potential for shaping the dynamic response by adjusting coupling parameters. The research provides a basis for designing multi-element elastic systems for vibration control and their potential application in mechanical vibration energy harvesting.

Keywords: elastic beams, mechanical coupling, forced vibrations, system dynamics

APPLICATION OF COMPUTER PROGRAMS IN TECHNOLOGY

SCALABILITY ANALYSIS AND PERFORMANCE EVALUATION OF WEBRTC SYSTEMS USING THE INFRASTRUCTURE AS CODE PARADIGM AND CONTAINERIZED TRAFFIC GENERATORS

Patryk Organiściak, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, org@prz.edu.pl

Paweł Kuraś, Faculty of Computer Science, Electronics and Telecommunications, AGH University of Kraków, pawel.kuras@agh.edu.pl

Alicja Gerka, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, a.gerka@prz.edu.pl

Krzysztof Demidowski, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, k.demidowski@prz.edu.pl

Mateusz Salach, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, m.salach@prz.edu.pl

Karolina Kisala, Faculty of Mathematics and Applied Physics, Rzeszów University of Technology, 178841@stud.prz.edu.pl

Abstract: The dynamic development of remote education and distributed work has driven the demand for reliable real-time communication platforms. Ensuring the stability of such systems under massive load is a standard engineering challenge. This research was conducted to evaluate the performance of ICT systems implemented as part of one of the largest educational projects in Poland. The research process utilized a modern testing framework based on the Infrastructure as Code (IaC) paradigm. Terraform was used to dynamically manage cloud resources, enabling the provisioning of computing instance clusters. The traffic generation environment consisted of a distributed cluster of Docker containers, ensuring full isolation and repeatability of test scenarios. End-user simulation was implemented using scripts based on the Playwright library, allowing for the emulation of realistic interactions with the WebRTC interface. Iterative load tests at a scale of up to 421 users demonstrated the high efficiency of the server cluster, which consumed only 12.1% of CPU resources and less than 10 GiB of RAM, with external network traffic at 374 Mbps. The analysis revealed that the critical limitation of the system is the performance of the client-moderator's browser, which loses functionality beyond the threshold of 250 active video streams despite significant server resource redundancy. The study identified a critical bottleneck: the server infrastructure remains significantly underutilized, while the browser performance on the moderator's workstation drastically degrades after exceeding 250 active video streams. The results confirm that the analyzed infrastructure is capable of stably supporting user groups that significantly exceed the initial design assumptions. The research suggests that for sessions exceeding 250 participants, engineering efforts should focus on client-side application optimization and

local workstation resource management, rather than merely scaling server resources. The proposed automated testing methodology constitutes an effective and scalable tool for auditing distributed communication systems.

Keywords: load testing, real-time communication, Terraform, Docker, cloud resources, end-user simulation, Playwright, automated testing methodology, distributed systems, complex system

CMES'26 draft version

SIMULATION STUDIES OF THE SPRAY WASHING PROCESS

Weronika Henzler - Grzywna, Faculty of Mechanical Engineering, Lublin University of Technology, NOYEN Company, weronika.henzler@pollub.edu.pl

Jacek Czarnigowski, Faculty of Mechanical Engineering, Lublin University of Technology, j.czarnigowski@pollub.pl

Lukasz Grabowski, Faculty of Mechanical Engineering, Lublin University of Technology, l.grabowski@pollub.pl

Abstract: Simulation studies of the spray washing process are an essential tool for analyzing and optimizing cleaning processes across various industries. In this study, a two-pronged approach was used to model the phenomena occurring when a liquid jet interacts with the surface being cleaned. The first stage involved the use of the DPM (Discrete Phase Model) method, which allows for the tracking of droplet trajectories in the spray stream, taking into account the transition to a liquid film model on the surface using the EWF (Eulerian Wall Film) concept. In the second approach, the SPH (Smoothed Particle Hydrodynamics) method was used, which enabled mesh-free flow modeling and a more accurate representation of phenomena related to jet deformation and droplet coalescence in the spray upon contact with the surface. Simulations were performed for various operating parameters of the spray system, such as operating pressure, nozzle angle, and nozzle-to-surface distance, allowing for an assessment of their impact on the cleaning process. In particular, the analysis focused on velocity distribution, liquid coverage intensity, and the dynamics of droplet-substrate interaction. The simulations conducted made it possible to compare the effectiveness of modeling key physical phenomena, such as spray distribution, liquid coverage, and the dynamics of droplet-substrate interaction. It was demonstrated that the DPM–EWF model provides computational efficiency while maintaining an accurate description of macroscopic phenomena, whereas the SPH method allows for a more detailed analysis of local hydrodynamic effects. The results obtained can serve as a basis for optimizing spray washing process parameters and for the further development of numerical models used in engineering practice.

Keywords: DPM, SPH, EWF, fluid flow, cleaning process, spray washing

LOW-COST MEASUREMENT OF LIGHT POLARISATION PLANE ROTATION USING DOUBLE TFBG SENSORS WITH POWER-BASED INTERROGATION

Grzegorz Koziel, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, g.koziel@pollub.pl

Marta Dziuba-Koziel, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, m.dziuba@pollub.pl

Damian Harasim, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, d.harasim@pollub.pl

Piotr Kisala, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, p.kisala@pollub.pl

Sylwester Nowocień, Faculty of Electronics, Photonics and Microsystems, Wrocław
University of Science and Technology, sylwester.nowocien@pwr.edu.pl

Abstract: This article presents a new method for measuring the angle of rotation of the light polarisation plane (LPPR) using a dual-channel power-based approach with tilted Bragg gratings (TFBG) and Bragg gratings (FBG), and optical power measurement. Unlike previous solutions based on the analysis of the full transmission spectrum of the TFBG, the proposed method does not require the use of an optical spectrum analyzer. The measurement system consists of two optical paths containing TFBGs positioned at a 45° angle to each other, working in conjunction with FBGs acting as spectral filters. The optical power values recorded in both channels are used to determine the angle of rotation of the polarization plane based on previously determined calibration characteristics approximated by a Fourier series. An analysis was carried out of the effect of the relative positions of the TFBG and FBG spectra on the amplitude of power variations and the distortion of measurement characteristics. It was demonstrated that the appropriate selection of the FBG reflection band position relative to the selected TFBG cladding mode allows the amplitude of the measurement signal to be increased whilst maintaining low distortion of the characteristics. The effectiveness of the developed method was experimentally verified in the range of angles from 0° to 180°. For an independent test set, a mean absolute error of 0.27°, an RMSE of 0.33°, and a maximum error not exceeding 0.76° were obtained. The coefficient of determination reached a value of $R^2 = 0.999$. The results confirm that the proposed method enables precise measurement of the angle of rotation of the plane of light polarisation whilst significantly simplifying the measurement setup, reducing measurement time and lowering costs compared to solutions requiring the recording of the full optical spectrum.

Keywords: tilted fibre Bragg grating, TFBG, polarisation plane rotation, optical fibre sensors, cladding mode resonances, power-based optical interrogation

MACHINE LEARNING-BASED ALGORITHM FOR ESTIMATING ENERGY EFFICIENCY OF PHOTOVOLTAIC PANELS IN PUBLIC TRANSPORT: CASE STUDY OF LUBLIN

Marcin Matczuk, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, m.matczuk@pollub.pl

Lukasz Grabowski, Faculty of Mechanical Engineering, Lublin University of Technology, l.grabowski@pollub.pl

Grzegorz Koziel, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, g.koziel@pollub.pl

Marta Dziuba-Koziel, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, m.dziuba@pollub.pl

Dominik Strzałka, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, strzalka@prz.edu.pl

Piotr Jakliński, Faculty of Mechanical Engineering, Lublin University of Technology, p.jaklinski@pollub.pl

Kamil Żyła, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, k.zyla@pollub.pl

Jacek Kęsik, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, j.kesik@pollub.pl

Abstract: The present study investigates the energy efficiency of photovoltaic (PV) panels installed on public transport buses. The focus is on assessing urban routes for their solar energy harvesting potential and its impact on fuel consumption reduction. The analysis is based on real-world data collected from the public transport system in the city of Lublin. Due to the prevalence of GPS signal loss, particularly in dense urban environments, a machine learning-based algorithm was developed to enhance bus trajectory reconstruction. The proposed methodology comprises four main stages: (1) filtering and processing GPS data to reconstruct bus routes, (2) augmenting the dataset by computing additional metrics and factors from the original dataset, (3) dividing bus routes into hexagonal spatial units and calculating average metric values for each region, and (4) identifying areas with higher shading factors and solar energy potential for each spatial unit. The reconstruction stage uses anomaly detection techniques to mitigate the effects of incomplete or noisy GPS signals. The results indicate that several areas in Lublin are suboptimal for installing PV panels, that routes on the outskirts are less energy-intensive than those within the city, and that the issue raised in the article could help improve urban planning. Furthermore, the proposed approach facilitates the identification of spatial patterns affecting PV performance and supports data-driven decision-making for planning energy-efficient transport systems.

Keywords: energy efficiency, photovoltaic panels, machine learning, isolation forest, algorithm, public transport, spatial distribution, urban planning

IMAGE-BASED CONTACT PATCH CHARACTERIZATION OF WHEELCHAIR TIRE–ROLLER INTERACTION USING CONVEX HULL AND ALPHA SHAPE ALGORITHMS

Bartosz Wieczorek, Faculty of Mechanical Engineering, Poznań University of Technology, bartosz.wieczorek@put.poznan.pl

Lukasz Wargula, Faculty of Mechanical Engineering, Poznań University of Technology, lukasz.wargula@put.poznan.pl

Abstract: This study presents a low-cost methodology for determining the contact patch geometry between a pneumatic wheelchair tire and a rigid roller using image processing and computational geometry techniques. Tire imprints were obtained using an ink transfer method and analyzed with convex hull and alpha shape algorithms. The approach enables estimation of the semi-axes of the equivalent contact ellipse and assessment of their influence on the pressure center shift x_0 , a key parameter in rolling resistance modeling. The results indicate that the convex hull algorithm systematically overestimates the contact geometry, particularly in the transverse direction. For irregular and highly elongated contact patches, the contact width is overestimated by approximately 15–35%, and the contact area by 20–50%. In contrast, the alpha shape algorithm provides a more accurate reconstruction of the actual contact boundary. These geometric discrepancies propagate into the analytical model, leading to an overestimation of the pressure center shift x_0 by approximately 5–10% when the convex hull is applied. The findings demonstrate that accurate geometric reconstruction of the contact patch is essential for reliable modeling of tire–roller interaction and that alpha shape-based methods offer a significant improvement over conventional convex approximations.

Keywords: contact patch, image processing, alpha shape, convex hull, wheelchair tire, rolling resistance, pressure center shift, computational geometry, tire–roller interaction, low-cost measurement

PASSWORD SECURITY AMONG INTERNET USERS: AN ANALYSIS OF KNOWLEDGE, ATTITUDES, AND PRACTICES

Beata Tyszkiewicz, Lublin University of Technology, s101095@pollub.edu.pl

Anastasiia Tarnavska, Lublin University of Technology, s99817@pollub.edu.pl

Barbara Buraczyńska, Faculty of Mathematics and Information Technology, Lublin
University of Technology, b.buraczynska@pollub.pl

Abstract: The aim of this study is to examine Internet users' knowledge, attitudes, and practices regarding password security. It also seeks to identify discrepancies between users' actual behaviors and the recommendations provided by cybersecurity experts. The study included participants from different age groups. The findings reveal that many users continue to engage in practices that undermine password security in digital environments. Importantly, the results indicate that users across all age groups make errors and do not adhere to recommended guidelines for creating, managing, and using passwords.

Keywords: password security, cybersecurity, Internet users, user behavior

IMPACT OF WEBSITE INTERACTIVITY AND PERFORMANCE ON USER EXPERIENCE: AN ANALYSIS OF SELECTED WEBSITES

Joanna Szulżyk-Cieplak, Faculty of Mathematics and Information Technology, Lublin
University of Technology, j.szulzyk-cieplak@pollub.pl

Barbara Buraczyńska, Faculty of Mathematics and Information Technology, Lublin
University of Technology, b.buraczynska@pollub.pl

Bogdan Basisty, Lublin University of Technology, bohdan.basistyi@pollub.edu.pl

Abstract: The aim of this paper is to analyze the impact of website interactivity and performance on user experience. The study evaluates how interface elements (including animations, microinteractions, and dynamic content), as well as technical performance parameters, influence user satisfaction and usability of web services. The research was conducted based on an analysis of selected websites and data obtained from the Google PageSpeed Insights tool (including LCP, FCP, and TBT metrics), complemented by the results of a user survey. A mixed-method approach was applied, combining both quantitative and qualitative analysis. The results indicate that higher technical performance correlates with improved user experience. At the same time, a high level of interactivity can increase user engagement; however, when not properly optimized, it may negatively affect usability, particularly on mobile devices. The findings highlight the need to maintain a balance between interactivity and performance in the design of modern web interfaces.

Keywords: user experience (UX), web performance, website interactivity, usability

MULTI-CRITERIA OPTIMIZATION OF UAV MEDICAL TRANSPORT CORRIDORS IN URBAN ENVIRONMENTS BASED ON COST SURFACE ANALYSIS

Jarosław Tatarczak, Faculty of Mathematics and Information Technology, Lublin
University of Technology, j.tatarczak@pollub.pl

Justyna Baran-Tatarczak, JB-T Solid Plan, solidplanjbt@gmail.com

Abstract: The dynamic development of medical logistics utilizing Unmanned Aerial Vehicles (UAVs) in time-critical missions requires a careful balance between operational efficiency and stringent Ground Risk Class (GRC) safety requirements within dense urban environments. This study introduces and implements a multi-criteria optimization model for autonomous Beyond Visual Line of Sight (BVLOS) medical flight corridors based on spatial cost surface analysis. The proposed methodology integrates urban planning structures with the SORA risk assessment framework. Utilizing a dasymetric mapping technique, a spatial disaggregation of demographic data was performed, shifting from homogeneous administrative districts to a continuous population presence probability model based on urban capacity indicators derived from the draft General Plan of the City of Lublin. Using the Analytic Hierarchy Process (AHP), specific weights were assigned to five operational criteria, with human exposure defined as the overriding component of the model. The final spatial resistance map was generated through Multi-Criteria Evaluation (MCE), and the optimal trajectories were calculated using the Least-Cost Path (LCP) algorithm. Validation of the model across selected healthcare facilities in Lublin demonstrated that LCP corridors reduce the operational population exposure risk (Rop) by an average of 74.38% compared to geometric shortest paths. Despite the extended trajectories, these routes guarantee a 22–40% time advantage over ground Emergency Medical Services (EMS). Furthermore, network analysis revealed that spatial optimization does not significantly affect cellular handover dynamics, maintaining a comparable frequency of network switches across both routing strategies. The developed method serves as a robust decision support tool, enabling the safe operationalization of Urban Air Mobility (UAM) networks integrated with municipal spatial planning.

Keywords: UAV, medical logistics, cost surface, GIS analysis, path planning, urban zone

COMPARATIVE ANALYSIS OF MEDICAL MOBILE APPLICATIONS USING THE MAQMA METHODOLOGY

Karol Lazaruk, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, k.lazaruk@pollub.pl

Małgorzata Plechawska-Wójcik, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, m.plechawska@pollub.pl

Marek Miłosz, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, m.milosz@pollub.plplecha

Piotr Tokarski, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, p.tokarski@pollub.pl

Sergio Luján-Mora, Department of Software and Computing Systems, University of Alicante, sergio.lujan@ua.es

Abstract: The growing importance of mobile applications in healthcare necessitates the systematic evaluation of their quality, particularly in the context of User Experience (UX). This paper presents the results of a comparative analysis conducted using Multi-criteria Methodology for Assessing the Quality of the Interface of Mobile Medical Applications (MAQMA). MAQMA is a multi-criteria approach to evaluating the quality of mobile medical application interfaces, integrating three key aspects of UX: usability, accessibility, and cognitive load. It provides a composite index that enables straightforward and unambiguous identification and comparison of the overall quality of applications. The analysis included three mobile applications of a medical or health-related nature: T1DCoach, Waterful, and Constant Therapy. The presented case study is based on data collected from 40 participants across two centers (in Poland and Spain). The obtained results confirm the consistency of the methodology, its sensitivity to differences between the evaluated applications, and the interpretability of the results. Statistical analyses, including the calculation of Cohen's d and correlation analysis, made it possible to assess the statistical significance of differences between the applications, as well as the relationships between the studied variables. These findings further demonstrate the usefulness of the MAQMA methodology for comprehensive comparison of mobile medical application quality.

Keywords: accessibility, cognitive load, interface quality assessment, MAQMA methodology, mobile medical apps, usability

GEOMETRY-BASED DUAL-GRID CLUSTERING ALGORITHM (G2LEACH) FOR ENERGY-EFFICIENT WIRELESS SENSOR NETWORKS FOR IOT ENVIRONMENT

Andrzej Paszkiewicz, Faculty of Electrical and Computer Engineering, Rzeszów
University of Technology, andrzejp@prz.edu.pl

Dariusz Rączka, Faculty of Electrical and Computer Engineering, Rzeszów University
of Technology, d.raczka@prz.edu.pl

Abstract: The LEACH protocol remains a foundational clustering algorithm for wireless sensor networks, yet its random cluster head selection leads to uneven energy consumption and premature network degradation. Despite numerous modifications, no existing variant incorporates a spatially deterministic dual-layer grid hierarchy for structured area management. This paper proposes G²LEACH, which introduces micro-area and Grid of Head Areas (GHA) structures to enable geometrically controlled cluster head placement. Six algorithm configurations are evaluated through extensive simulations (1200 nodes, 100 independent runs) in two deployment scenarios. In the 1000 × 1000 m scenario, G²LEACH achieves a 955% improvement in the Half Nodes Alive metric and extends total network lifetime by 75%. In the compact 100 × 100 m scenario, the First Node Dead metric improves by 87%. The results confirm that spatially structured clustering significantly enhances network longevity and coverage uniformity.

Keywords: clustering protocol, distributed systems, energy efficiency, grid-based clustering, IoT, LEACH, network lifetime, spatial coverage, wireless sensor networks

EVALUATION OF DISTANCE METRICS FOR HUMAN POSE-LANDMARK TRAJECTORIES EXTRACTED WITH DIFFERENT POSE ESTIMATION MODELS

Dominik Ożóg, Faculty of Civil and Environmental Engineering and Architecture,
Rzeszów University of Technology, d.ozog@prz.edu.pl

Wojciech Łabuński, Faculty of Mechanical Engineering and Aeronautics, Rzeszów
University of Technology, w.labunski@prz.edu.pl

Natalia Jajko, Rzeszów University of Technology, 173626@stud.prz.edu.pl

Eryk Sęk, Rzeszów University of Technology, 173705@stud.prz.edu.pl

Bartosz Stala, Rzeszów University of Technology, 173717@stud.prz.edu.pl

Abstract: This research presents a structured methodological framework for assessing the similarity of human pose-landmark trajectories extracted from video sequences. The primary objective is to evaluate the robustness of diverse distance-based similarity measures and determine whether their multi-criteria performance ranking depends on the underlying computer vision model used for coordinate extraction. Utilizing the public Penn Action benchmark, a customized sub-dataset encompassing 853 video sequences across five distinct physical exercise classes was established. Trajectories were extracted concurrently using two state-of-the-art architectures: Google MediaPipe (BlazePose) and OpenMMLab MMPose (RTMPose-m). To ensure full methodological alignment, the output coordinates were mapped onto a unified 13-keypoint skeletal topology and converted through an agnostic spatial-temporal preprocessing layer into dense 1x2600 feature motion vectors. Pairwise similarity matrices of dimensions 853x853 were generated for ten individual distance metrics and evaluated through a dual multi-criteria scheme utilizing the global mean Silhouette coefficient and the inter/intra-class distance ratio. Instead of abstract non-parametric correlations, the framework deploys a direct structural permutation analysis of the performance hierarchies. The empirical findings reveal that while high-frequency tracking jitter and bounding-box drift introduce localized noise, the top-performing distance metrics maintain high structural stability across both vision models, undergoing only minor topological rank permutations. This stability demonstrates that optimal similarity metrics can operate as robust, model-agnostic components, paving the way for standardized and explainable analytical pipelines in vision-based human motion analysis.

Keywords: human pose estimation; pose-landmark trajectories; distance metrics; video-based movement analysis; trajectory analysis

ANOMALY DETECTION IN MAVLINK TELEMETRY LOGS OF UNMANNED AERIAL VEHICLES USING DATA ANALYTICS METHODS

Pawel Dymora, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, pawel.dymora@prz.edu.pl

Mirosław Mazurek, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, mirekmaz@prz.edu.pl

Bartosz Nycz, State Academy of Applied Sciences in Przemyśl, b.nycz@pansp.pl

Abstract: The rapid expansion of unmanned aerial vehicles (UAVs) in logistics, agriculture, surveillance, and emergency services has increased the importance of operational safety and cybersecurity. Modern UAV platforms generate telemetry and flight log data that can be used not only for diagnostics and maintenance, but also for detecting abnormal or malicious behavior. This paper presents an approach to the analysis of MAVLink telemetry logs for identifying security-related anomalies in UAV systems. The study focuses on incidents such as GPS jumps, communication loss, battery failsafe events, abnormal trajectory changes, and suspicious command sequences. Using telemetry parameters including position, velocity, attitude, battery status, and mode transitions, the proposed methodology combines statistical analysis, rule-based methods, and machine learning techniques. The results show that MAVLink log analysis can effectively improve anomaly detection, post-incident investigation, and real-time UAV safety monitoring.

Keywords: UAV, unmanned aerial vehicles, MAVLink, Anomaly Detection

AUDITABLE OFFLINE SPATIOTEMPORAL ALIGNMENT OF HETEROGENEOUS TELEMETRY AND MOTION TRACKING LOGS

Stanisław Piotr Skulimowski, Faculty of Electrical Engineering and Computer Science,
Lublin University of Technology, s.skulimowski@pollub.pl

Abstract: Heterogeneous experimental logs cannot be compared directly when independent clocks, unequal sampling rates, and different coordinate frames are used. This paper evaluates OFF-STAP, a configuration-driven offline system for deterministic batch integration of LEGO EV3 telemetry and HTC Vive Tracker logs. Its computer-science contribution is a fail-explicit, auditable processing contract comprising typed schemas, staged quality gates, calibration/evaluation separation, exact comparison support, and source-linked artifacts. The archive contained 848 entries: 405 planned trials, 368 compatible logs from an earlier experiment, and 75 diagnostic or unplanned entries. Quality control retained 771 paired entries, excluding 87 calibration-degenerate trials, and four subsequent alignment failures yielded 680 trials with finite final metrics. In planned analyses, H1 was not supported: cross-correlation refinement did not reduce pipeline-conditional root-mean-square error (RMSE) relative to onset-only alignment ($n = 399$; mean paired difference = -0.090 mm, Holm-adjusted $p = 0.442$), and the all-compatible sensitivity result was also non-significant. H2 was supported statistically in the planned population and remained detectable in sensitivity analysis, but not as a practically important method advantage: four common-grid resampling methods differed ($n = 398$, Kendall’s $W = 0.086$), while their mean errors differed by less than 0.1 mm. The planned H3 test was supported: split-fit calibration showed residuals 0.094 mm higher than deliberately leaky full-trajectory fitting on the same held-out support ($n = 396$, Holm-adjusted $p = 0.037$), whereas the all-compatible sensitivity result was not significant after correction. The composite baseline included 684 trials, compared with 680 for OFF-STAP. Among 398 planned pairs, baseline mean RMSE was 0.160 mm lower ($p = 0.042$), whereas the all-compatible paired difference was non-significant. The results support OFF-STAP as a traceable, leakage-aware, failure-transparent offline integration contract with a bounded, pipeline-conditional interpretation. They do not establish algorithmic superiority or robot performance accuracy.

Keywords: heterogeneous logs, offline data integration, data contracts, deterministic preprocessing, temporal alignment, spatial registration, calibration/evaluation separation, EV3 telemetry, HTC Vive tracking

ANALYSIS OF THE POTENTIAL FOR MODIFYING SELECTED COMBUSTION PARAMETERS OF RAPESEED OIL–N-HEXANE BLENDS IN A DIESEL ENGINE BY VARYING THE START-OF-INJECTION ANGLE

Dawid Tatarynow, Faculty of Mechanical Engineering, Lublin University of
Technology, d.tatarynow@pollub.pl

Abstract: Increasingly stringent emission regulations and directives promoting the use of renewable fuels are driving the search for diesel alternatives in compression ignition engines. The addition of n-hexane to rapeseed oil significantly reduces its viscosity, enabling common rail engine operation without structural modifications. The aim of this study was a preliminary assessment of the effect of changing the start-of-injection angle of the first pilot injection (P1) on indicated and dynamic combustion parameters of a rapeseed oil and 10% n-hexane blend (OR90Hex10). Tests were conducted on a chassis dynamometer using a Fiat Qubo 1.3 Multijet vehicle (Euro 5), with ECU control maps modified using WinOLS software. The test point corresponded to driving at 50 km/h under a 50 Nm load. The P1 start angle was varied in the range from -4 to $+4^{\circ}\text{CA}$ relative to the nominal setting, while the second pilot injection and main injection settings remained unchanged. The highest mean indicated pressure ($P_i = 0.999$ MPa) was obtained at nominal control. Both advancing and retarding P1 reduced P_i . Advancing P1 increased the maximum rate of pressure rise ($dp/d\alpha$) and the maximum heat release rate ($Q_{\max}$), while retarding softened the combustion process. A moderate P1 retard of $+2^{\circ}\text{CA}$ provided the best compromise: it markedly reduced $dp/d\alpha$ with an acceptable decrease in P_i , and shifted the peak combustion pressure to a range characteristic of diesel operation. The results indicate that the P1 angle can serve primarily as a tool for shaping combustion dynamics rather than improving engine energy output.

Keywords: ECU remapping; common rail; rapeseed oil; pilot injection timing

MONITORING STORM SEWER DISCHARGES AND ASSESSING THE QUALITY OF RECEIVING WATERS USING MULTI-PARAMETER AND ELECTROCHEMICAL PROBES

Edyta Wojtaś, Faculty of Environmental Engineering and Energy, Lublin University of Technology, e.wojtas@pollub.pl

Abstract: Stormwater discharges are a significant source of episodic pollution affecting the ecological status of surface waters. However, their short duration and high temporal variability hinder effective monitoring and assessment of their impact on receiving water bodies. This paper presents the development and real-time validation of a modular monitoring system designed to detect stormwater discharges and assess their impact on receiving water quality using signals from multiparameter probes and electrochemical sensors. The measurement network included multi-point monitoring conducted upstream of the discharge point, in the mixing zone, and downstream of the stormwater discharge point, as well as an additional measurement point located in a sewer manhole. Continuous measurements of physicochemical parameters, such as electrolytic conductivity, pH, temperature, dissolved oxygen concentration, and turbidity, were conducted with high temporal resolution, enabling the recording of dynamic changes in water quality during rainfall events. Field data were supplemented with laboratory analyses to calibrate and validate the measurement results. Data interpretation utilized statistical and chemometric methods, as well as machine learning algorithms, to identify relationships between water quality parameters, classify discharge events, and detect changes in the aquatic environment. Principal component analysis (PCA) was used to reduce data dimensionality and identify dominant trends, cluster analysis to group similar measurement events, and LDA and PLS-DA classification models to distinguish between environmental states and assess the effectiveness of electrochemical signals in detecting storm sewer discharges. The proposed approach enabled the effective identification of short-term changes in water quality associated with storm sewer discharges and demonstrated the usefulness of "electronic tongue" signals for event classification and assessment of the aquatic environment. The obtained results confirm the potential of modular, low-cost sensor systems supported by multivariate analysis as tools for continuous environmental monitoring and early detection of pollution episodes in urban water systems.

Keywords: storm sewerage, urban pollution monitoring, pollution indicators, electronic senses

A MULTI-LAYER CYBER-PHYSICAL 3D PRINTING SECURITY FRAMEWORK FOR THE AEROSPACE AND DEFENSE INDUSTRY

Grzegorz Budzik, Faculty of Mechanical Engineering and Aeronautics, Rzeszów
University of Technology, gbudzik@prz.edu.pl

Andrzej Paszkiewicz, Faculty of Electrical and Computer Engineering, Rzeszów
University of Technology, andrzejp@prz.edu.pl

Lucjan Śniezek, Faculty of Mechanical Engineering, Military University of
Technology, lucjan.sniezek@wat.edu.pl

Mirosław Surowaniec, Faculty of Mechanical Engineering and Aeronautics, Rzeszów
University of Technology, m.surowaniec@hsw.pl

Kamil Burczy, Doctoral School of the Rzeszów University of Technology, Rzeszów
University of Technology, kamil.burczy@global.lmco.com

Dariusz Rączka, Polskie Zakłady Lotnicze Sp. z o.o., Mielec, d.raczka@prz.edu.pl

Abstract: Additive technologies are based on the numerical preparation of data for the manufacturing process, starting from the 3D-CAD model, through the processing of solid and surface model data, up to the implementation of 3D printing itself. This article presents an analysis of a multi-layered approach to 3D printing process security as a cyber-physical manufacturing system. This approach can be applied to securing data used in the production of products using additive technologies used in the aerospace, energy, and defense industries. The analysis examines the potential and risks of interference or unauthorized access to numerical data resulting from the concept of additive manufacturing itself at subsequent stages of data processing and transfer. Given that, in the case of 3D printing technology, a significant number of stages of production planning and preparation occur in a software environment, special attention is paid to these process layers. The physical aspect of the additive manufacturing process, including pre- and post-processing stages, is also analyzed. Additionally, a framework approach to information security procedures was presented in the area of physical security resulting from the organizational structure of the additive manufacturing process itself as well as of an enterprise using 3D printing to produce aerospace or space components.

Keywords: Cyber-Physical Security, 3D Printing, data processing, Multi-Layer Analysis, aerospace and defence industry

DETECTION OF ATTACKS ON COMPUTER NETWORKS USING MACHINE LEARNING - PREDICTIVE MODEL

Imed El Fray, Faculty of Applied Informatics and Mathematics, Warsaw University of Life Sciences, Faculty of Computer Sciences and Information Technology, West Pomeranian University of Technology in Szczecin, ielfray@zut.edu.pl

Julia Stępień, Faculty of Computer Sciences and Information Technology, West Pomeranian University of Technology in Szczecin

Abstract: Intrusion detection systems based on machine learning achieve high effectiveness in optimal testing conditions. However, real environments come with limitations such as changing data characteristics, previously unknown attacks or low and delayed label availability. To address these challenges, this paper proposes an approach of continuous adaptation to streaming data in the form of active incremental learning. This solution further incorporates a semi-supervised learning approach to reduce expert involvement. The effectiveness of the approach was assessed under conditions simulating real-time system operation. The obtained results confirm the validity of adaptive mechanisms in the context of intrusion detection in a streaming environment.

Keywords: intrusion detection system, incremental learning, active learning, cybersecurity

MACHINE LEARNING MODELS TRAINED ON MULTIDIMENSIONAL GAS SENSOR SIGNALS WITH EXPLAINABLE AI INTERPRETATION FOR SURFACE WATER AND WASTEWATER CLASSIFICATION

Magdalena Pilat-Rożek, Faculty of Mathematics and Information Technology, Lublin University of Technology, m.pilat-rozek@pollub.pl

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University of Technology, g.lagod@pollub.pl

Abstract: In this study, the same machine learning models were applied to analyze multidimensional data obtained by a gas sensor matrix, concerning surface water and wastewater. The aim of this study was to compare the application of the same machine learning methods trained on data from different types of polluted water and to apply explainable artificial intelligence (XAI) methods to interpret the decisions made by the trained models. The performance of the mentioned methods, both supervised and unsupervised, was much better for the data from the more polluted samples and for the wastewater samples. Applying the selected unsupervised methods to the surface water data did not yield a clear separation of distinct groups for all observations. Nevertheless, the supervised methods showed greater potential for drawing conclusions – the vast majority of observations were correctly classified to the true location of the sampling point. However, the accuracy of the supervised models trained on the data derived from wastewater samples is higher than the accuracy of the models trained on surface water samples. To better understand the basis of these classification outcomes, several XAI techniques were employed to identify which sensor signals and features contributed most significantly to models' predictions, providing greater interpretability of the obtained results.

Keywords: multidimensional data analysis, machine learning, gas sensor array, explainable artificial intelligence (XAI), surface water, wastewater

ENTROPY-BASED ANALYSIS OF ACTIVATED SLUDGE PARAMETERS

Aleksandra Kozłowska, Faculty of Environmental Engineering and Energy, Lublin University of Technology, aleksandra.kozlowska1@pollub.edu.pl

Michał Staniszewski, Faculty of Environmental Engineering and Energy, Lublin University of Technology, m.staniszewski@pollub.pl

Roman Babko, Schmalhausen Institute of Zoology, National Academy of Sciences of Ukraine, rbabko@ukr.net

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University of Technology, g.lagod@pollub.pl

Abstract: Activated sludge constitutes a complex microbial ecosystem the spatial organization and community structure of which play a crucial role in the effectiveness of bioreactor performance. Conventional assessments of activated sludge are primarily based on microscopic observations of floc morphology and the identification of bioindicator organisms. Although floc size can be quantified relatively easily, the objective characterization of floc shape and microbial community structure remains challenging. Therefore, there is a growing demand for quantitative and reproducible analytical methods capable of supporting traditional biological approaches. This study applied mathematical methods derived from information theory, with particular emphasis on entropy-based metrics, to characterize and compare both the geometric properties of activated sludge flocs and the structure of associated microbial communities. Activated sludge samples were collected from various stages of the technological line at the Hajdów wastewater treatment plant in Lublin, Poland. Microscopic observations were performed with a standard biological microscope, and digital photographic documentation was acquired for subsequent image analyses. Based on the collected data, selected metrics, including Shannon entropy and related statistical metrics, were calculated and compared across sampling locations to evaluate the differences in floc morphology and microbial community composition. The obtained results demonstrate the potential of entropy-based metrics for the quantitative assessment of activated sludge structure and for distinguishing between different operational conditions within the biological factor of the treatment process. The proposed approach may contribute to the development of advanced tools for wastewater treatment monitoring and process control. Furthermore, the integration of quantitative entropy-based analytical methods with modern artificial intelligence techniques, particularly deep-learning-based image analysis, offers significant potential for the automated detection, classification, and quantification of microscopic objects. Such integration could substantially reduce the time required for biological process assessment while providing rapid, objective, and cost-effective quantitative data to support wastewater treatment management.

Keywords: Entropy-based analysis, activated sludge parameters, flock size and shape, community structure, automated image analysis

AMPLITUDE-RANGE REFLECTANCE TOMOGRAPHY FOR ENERGY-EFFICIENT INDOOR OBJECT TRACKING

Michał Styła, Information Technology Research & Development Centre (CBRTI sp. z o. o.), michal.styla@cbrti.pl

Przemysław Adamkiewicz, Information Technology Research & Development Centre (CBRTI sp. z o. o.), Institute of Computer Science and Innovative Technologies, WSEI University, przemyslaw.adamkiewicz@cbrti.pl

Abstract: This paper presents an energy-efficient, non-intrusive system for indoor object detection and tracking based on reflection tomography. The proposed architecture combines distributed ceiling-mounted microwave probes with a central localization engine. Each probe integrates a 10.585 GHz continuous-wave radio unit, an array antenna, an STM32 F4 microcontroller, a 12-bit analog-to-digital converter, and CAN-bus communication. Motion is captured through Doppler-induced variations in the returned signal, enabling the sampling rate and measurement schedule to be reduced or adapted while preserving measurement resolution. A forward model simulates complex continuous-wave responses for direct and wall-reflected propagation paths with additive noise. The inverse stage uses measured amplitudes only and therefore does not require phase information. For every candidate grid point, range-dependent Gaussian weights are accumulated over antennas and time samples and normalized to generate a spatial probability map. Numerical examples illustrate the reconstruction of a moving target trajectory and the antenna-dependent behavior of estimated ranges. The resulting hardware-algorithm framework demonstrates the feasibility of combining low-power distributed sensing with amplitude-only localization in rooms containing architectural obstacles. Its principal strengths are non-visual operation, adjustable data acquisition, and a favorable balance among localization capability, communication load, and energy consumption. The simplified inverse model does not explicitly compensate for phase or multipath reflections, indicating the main direction for further improvement and experimental validation.

Keywords: Reflection Tomography, Indoor Localization, Object Tracking, Doppler Sensing, Amplitude-Only Reconstruction, Microwave Sensors, CAN Bus, Energy-Efficient Sensing

PHYSICS-CONSTRAINED UNROLLED RECONSTRUCTION OF SLOWNESS MAPS IN ULTRASOUND TRANSMISSION TOMOGRAPHY

Dariusz Majerek, Faculty of Mathematics and Information Technology, Lublin
University of Technology, d.majerek@pollub.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A., Institute of Computer
Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A., Institute of
Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Abstract: This study introduces an interpretable physics-constrained framework for reconstructing two-dimensional slowness maps in transmission ultrasound tomography using only time-of-flight (ToF) measurements. The inverse problem is formulated with a differentiable straight-ray projection operator, providing a controlled baseline between data fidelity and learned image regularization rather than full-waveform inversion. The method initializes the image by Tikhonov regularization and unfolds eight proximal iterations. Each iteration combines the explicit data-consistency gradient $A^T(Ax - y)$ with a bounded residual correction predicted by a measurement-conditioned U-Net. The network receives the current estimate, Tikhonov image, data-consistency map, backprojection, previous residual, and field-of-view mask, while auxiliary heads estimate inclusion masks and boundaries. Training employs image, foreground, edge, segmentation, data-consistency, and deep-supervision losses. Evaluation on 512 synthetic validation cases showed that fine-tuning the mask head produced the strongest deployable variant, reaching a PSNR of 26.2371 dB, Dice of 0.9148, IoU of 0.8489, boundary IoU of 0.7246, and mean absolute data-consistency error of 0.000351. Boundary-focused calibration increased boundary IoU to 0.7272 but slightly reduced global mask IoU, revealing a contour-versus-region trade-off. A diagnostic oracle-gated residual denoiser reached approximately 26.596 dB PSNR, indicating remaining local amplitude-correction capacity but no deployable solution to topology errors. The results show that embedding an explicit forward operator in an unrolled network yields stable, measurement-consistent reconstructions from information-limited ToF data and provides a reproducible baseline for future models using waveform, amplitude, phase, or multi-feature measurements.

Keywords: ultrasound transmission tomography, time of flight, inverse problems, physics-guided deep learning, unrolled optimization, proximal reconstruction, data consistency

MATRIX-FREE RECONSTRUCTION FOR PORTABLE 3D ULTRASONIC NDE

Dariusz Wójcik, Research and Development Center, Netrix S.A., Institute of Computer Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A., Institute of Computer Science and Innovative Technologies, WSEI University, tomasz.rymarczyk@netrix.com.pl

Michał Gołębek, Research and Development Center, Netrix S.A., michal.golabek@netrix.com.pl

Barbara Stefaniak, Research and Development Center, Netrix S.A., barbara.stefaniak@netrix.com.pl

Oleksii Hyka, Research and Development Center, Netrix S.A., oleksii.hyka@netrix.com.pl

Abstract: Portable three-dimensional ultrasonic non-destructive evaluation requires volumetric reconstruction under severe memory, computational, and thermal constraints. This study presents an edge-oriented imaging pipeline that reconstructs spatial reflectivity directly from raw radio-frequency data on a Raspberry Pi 5. Under the First Born approximation, the inverse problem is implemented as a matrix-free adjoint operation; compact delay and weighting tables replace an explicit system matrix exceeding 5 GB for 1024^2 grids. Radio-frequency signals are quantized to signed INT8 values, accumulated in 32-bit registers, and processed by parallel Just-In-Time compiled kernels on four Cortex-A76 cores. The prototype combines a 32-element, 2 MHz linear array, 32-channel acquisition over USB 3.0, band-pass filtering with time-gain compensation, and OpenGL-based 3D maximum-intensity-projection visualization. Performance was assessed using tissue-mimicking and resin-aluminum phantoms against a Float32 baseline. INT8 processing reduced reconstruction latency from 172.4 ms to 7.0 ms and increased reconstruction throughput from 5.8 to 142.7 frames per second, corresponding to approximately a 24-fold speedup. End-to-end pipeline latency fell from 384.6 ms to 27.0 ms, while throughput increased from 2.6 to 37.0 frames per second. Reconstructed images achieved 34.9 dB PSNR and exhibited negligible visual degradation relative to Float32 output. The results demonstrate that matrix-free integer reconstruction can support real-time 3D ultrasonic inspection on low-cost embedded hardware without materially compromising image quality. The proposed architecture provides a practical basis for handheld field-deployable NDE systems and further edge-based ultrasonic imaging research.

Keywords: ultrasonic non-destructive evaluation, 3D imaging, Raspberry Pi 5, matrix-free reconstruction, INT8 quantization, JIT compilation, edge computing, real-time imaging

PHYSICS-INFORMED IDENTIFICATION OF RADIAL CLEARANCE IN A NONLINEAR 4-DOF ROLLING BEARING MODEL

Bartłomiej Ambrożkiewicz, Faculty of Mathematics and Technical Information Technology, Lublin University of Technology, Nadbystrzycka 36, 20-618 Lublin, Poland, b.ambrozkiwicz@pollub.pl

Maciej Czarnacki, Faculty of Mathematics and Technical Information Technology, Lublin University of Technology, Nadbystrzycka 36, 20-618 Lublin, Poland, m.czarnacki@pollub.pl

Abstract: Radial internal clearance strongly influences the nonlinear dynamic response of rolling element bearings and is therefore an important parameter in condition monitoring and predictive maintenance. This study develops a physics-informed neural network (PINN) framework for inverse identification of bearing clearance in a strongly nonlinear 4-DOF dynamic model. The proposed formulation extends reduced bearing models by explicitly describing the horizontal and vertical motion of both the shaft and the bearing housing, while the interaction between the two subsystems is governed by intermittent nonlinear Hertzian contact. The PINN is trained to simultaneously reconstruct the four displacement responses and estimate the unknown radial clearance by embedding the governing equations of motion directly into the loss function. Synthetic reference responses generated using a 4th-order Runge-Kutta solver are used for numerical validation. The robustness of the proposed approach is additionally evaluated under different levels of noise in order to assess its suitability for future application to experimental vibration measurements. For the investigated operating condition, the identified clearance converges to the prescribed reference value with a relative error of approximately 0.008%. Moreover, the reconstruction error of the four-dimensional dynamic response remains below 0.05% even for a 10% noise level. These results demonstrate that the PINN-based inverse formulation retains high parameter-identification accuracy despite increased model complexity and measurement uncertainty. The developed 4-DOF framework provides a basis for future identification of bearing operating parameters directly from experimental vibration signals.

Keywords: Physics-informed neural networks; rolling element bearing; radial internal clearance; nonlinear dynamics; parameter identification

DESIGN AND DEVELOPMENT OF AN INTEGRATED TEST BENCH FOR VIBRATION ENERGY HARVESTING WITH A MEASUREMENT AND CONTROL SYSTEM DEVELOPED IN LABVIEW

Krzysztof Skiba, Lublin University of Technology, Faculty of Electrical Engineering and Computer Science, Poland, k.skiba@pollub.pl

Robert Bąbel, Faculty of Aviation, Polish Air Force University, Poland, r.babel@law.mil.pl

Zbigniew Czyż, Faculty of Aviation, Polish Air Force University, Poland, z.czyz@law.mil.pl

Paweł Karpiński, Faculty of Production Engineering, University of Life Sciences in Lublin, Poland, pawel.karpinski@up.edu.pl

Bartłomiej Ambrozkiewicz, Faculty of Mathematics and Technical Information Technology, Lublin University of Technology, Poland, b.ambrozkiewicz@pollub.pl

Abstract: The experimental investigation of vibration energy harvesting systems requires dedicated test benches capable of generating controlled mechanical excitations and accurately measuring the resulting electrical response. This paper presents the design and development of an integrated test bench intended for evaluating the performance of a piezoelectric energy harvesting system. The mechanical structure was designed in the SolidWorks environment, enabling the development of a three-dimensional CAD model incorporating the supporting frame, excitation system, mounting components, and interchangeable elements of the investigated device. Particular attention was paid to structural adaptability, accessibility of measurement points, and repeatability of experimental conditions. In parallel, a measurement and control application was developed in the LabVIEW environment to support the integration of measurement instruments, excitation control, and data acquisition. The application architecture includes functions for setting selected excitation parameters, monitoring measurement signals in real time, recording experimental data, and performing preliminary signal processing. The proposed measurement system is designed to acquire mechanical and electrical parameters, including vibration frequency, amplitude, generated voltage, and electrical power, enabling the evaluation of energy conversion performance under different operating conditions. The integration of the CAD-designed mechanical structure with the LabVIEW measurement and control environment provides a flexible experimental platform for investigating piezoelectric energy harvesting systems. The developed solution establishes a basis for subsequent experimental validation, comparative analysis of different system configurations, and optimisation of the energy conversion.

Keywords: vibration energy harvesting, test bench design, SolidWorks, LabVIEW, Measurement and control system

ARTIFICIAL AND COMPUTATIONAL INTELLIGENCE

EXPLAINABLE CNN-BASED BOTTLENECK DIAGNOSIS IN HUMAN-COBOT MANUFACTURING USING PROCESS HEATMAPS: AN OPERATIONS AND QUALITY MANAGEMENT PERSPECTIVE

Łukasz Kański, Faculty of Economics, Maria Curie-Skłodowska University,
lukasz.kanski@mail.umcs.pl

Abstract: Human-robot collaborative manufacturing, positioned at the core of the Industry 5.0 paradigm, increases the stochasticity of production systems through human variability, safety-related stops, and resource-sharing constraints. In such environments, rapid identification of dominant bottlenecks and their root causes is critical to operational resilience, production-management responsiveness, and preserving the human-centric character of operations. This study proposes an explainable bottleneck-diagnosis framework based on convolutional neural networks (CNNs) that leverages process heatmaps derived from a discrete-time flow-line simulation model inspired by the digital twin concept. Each simulation run is encoded as a three-channel heatmap (queue length, station busy state, and downtime), yielding a compact spatio-temporal “process fingerprint” suitable for image-based representation learning. We consider a six-class taxonomy: balanced operation, bottleneck caused by human fatigue, bottleneck caused by cobot performance degradation, bottleneck caused by safety stops in a human-cobot cell, bottleneck caused by robot failure, and supply delays (line starvation). On a balanced dataset of 1,500 synthetic samples, the CNN achieves a test accuracy of 0.938 (macro-F1 = 0.938; 95% Wilson confidence interval for accuracy: 0.898–0.963). An ablation study shows that multi-channel heatmaps improve accuracy by 0.10 compared with queue-only heatmaps. Explainability is operationalised using Gradient-weighted Class Activation Mapping (Grad-CAM), which consistently localises station-time regions associated with queue build-up and downtime patterns, providing process engineers with evidence that can be translated into corrective actions. The results indicate that simulation-generated heatmaps can support transparent and scalable bottleneck analytics for human-cobot manufacturing, enabling rapid prototyping prior to deployment on shop-floor data and providing an evidence-based decision-support instrument for operations and quality management.

Keywords: digital twin; simulation; Industry 5.0; human-robot collaboration; bottleneck diagnosis; process heatmaps; convolutional neural networks; explainable artificial intelligence; Grad-CAM; operations management; quality management

A HYBRID MACHINE LEARNING AND GENETIC ALGORITHM APPROACH FOR WEATHER-INFORMED BIOGAS PROCESS OPTIMIZATION

Patryk Organiściak, Faculty of Electrical and Computer Engineering, Rzeszów
University of Technology, org@prz.edu.pl

Paweł Kuraś, Faculty of Computer Science, Electronics and Telecommunications, AGH
University of Krakow, pawel.kuras@agh.edu.pl

Arkadiusz Stęchly, Faculty of Electrical and Computer Engineering, Rzeszów
University of Technology, a.stechly@prz.edu.pl

Adam Masłoń, Faculty of Civil and Environmental Engineering and Architecture,
Rzeszów University of Technology, amaslon@prz.edu.pl

Anna Turek, Faculty of Mathematics and Applied Physics, Rzeszów University of
Technology, 169856@stud.prz.edu.pl

Abstract: Efficient control of the anaerobic digestion process in municipal wastewater treatment plants poses an engineering challenge due to the high inertia of the system and the impact of uncontrolled external disturbances. This paper presents a novel approach to optimizing feedstock composition (the ratio of primary to excess sludge) to maximize biogas production. Unlike classical control methods, the proposed solution accounts for the impact of exogenous factors, such as ambient temperature and precipitation, which determine the physicochemical parameters of raw sludge. To build an effective model on a limited dataset, a Spatial Disaggregation technique was applied, merging data from four parallel digestion chambers. A hybrid decision-making system was developed, integrating a Random Forest model with a Genetic Algorithm (GA). The resulting predictive model achieved accuracy ($R^2=0.756$, $MAPE=7.4\%$) under LODO validation, confirming that incorporating time delays in weather data allows for precise prediction of efficiency drops. The application of the evolutionary algorithm enabled the determination of optimal control trajectories, allowing for increased energy yield under difficult operating conditions. The presented solution constitutes a functional module for a Decision Support System (DSS), enabling a transition from reactive to prescriptive strategies.

Keywords: anaerobic digestion, genetic algorithms, predictive control, machine learning, process optimization, biogas

FORECASTING CO₂ EMISSIONS FROM SOILS AMENDED WITH SEWAGE SLUDGE BIOCHAR USING ARTIFICIAL NEURAL NETWORKS

Justyna Kujawska, Faculty of Environmental Engineering and Energy, Lublin University of Technology, j.kujawska@pollub.pl

Monika Kulisz, Faculty of Management, Lublin University of Technology, m.kulisz@pollub.pl

Abstract: The aim of this study was to develop neural models to forecast CO₂ emissions from soils amended with sewage sludge biochar and to determine the impact of input variable selection on modeling quality. The analysis was based on data from a 36-day experiment on sandy soil and chernozem, with varying biochar application rates and production temperatures. Modeling was performed using Statistica software with MLP-type artificial neural networks trained via the BFGS algorithm. The output variable was the soil CO₂ emission flux. Five variants of input variable sets were analyzed: (1) a full set of 16 parameters, including biochar application rate, pyrolysis temperature, soil type, incubation time, carbon forms: total (TOC), residual (ROC), and dissolved (DOC), pH, total nitrogen, nitrate nitrogen (N–NO₃), ammonium nitrogen (N–NH₄), and the content of phosphates, sodium, magnesium, potassium, and calcium; (2) four experimental parameters: biochar application rate, pyrolysis temperature, soil type, and incubation time; (3) three forms of organic carbon: TOC, ROC, and DOC; (4) three forms of nitrogen: total, N–NO₃, and N–NH₄; and (5) pH and the content of phosphates, sodium, magnesium, potassium, and calcium. Networks with different numbers of input and hidden neurons were compared by evaluating the agreement between modeled values and measured results. The MLP 16–3–1 model, incorporating the full set of input variables, achieved a correlation coefficient of $R = 0.70$. For the model using four experimental parameters, $R = 0.77$ was obtained. Thus, limiting the set of input variables resulted in a higher correlation coefficient. In this comparison, the inclusion of additional physicochemical parameters did not improve the network model's quality. The results indicate that the ANN model can serve as a useful tool for estimating CO₂ emissions.

Keywords: mathematical modeling, artificial neural networks, MLP, input variable selection, CO₂ emissions, biochar

A DETERMINISTIC MEMORY ARCHITECTURE FOR LARGE LANGUAGE MODELS (LLM) WITH KNOWLEDGE LIFECYCLE MANAGEMENT (KLM)

Mateusz Gogola, Poznań University of Technology,
mateusz.gogola@student.put.poznan.pl

Abstract: Large language models lack built-in mechanisms for persistent and verifiable memory, leading to factual inconsistencies in long interaction sequences. Unlike the Retrieval-Augmented Generation (RAG) technique, which relies on vector similarity without explicit knowledge lifecycle management, and the MemGPT architecture, which delegates memory management to the language model itself, the proposed architecture separates these responsibilities. Memory evolution proceeds deterministically through mechanisms of activation decay, reinforcement, and threshold-based archival, while higher-layer consolidation results are made available only upon detection of actual structural change. The language model closes the feedback loop – automatically detected signals from natural user reactions modify the activation of memory nodes. This paper describes a designed and implemented memory system architecture in which knowledge is represented as structured knowledge nodes with quantitative activity and reliability parameters. Activation decays exponentially over time, following the Ebbinghaus forgetting curve, and increases with the number of node confirmations — the reinforcement mechanism is inspired by the ACT-R base-level activation model. The system organizes knowledge across four layers: L1 stores knowledge nodes with full quantitative parameters; L2 records snapshots of thematic scope state; L3 generates temporal summaries, made available in the response context only upon detection of structural divergence between snapshots; L4 stores critical facts subject to automatic revalidation and archival when activity and reliability criteria are no longer met. Query routing deterministically directs queries along one of two paths: for queries about known facts, the response is drawn directly from memory layers; for all others, the language model generates a response based on a structurally compressed memory context and the relation graph. The result is a working prototype of a memory system with functional knowledge lifecycle mechanisms: ingestion, consolidation, promotion, and fact revalidation. Preliminary tests indicate the potential to reduce factual inconsistencies in multi-session interactions without increasing the model’s context window.

Keywords: Large Language Models (LLMs), Memory Architecture, Knowledge Lifecycle Management, Factual Consistency, Knowledge Representation, Deterministic Systems, Context Management

INVERSE DESIGN OF MULTIRING OPTICAL FIBRES USING MACHINE LEARNING FOR BEAM SHAPING APPLICATIONS

Marta Dziuba-Koziel, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, m.dziuba@pollub.pl

Abstract: Recent advances in machine learning have shown strong potential to accelerate the design of optical fibres by predicting beam characteristics from structural parameters. However, practical applications often require the inverse approach, in which desired beam properties are specified a priori and the corresponding fibre configuration must be determined. This study proposes an inverse design framework for multiring optical fibres using machine learning techniques. Building on a dataset of numerically simulated fibre configurations and their corresponding beam characteristics, including beam flatness, edge steepness, and full width at half maximum (FWHM), an inverse mapping is developed to predict fibre parameters from target beam specifications. Unlike conventional forward models, which estimate beam properties from refractive index profiles, the proposed approach addresses the more challenging inverse problem, which is inherently non-unique and ill-posed. Several machine learning strategies, including single- and multi-target regression models, are examined to determine whether beam parameters should be predicted jointly or independently. The study also assesses the impact of feature selection and parameter representation on the stability and accuracy of the inverse model. Particular attention is paid to the role of derived geometric descriptors of the refractive index profile, which have previously been shown to significantly influence forward prediction performance. Preliminary results indicate that the inverse model can identify fibre configurations that produce beam characteristics close to the desired specifications, significantly reducing the need for exhaustive numerical simulations. The proposed framework provides a foundation for automated fibre design and demonstrates the feasibility of machine-learning-assisted inverse engineering for photonic structures.

Keywords: machine learning, photonic design, inverse design, multiring optical fibres, beam shaping, data-driven modelling

CUSTOM RECURRENT-BASED FRICTION PREDICTION IN A WEAR-RESISTANT HARDFACING ALLOY

Krzysztof Dziedzic, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, k.dziedzic@pollub.pl

Abstract: Predicting tribological behaviour in multi-component wear-resistant alloys is difficult because of their complex microstructure and the nonlinear phenomena in the contact zone. The Fe–Mn–C–B–Si–Ni–Cr coating combines hard carbide (Fe_3C , Cr_7C_3) and boride (Fe_2B , FeB) phases with a ductile austenitic–martensitic matrix. A custom recurrent neural network predicts its friction behaviour. Tribological tests were performed on a high-temperature ball-on-disc tribometer (THT 1000, Anton Paar), which continuously recorded the coefficient of friction (COF). Because point-wise analysis could not capture the dynamic nature of wear, raw time-signals were processed with a moving-window technique to extract statistical descriptors. A custom two-branch recurrent network, TriboRNN, was developed. The recurrent branch comprises a bidirectional GRU (Gated Recurrent Unit) followed by an LSTM (Long Short-Term Memory) with additive attention. It processes the descriptors, whereas a dense branch encodes static alloy and process parameters. The model achieved a pooled R^2 (coefficient of determination) of 0.911 and an RMSE (Root Mean Square Error) of 0.0312 on the withheld test set. It matched a stacked-LSTM baseline in accuracy but proved far more reproducible. Its seed-to-seed variance was roughly an order of magnitude lower. The method predicts the friction behaviour of iron-based hardfacing systems and helps address the limited datasets that constrain tribological research.

Keywords: artificial intelligence, recurrent algorithms, attention mechanism, coefficient of friction, coated alloy

TRAINING MACHINE LEARNING AGENT BEHAVIORS IN UNITY: PROXIMAL POLICY OPTIMIZATION VS. SOFT ACTOR-CRITIC ALGORITHMS

Krystian Czajkowski, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, s95379@pollub.edu.pl

Maria Skublewska-Paszkowska, Faculty of Electrical Engineering and Computer
Science, Lublin University of Technology, maria.paszkowska@pollub.pl

Paweł Powroźnik, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, p.powroznik@pollub.pl

Marcin Barszcz, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, m.barszcz@pollub.pl

Krzysztof Dziedzic, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, k.dziedzic@pollub.pl

Sylwester Korga, Faculty of Electrical Engineering and Computer Science, Lublin
University of Technology, s.korga@pollub.pl

Abstract: The gaming evolution is strictly associated with machine learning development, such as Reinforcement Learning. Thus, there is an ongoing need to study and apply machine learning algorithms to games to achieve human-like agent behavior. Among various algorithms, Proximal Policy Optimization (PPO) and Soft Actor-Critic (SAC) are among the state-of-the-art reinforcement learning methods. They have been widely adopted due to their optimal balance of performance, stability, and ease of implementation. Factors such as the test environment, reward function, neural network architecture, and computational resource availability significantly influence the relative performance of both algorithms. Thus, the main aim of our study is to analyze PPO and SAC reinforcement learning methods across three Unity-created environments, using parallel learning with discrete and continuous actions. SAC performed better in simpler scenarios, whereas PPO achieved better results in more complex environments. The ablation study assesses hyperparameter sensitivity. Batch size had a stronger impact on SAC performance, whereas buffer size had a stronger impact on PPO.

Keywords: Unity, ML-Agents, PPO, SAC

AUTOMATIC METHODS FOR 3D MOTION TRAJECTORIES GAP FILLING: CUSTOM-BASED KALMAN VS. BILSTM

Kamil Żelazowski, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, s97781@pollub.edu.pl

Wojciech Wojciechewicz, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, s97767@pollub.edu.pl

Maria Skublewska-Paszkowska, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, maria.paszkowska@pollub.pl

Paweł Powroźnik, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, p.powroznik@pollub.pl

Abstract: Modern data analysis increasingly relies on time series data across diverse domains, such as biomechanics, medicine, sports, and computer animation. A special case of this data type is one generated from optical motion capture systems, enabling the precise spatiotemporal tracking of anatomical marker positions. However, during dynamic and fast movement recordings, some markers may not be registered properly, mainly due to their obscuration or an insufficient number of cameras. While continuous trajectories provide the basis for human movement analysis, their utility is heavily dependent on the accurate registration of all measurement points. The post-processing of motion capture data is highly time-consuming, thus, adjusting the appropriate and highly reliable gap-filling method is extremely important for further data analysis. In this study, we propose a novel, custom-based Kalman filter for gap filling of dance motion capture trajectories. This method integrates the three-dimensional positions of markers, their velocities, and accelerations. The proposed method is compared with the basic Kalman filter and a bidirectional Long Short-Term Memory (BiLSTM) model, which is highly effective for sequential data imputation. Given these dual paradigms, this study aims to compare the classical mathematical model with the modern machine learning approach in the context of motion capture data reconstruction, evaluating their respective effectiveness across varying spatial and temporal characteristics of missing data. Several examinations, based on the number of missing markers (from 2 to 14) in the given marker's neighbor group across various frame numbers (from 100 to 500), were performed. The BiLSTM model achieved lower RMSE values than the custom Kalman-based filter in almost all scenarios and was also highly stable for a small number of missing markers. However, the accuracy of both methods deteriorated with a large number of missing markers, indicating a significant impact of the spatial distribution of missing data on reconstruction quality.

Keywords: Kalman filter, BiLSTM, motion capture, gap filling

ADVANCES IN AUTOMATIC SEEDLING DETECTION AND LOCALIZATION USING CNN-BASED COMPUTER VISION FOR PRECISION WEED CONTROL IN PRECISION AGRICULTURE

Lukasz Gierz, Faculty of Mechanical Engineering, Poznań University of Technology,
lukasz.gierz@put.poznan.pl

Dominik Ryder, Faculty of Mechanical Engineering, Poznań University of Technology,
dominik.z.ryder@gmail.com

Lukasz Wargula, Faculty of Mechanical Engineering, Poznań University of
Technology, lukasz.wargula@put.poznan.pl

Murat Köklü, Department of Computer Engineering, Selcuk University Technology
Faculty, mkoklu@selcuk.edu.tr

Abstract: It can be observed that dynamic developments in artificial intelligence are contributing to the evolution of existing techniques used in agricultural research and crop protection systems. Currently, innovative methods are being sought to support unit processes such as precision agrochemical application, while at the same time monitoring crop health and reducing herbicide usage. The development of innovative technology using convolutional neural networks (CNNs) for the automatic detection, classification, and localization of plant seedlings seems highly desirable. This will translate into obtaining localized spot-spraying capabilities based on the specific morphological structure and geometric positioning of the young plants. This study aims to apply convolutional neural networks to the classification and precise localization of radish, parsley, and cress seedlings, supported by comparative image processing using the LAB and HSV color spaces combined with Otsu thresholding. The results show that LAB-based segmentation using *a* channel is highly effective and stable when identifying plant morphological structures using CNNs, particularly under challenging illumination conditions. The use of CNNs, contour analysis, and geometric center (centroid) calculations together with dataset expansion via Auxiliary Classifier Generative Adversarial Networks (AC-GAN) shows the most favorable results. The best results were obtained for a sample during the intermediate growth stage (5–12 days) under sunny conditions, where the LAB-based approach achieved a precision of 0.89, recall of 0.84, and accuracy of 0.93. The CNN model achieved an overall classification accuracy of 93% on a balanced dataset comprising over 1,200 samples generated from approximately 60 original field images using AC-GAN, confirming its effectiveness for the classification of seedling microstructures under realistic field conditions.

Keywords: seedling identification; spot-spraying, image segmentation (LAB, HSV); convolutional neural networks (CNN); auxiliary classifier generative adversarial networks (AC-GAN); precision agriculture.

PARAMETER IDENTIFICATION OF A DYNAMIC SYSTEM UNDER RANDOM EXCITATION USING NEURAL NETWORKS

Lukasz Rykała, Faculty of Mechanical Engineering, Military University of Technology,
lukasz.rykala@wat.edu.pl

Arkadiusz Rubiec, Faculty of Mechanical Engineering, Military University of
Technology, arkadiusz.rubiec@wat.edu.pl

Karol Cieřlik, Faculty of Mechanical Engineering, Military University of Technology,
karol.cieslik@wat.edu.pl

Mirosław Przybysz, Faculty of Mechanical Engineering, Military University of
Technology, miroslaw.przybysz@wat.edu.pl

Abstract: This paper focuses on identifying physical parameters of a mechanical system subjected to random excitation. Stochastic signal is the only input, which eliminates classical harmonic or impulse test signals. A large synthetic dataset is generated by numerically simulating the mechanical quarter Unmanned Ground Vehicle (UGV) model across a wide range of stiffness and damping values under band-limited white noise excitation with additive measurement noise. The Power Spectral Density (PSD) of the measured response is computed using Welch's estimator and used as a feature vector. A multilayer perceptron (MLP) regression model is subsequently trained to map the spectral features to the physical parameters (c , k). Results demonstrate that the machine learning-based approach achieves high accuracy while offering robustness to measurement noise. The performance of the proposed method is evaluated in terms of selected assessment quality indicators. The influence of selected parameters on identification accuracy is systematically investigated, providing practical guidelines for future experimental studies.

Funding: This work was financed by the Military University of Technology under research project UGB 22-104/2026 (531-000104-W100-22).

Keywords: system identification, dynamical system, UGV, quarter model, random excitation, machine learning, neural network, parameter estimation

ANALYSIS OF THE IMPACT OF NATURAL LANGUAGE SELECTION IN LARGE LANGUAGE MODELS (LLMS) ON ENERGY CONSUMPTION

Tomasz Szymczyk, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, t.szymczyk@pollub.pl

Marcin Badurowicz, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, m.badurowicz@pollub.pl

Abstract: Large Language Model (LLM) inference is computationally intensive, yet the extent to which the interaction language affects energy consumption remains insufficiently understood. This study investigates whether inference energy consumption varies across six European languages: Polish, English, German, French, Spanish, and Russian. Three open-weight models, Llama3.1-8b, Gemma-3-12b, and Qwen2.5-14b, were evaluated using ten semantically equivalent prompts, each translated into the six languages and repeated three times. Experiments were conducted on a workstation-class server equipped with an AMD Radeon RX 7900 XT GPU and the Ollama inference framework. Whole-system power consumption was measured using a calibrated HIOKI PW3337 power meter, and energy efficiency was expressed as energy per generated token (EPT). Mean EPT varied substantially among models: Llama3.1-8b consumed 6.43 J/token, Qwen2.5-14b 10.23 J/token, and Gemma-3-12b 10.87 J/token. Kruskal–Wallis tests identified statistically significant between-language differences only for Llama3.1-8b; no significant differences were found for Qwen2.5-14b or Gemma-3-12b. However, regression analysis for Llama3.1-8b showed that response length was the dominant predictor of EPT, as fixed inference overhead was amortized over longer outputs. The findings indicate that apparent language-dependent differences in inference energy are driven primarily by generated-output length rather than by language itself. Energy efficiency also depends strongly on model architecture, tokenizer behavior, and inference implementation, highlighting the importance of response-length control and whole-system measurement in Green AI benchmarking.

Keywords: energy consumption, large language models, natural language processing, LLM, tokens

TRUSTWORTHY DEEP LEARNING-BASED ARCHITECTURES FOR THE EVALUATION PROGRESSION OF RETINITIS PIGMENTOSA

Maria Skublewska-Paszkowska, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, maria.paszkowska@pollub.pl

Paweł Powroźnik, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, p.powroznik@pollub.pl

Katarzyna Nowomiejska, Faculty of Medicine, Chair and Department of General and Pediatric Ophthalmology, Medical University of Lublin, katarzyna.nowomiejska@umlub.pl

Robert Rejdak, Faculty of Medicine, Chair and Department of General and Pediatric Ophthalmology, Medical University of Lublin, robertrejdak@yahoo.com

Paweł Karczmarek, Faculty of Mathematics and Information Technology, Lublin University of Technology, p.karczmarek@pollub.pl

Kamil Jonak, Faculty of Mathematics and Information Technology, Lublin University of Technology, k.jonak@pollub.pl

Abstract: Retinitis pigmentosa (RP) is a group of inherited retinal diseases that often cause retinal cell loss. Depending on the type of cell primarily affected, RP can be categorised into rod-dominant (classical RP) and cone-dominant – cone-rod dystrophy (CORD). These disorders initially affect photoreceptors and the retinal pigment epithelium and, in later stages of the disease, also act on cells of the inner layers. Therefore, it is necessary to monitor the progression of the disease in order to adapt the appropriate treatment. In this study, we propose a trustworthy application to monitor RP progression utilising several custom-designed, reliable and robust deep learning architectures, such as the Convolutional Gated Recurrent Unit U-Net, Deep CNN-GRU, Residual Attention Network, and Residual Self-Attention Vision Transformer. This study utilises a dataset gathered over three years at the Chair and Department of General and Paediatric Ophthalmology of the Medical University in Lublin to provide three analogous data samples at different time intervals. The models are assessed using a trustworthy protocol that combines accuracy, precision, recall, F1-score metrics, Gradient-weighted Class Activation Mapping visualisation to indicate the most relevant parts of images, indicating the RP and CORD distortions, and model generalisation by verifying how noise data affects the classification results. We proposed a new classifier-derived progression index, which determines how much the analysed image deviates from a healthy case based on the disease probability obtained by the DL model. This index was further utilised to verify if the progression of retinitis pigmentosa diseases had occurred within three examinations at annual intervals. The obtained evaluations were consistent with the ophthalmological assessment. The proposed application will serve as an auxiliary tool for assessing the progression of RP diseases, thereby shortening the time to diagnosis.

Keywords: Retinitis pigmentosa progression, deep learning, eye diseases

LOCAL DEPLOYMENT OF OPEN-SOURCE LARGE LANGUAGE MODELS FOR ENTERPRISE AUTOMATION: PERFORMANCE, EFFICIENCY AND DATA SOVEREIGNTY ANALYSIS

Tomasz Kobus, Lublin University of Technology, s97637@pollub.edu.pl

Jakub Kopacki, Lublin University of Technology, s97640@pollub.edu.pl

Marcin Barszcz, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, m.barszcz@pollub.pl

Krzysztof Dziedzic, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, k.dziedzic@pollub.pl

Maria Skublewska-Paszkowska, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, maria.paszkowska@pollub.pl

Paweł Powroźnik, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, p.powroznik@pollub.pl

Sylwester Korga, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, s.korga@pollub.pl

Abstract: The accelerating digitisation of enterprise decision-making processes and the rapid advancement of large language models (LLMs) are opening new avenues for automating tasks that have traditionally required human involvement. Commercial cloud-based models, despite their high performance, encounter significant deployment barriers in corporate environments - most notably in the form of substantial operational costs, limited control over externally processed data, and legal risks associated with compliance with personal data protection regulations (GDPR). Local deployment of open-source language models on proprietary enterprise infrastructure represents a viable response to these constraints; however, the actual utility of such models in practical business scenarios remains poorly characterised empirically. This paper presents a structured methodology for evaluating the performance of selected open-source LLMs differing in parameter size and architecture - including gemma4:26b, gemma4:31b, qwen3.5:9b, qwen3.6:27b, qwen3.6:35b, nemotron-3-nano, glm-4.7-flash, gpt-oss:20b, and mistral-small-3.2:4b - deployed locally on dedicated consumer-grade hardware. Evaluation was conducted across five practical business scenarios: handwritten text recognition (HTR), optical character recognition of noisy documents (OCR), automated text summarisation, structured data extraction in JSON format, and a comparative assessment of Retrieval-Augmented Generation (RAG) versus long-context processing. Model quality was assessed using objective metrics encompassing Character Error Rate (CER), Word Error Rate (WER), inference time, and computational resource consumption, including VRAM usage and energy efficiency. The obtained results verify the hypothesis regarding the operational and economic viability of locally deploying optimised open-source models in medium-sized enterprises, while simultaneously revealing significant performance differences between architectures depending on scenario complexity. The proposed methodology constitutes a replicable evaluation framework applicable to LLM selection in the context of data sovereignty requirements and corporate process automation.

Keywords: large language models, local deployment, business process automation, open-source models, retrieval-augmented generation, data sovereignty, inference efficiency

CMES'26 draft version

MACHINE LEARNING CLASSIFICATION OF ION-IMPLANTED INCONEL 718

Mariusz Kamiński, Faculty of Mechanical Engineering, Lublin University of Technology, mariusz.kaminski@pollub.pl

Abstract: Ion implantation induces complex modifications in the near-surface region of metallic materials, affecting their mechanical and tribological behavior in a non-linear and depth-dependent manner. Detecting and interpreting these changes using conventional analysis methods becomes particularly difficult when implantation-induced tribological effects are subtle or partially masked by test conditions. This study presents a machine-learning-based classification approach for Inconel 718 implanted with nitrogen ions (N^+) at 80, 120, and 160 keV and fluences ranging from 1×10^{15} to 1×10^{17} ions/cm². A dedicated feature engineering pipeline was developed to integrate multi-source experimental data, including coefficient of friction (COF) time-series, COF dip-event descriptors, nanoindentation parameters (HIT, EIT, HVIT), and SRIM-derived ion-damage profiles, into a unified feature representation for each sample. Random Forest classifiers were trained for four classification tasks: implanted versus reference samples, fluence classification, implantation energy classification, and combined fluence–energy classification. Within the adopted train–test evaluation framework, all classification tasks resulted in perfect separation of the analyzed classes. Feature importance analysis indicated that nanoindentation-derived parameters, particularly HIT and HVIT, provided the strongest contribution to classification performance. Additional experiments performed using exclusively tribological features (COF and dip-event descriptors) resulted in a substantial decrease in classification accuracy (~ 0.5 – 0.6), demonstrating that friction signals alone do not sufficiently represent the structural and mechanical modifications introduced by ion implantation. The results indicate that integrating tribological, mechanical, and implantation-related descriptors significantly improves the ability of ML models to identify implantation conditions and distinguish subtle material modifications. The proposed approach demonstrates the potential of machine learning methods for analysis and classification of ion-implanted materials and provides a scalable framework for integrating heterogeneous experimental datasets in surface engineering research.

Keywords: Inconel 718; ion implantation; machine learning; tribology;

ADAPTIVE NEIGHBORHOOD SELECTION IN TOLERANT V-DETECTOR FOR ANOMALY AND INTRUSION DETECTION

Bartłomiej Chmielewski, Faculty of Computer Science, Białystok University of Technology, bartlomiej.chmielewski@pb.edu.pl

Ireneusz Mrozek, Faculty of Computer Science, Białystok University of Technology, i.mrozek@pb.edu.pl

Andrzej Chmielewski, Faculty of Computer Science, Białystok University of Technology, a.chmielewski@pb.edu.pl

Abstract: The tolerant V-Detector extends the classical V-Detector by introducing a tolerance region controlled by the neighborhood parameter k . Previous studies have shown that the choice of k has a substantial impact on detection performance, false alarm rates, and uncertainty-region size. However, existing approaches typically rely on a single manually selected global value of k for all detectors. This paper proposes an adaptive neighborhood selection mechanism that automatically determines detector-specific values of k during detector generation. The method analyzes the growth of consecutive self-neighbor distances and expands the tolerance region only while the corresponding radius increase remains significant. As a result, each detector receives an individually adjusted tolerance radius without modifying the original classification procedure. Experiments conducted on the NSL-KDD and Kyoto 2006+ intrusion detection datasets demonstrate that the proposed approach achieves performance comparable to manually tuned fixed- k configurations while reducing dependence on global parameter selection. Furthermore, the adaptive mechanism preserves the computational complexity of the original tolerant V-Detector because adaptation is performed exclusively during detector construction. The results indicate that automatic neighborhood selection provides an effective and interpretable alternative to manually specifying a global tolerance parameter in intrusion detection applications.

Keywords: artificial immune systems; negative selection algorithm; V-Detector; intrusion detection; anomaly detection; adaptive neighborhood selection.

EFFECT OF BODY MASS INDEX ON KNEE JOINT VIBROARTHROGRAPHIC SIGNAL PARAMETERS

Aleksandra Prus, Faculty of Mathematics and Information Technology, Lublin
University of Technology, a.prus@pollub.pl

Kamil Jonak, Faculty of Mathematics and Information Technology, Lublin University
of Technology, k.jonak@pollub.pl

Przemysław Krakowski, Department of Trauma Surgery and Emergency Medicine,
Medical University of Lublin, Orthopaedic and Sports Traumatology Department,
Carolina Medical Center, przemyslaw.krakowski84@gmail.com

Robert Karpiński, Faculty of Mechanical Engineering, Lublin University of
Technology, Faculty of Medicine, John Paul II Catholic University of Lublin,
r.karpinski@pollub.pl

Abstract: Vibroarthrography (VAG) is a non-invasive method based on the analysis of mechanical vibrations generated within a joint during movement and is finding increasingly widespread application in musculoskeletal diagnostics. A significant challenge in VAG signal analysis is the variability of recorded signals between subjects, which may be influenced by biomechanical and biological factors. Increased Body Mass Index (BMI) is associated with greater mechanical loading of the knee joint, which may alter soft-tissue properties and, consequently, affect vibration transmission and the acoustic characteristics of vibroarthrographic signals. Therefore, BMI may influence signal propagation and the damping of tissue vibrations during knee joint movement. This study aims to analyse the effect of BMI on selected vibroarthrographic signal parameters recorded during knee joint movement. The study was conducted on a group of adults aged 18-26, divided into BMI-related groups. The participants reported no knee pain or dysfunction and had not undergone any prior knee surgery. The signals were recorded using a multi-sensor measurement system during movements performed in the open-kinetic chain (OKC) and closed-kinetic chain (CKC). The acquired data were subjected to preprocessing procedures, including artefact reduction and signal filtering, followed by selected signal parameter extraction and statistical analysis. The presented study may contribute to a better understanding of the influence of biomechanical and biological factors on vibroarthrographic measurements and support further work on the standardisation and interpretation of VAG-based diagnostic methods in clinical practice.

Keywords: vibroarthrography, VAG, biomedical signal processing, body mass index, knee joint, signal analysis, biomechanics

RESTING-STATE EEG ACTIVITY AND ITS ASSOCIATIONS WITH SELECTED DIMENSIONS OF PSYCHOLOGICAL FUNCTIONING

Katarzyna Mróz, Faculty of Mathematics and Information Technology, Lublin
University of Technology, k.mroz@pollub.pl

Abstract: Psychological disorders and anxiety-related conditions are commonly assessed using self-report questionnaires and clinical observations; however, these approaches often lack objective neurophysiological markers that could support the identification of anxiety-related processes. Electroencephalography (EEG), particularly resting-state EEG, has emerged as a valuable non-invasive method for investigating neural activity associated with emotional and cognitive functioning. Due to its high temporal resolution, resting-state EEG enables the assessment of spontaneous brain activity under both eyes-open and eyes-closed conditions, providing insight into neural mechanisms potentially related to anxiety and psychological functioning. In the present study, resting-state EEG activity was examined in relation to selected dimensions of psychological functioning and anxiety-related characteristics. EEG recordings were obtained during both eyes-closed and eyes-open resting-state conditions. To complement the neurophysiological measurements, participants completed standardized psychological questionnaires, including the NASA Task Load Index (NASA-TLX), EAS-D, State-Trait Anxiety Inventory (STAI), and Beck Depression Inventory (BDI-II). EEG signals were preprocessed in MATLAB using signal processing procedures, including band-pass filtering and artifact reduction to minimize noise related to eye movements and muscle activity. Spectral analysis was subsequently performed to extract quantitative EEG features, including power estimates within conventional frequency bands (delta, theta, alpha, and beta). Participants were categorized according to anxiety severity levels based on questionnaire scores, enabling comparative analyses between individuals presenting elevated anxiety symptoms and healthy controls. Statistical analyses were conducted to identify associations between EEG-derived features and psychological measures related to anxiety, depressive symptoms, emotional functioning, and perceived cognitive workload. The proposed computational workflow enabled systematic processing of multidimensional neurophysiological and psychometric data and may contribute to the identification of EEG-based markers of anxiety. Furthermore, the presented approach demonstrates the applicability of EEG signal processing and biomedical data analysis methods in the development of computer-aided systems supporting the objective assessment of anxiety-related conditions.

Keywords: electroencephalography, anxiety disorder, resting-state EEG, brain activity, EEG biomarkers, neurophysiological markers

THCS-ViT: A HYBRID LIGHTWEIGHT VISION TRANSFORMER WITH MULTI-SCALE FEATURE FUSION FOR THERMAL FACIAL EMOTION RECOGNITION

Katarzyna Baran, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, k.baran@pollub.pl

Kamil Pietrak, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, k.pietrak@pollub.pl

Abstract: Thermal facial images pose serious challenges for classical convolutional networks and standard transformer architectures due to their low contrast, significant sensor noise, and lack of rich textural details. In this paper, we propose THCS-ViT (Thermal Hybrid Cross-Scale Vision Transformer), a hybrid architecture integrating a lightweight convolutional stem inspired by MobileNetV3, a Cross-Scale Attention Fusion (CSAF) module, and a modified MobileViT-S backbone. The model was trained on the KTFE_{v2} (Korean Thermal Facial Emotion Dataset v2) dataset and evaluated through cross-dataset experiments on the Rainbow subset of the Comprehensive Facial Thermal Dataset (CFTD). The proposed architecture achieved a mean accuracy of $93.8\% \pm 0.6\%$ (5-fold cross-validation) on KTFE_{v2} and 84.36% on CFTD Rainbow, with only 1.85 million parameters and 0.68 GFLOPs. These results outperform selected baseline models in terms of both accuracy and computational efficiency. Ablation studies, statistical tests, and explainability analyses confirm the contribution of individual components. The low parameter count suggests potential for edge deployment, though hardware validation remains future work. The proposed architecture offers a promising balance between accuracy and computational efficiency, with the CSAF module and thermal bias providing complementary benefits for thermal emotion recognition.

Keywords: hybrid CNN-ViT, lightweight Vision Transformer, thermal images, multi-scale feature fusion, cross-dataset generalization, computational efficiency, explainability, edge computing.

A FINE-TUNED MULTI-AGENT LARGE LANGUAGE MODEL PLATFORM WITH RETRIEVAL-AUGMENTED GENERATION FOR CLINICAL CASE REPORT ANALYSIS

Mateusz Walo, Faculty of Mathematics and Information Technology, Lublin University of Technology, s103011@pollub.edu.pl

Dariusz Majerek, Faculty of Mathematics and Information Technology, Lublin University of Technology, d.majerek@pollub.pl

Abstract: The growing volume of digitised medical case reports, and the need for tools that support their structured analysis, motivated the prototype platform presented in this work. A single general-purpose language model lacks the domain precision and up-to-date references required for reliable case-report analysis; we address this by combining domain fine-tuning with a retrieval-augmented generation (RAG) component that queries a vector database of clinical literature on demand. The platform comprises five specialised agents (general practitioner, surgeon, cardiologist, neurologist and psychologist) and a synthesis agent that consolidates their individual assessments, with each agent reasoning within its specialty and grounded in retrieved medical sources. The shared base model, DeepSeek-R1-Distill-Qwen-7B, was fine-tuned using 4-bit QLoRA on 8,999 chain-of-thought-enriched PubMed case reports (from a curated corpus of 9,999), training 40.4M parameters (0.93% of the model) over three epochs on an A100 GPU. Retrieval draws on 7,679 text chunks extracted from 13 clinical textbooks and guidelines (2,164 pages). On a 501-case held-out test set, the fine-tuned model outperformed the base model across all metrics, reaching ROUGE-1 0.58, BERTScore 0.68, ChrF++ 0.50, faithfulness 0.44 and structural completeness 0.65. These results demonstrate that parameter-efficient domain fine-tuning significantly improves the shared backbone driving all platform agents; end-to-end quantitative evaluation of the retrieval and multi-agent orchestration layers is the subject of ongoing work.

Keywords: large language models, multi-agent systems, retrieval-augmented generation, clinical decision support, parameter-efficient fine-tuning (QLoRA), medical case reports

APPLICATION OF AUTOMATED IMAGE ANALYSIS IN THE BIOINDICATIVE ASSESSMENT OF ACTIVATED SLUDGE PARAMETERS AND THE IMPACT OF TREATMENT PLANTS ON RECEIVING WATERS

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University of Technology, g.lagod@pollub.pl

Dariusz Majerek, Faculty of Mathematics and Information Technology, Lublin University of Technology, d.majerek@pollub.pl

Michał Staniszewski, Faculty of Environmental Engineering and Energy, Lublin University of Technology, m.staniszewski@pollub.pl

Edyta Wojtaś, Faculty of Environmental Engineering and Energy, Lublin University of Technology, e.wojtas@pollub.pl

Aleksandra Kozłowska, Doctoral School, Lublin University of Technology, aleksandra.kozlowska1@pollub.edu.pl

Konrad Jamka, Doctoral School, Lublin University of Technology, d634@pollub.edu.pl

Abstract: The use of a bioindicative analysis method based on community structure indices allows for a quick and cost-effective assessment of activated sludge condition at various stages of biological wastewater treatment, due to the lack of expensive equipment and low environmental impact (no chemical reagents required). It is also useful in assessing the impact of wastewater treatment plants on receiving surface waters. Community structure indices do not require precise identification of organism species; a rapid counting of individuals identified in live specimens within appropriately selected ecological groups is sufficient. These groups differ in their morphological characteristics (visually) and can be observed with a standard transmitted light optical microscope, without the need for preliminary preparation and staining of the specimens. During the analysis of microscopic images, which can be supported by automated image analysis methods using artificial intelligence (e.g., deep learning neural networks), organisms are counted and classified based on visual features that influence their role in the activated sludge ecosystem. This classification significantly simplifies obtaining results for bioindicative assessment, while the use of supporting artificial intelligence models reduces the required time from several hours to a few minutes. Using the software for automated analysis of microscopic images of activated sludge in larger treatment plants can significantly reduce the financial costs of monitoring the stability of biological processes. In smaller treatment plants, which typically lack access to specialized analytical equipment and activated sludge analysis specialists, such software may be the only tool available for monitoring the biological process factor during ongoing operation.

Keywords: automated image analysis, bioindicative assessment, activated sludge parameters, treatment plants, receiving waters

MULTIMODAL AI AND EDGE INTELLIGENCE FOR CONTEXT-AWARE CUSTOMER RELATIONSHIP MANAGEMENT

Michał Maj, Institute of Computer Science and Innovative Technologies, WSEI
University, Netrix Link sp. z o.o., michal.maj@netrix.com.pl

Tomasz Cieplak, Faculty of Management, Lublin University of Technology, Netrix
Link sp. z o.o., t.cieplak@pollub.pl

Damian Pliszczyk, Netrix Link sp. z o.o., damian.pliszczyk@netrix.com.pl

Jakub Pizoń, Faculty of Management, Lublin University of Technology, Netrix Link sp.
z o.o., j.pizon@pollub.pl

Abstract: Contemporary customer relationship management platforms often aggregate heterogeneous operational records without converting them into context-aware, real-time decisions. This paper presents a modular architecture for an artificial-intelligence-enabled CRM system that integrates structured customer and enterprise data with multimodal interaction streams from online channels, virtual assistants, mobile applications, and an IoT concierge terminal. The proposed solution comprises five cooperating layers covering data acquisition, edge concierge processing, integration, analytics, and decision support. At the edge, camera, microphone, and touch events are processed for face localisation and alignment, user identification, and emotion estimation, thereby limiting transmission of raw sensory data and reducing latency. The analytical layer combines CRM and ERP records with text, speech, and visual cues to support intent recognition, customer segmentation, anomaly detection, forecasting, natural-language queries, and recommendation generation. Normalised events are translated into actionable CRM outputs, including personalised offers, follow-up tasks, service alerts, and managerial reports. The prototype demonstrates a deployment approach spanning cloud, on-premises, and embedded components, with perception models trained externally and optimised for execution on accelerators or smart cameras. The architecture addresses interoperability, data protection, network reliability, hosting costs, and human oversight by separating raw perception from business-level decisions. The resulting framework extends CRM from passive data storage to context-aware decision support while retaining human responsibility in complex customer-service scenarios. Future work concerns tighter CRM/ERP integration and further optimisation of the edge inference pipeline.

Keywords: artificial intelligence, customer relationship management, multimodal analysis, edge computing, Internet of Things, virtual assistants, decision support, customer service

CROSS-SIGNER GENERALIZATION OF VISION- LANGUAGE EMBEDDINGS FOR POLISH FINGERSPELLING RECOGNITION

Łukasz Maciura, Netrix Link sp. z o.o., Lublin, lukasz.maciura@netrix.com.pl

Michał Maj, Institute of Computer Science and Innovative Technologies, WSEI
University, Netrix Link sp. z o.o., michal.maj@netrix.com.pl

Tomasz Cieplak, Faculty of Management, Lublin University of Technology, Netrix
Link sp. z o.o., t.cieplak@pollub.pl

Jakub Pizoń, Faculty of Management, Lublin University of Technology, Netrix Link sp.
z o.o., j.pizon@pollub.pl

Abstract: Automatic recognition of fingerspelling sequences is an important component of assistive systems supporting communication with Deaf and hard-of-hearing users. This study evaluates whether sequence-level embeddings generated by the LLaVA-OneVision vision-language model with a Qwen backbone provide discriminative features for Polish Sign Language (PJM) fingerspelling recognition. A publicly available dataset containing 1,659 valid video sequences, 20 gesture classes, and recordings from nine signers was used. Each video was uniformly reduced to at most 30 frames and encoded into a 7,168-dimensional representation. Three embedding variants were compared: mean-pooled hidden states, the last-token representation, and their concatenation. The embeddings were classified using several conventional machine-learning algorithms. A preliminary multimodal variant additionally incorporated textual descriptions derived from detected hand landmarks, but this information did not improve recognition and was omitted from the final pipeline. In standard cross-validation, the Extra Trees classifier achieved the best accuracy, approaching 98%; Decision Tree also performed strongly, whereas Gaussian Naive Bayes and the remaining evaluated methods were less effective. The concatenated embedding provided the most useful feature representation, indicating complementary value from global token-level context and the final hidden-state token. However, signer-independent GroupKFold evaluation with disjoint signer groups produced substantially lower scores, revealing limited generalization across individuals. The results demonstrate the usefulness of vision-language embeddings for PJM fingerspelling recognition while showing that high conventional cross-validation accuracy does not guarantee robustness to unseen signers. Larger and more diverse datasets, improved normalization, and dedicated temporal models are therefore required for reliable deployment.

Keywords: Polish Sign Language, fingerspelling recognition, vision-language model, video embeddings, Extra Trees, signer-independent evaluation

EXPLAINABLE LOCAL EVALUATION OF FACTUAL CONSISTENCY IN AUTOMATED CLINICAL SUMMARIES AGAINST SOAP REFERENCES

Michał Maj, Institute of Computer Science and Innovative Technologies, WSEI
University, Netrix Link sp. z o.o., michal.maj@netrix.com.pl

Tomasz Cieplak, Faculty of Management, Lublin University of Technology, Netrix
Link sp. z o.o., t.cieplak@pollub.pl

Damian Pliszczyk, Netrix Link sp. z o.o., damian.pliszczyk@netrix.com.pl

Jakub Pizoń, Faculty of Management, Lublin University of Technology, Netrix Link sp.
z o.o., j.pizon@pollub.pl

Abstract: Reliable automatic generation of clinical documentation requires more than linguistic fluency because summaries must preserve clinically relevant facts while avoiding unsupported additions. This study presents an interpretable, locally deployable natural language processing pipeline for fact-level evaluation of automatically generated summaries of doctor-patient conversations against references structured according to SOAP. The dataset comprised 500 matched transcript-summary-reference records. Reference elements were available for 500 Subjective, 404 Objective, 316 Assessment, and 496 Plan sections. The hybrid rule-based and factual pipeline validated and normalized inputs, extracted clinical and organizational facts, including symptoms, diagnoses, diagnostic tests, procedures, recommendations, medications, hospitalization, and urgency, and mapped them to SOAP elements while retaining negation, certainty, and temporal context. Summary quality was quantified using element-level accuracy, precision, recall, and F1 score. Stricter case-level accuracy and robustness to 5% token noise were reported as supplementary measures. The method achieved element-level accuracy of 0.9448, precision of 0.9443, recall of 1.0000, and an F1 score of 0.9691. Case-level accuracy was 0.7360, reflecting the more demanding requirement that an entire record be correct. The capped noise-retention score was 1.0000, indicating preserved quality under the applied perturbation. These findings show that automated clinical summaries can be evaluated locally and transparently at the level of clinically meaningful information units. The proposed framework distinguishes omissions from unsupported content and provides an auditable basis for quality assurance. Further validation should incorporate expert review, improved negation handling, synonym mapping, and terminology normalization.

Keywords: clinical summarization, factual consistency, SOAP notes, natural language processing, explainable evaluation, medical documentation

FUZZY LOGIC CONTROLLER FOR AUTONOMOUS OBSTACLE AVOIDANCE IN A QUADROTOR UNMANNED AERIAL VEHICLE

Grzegorz Jabłoński, Unmanned Aerial Vehicle Training Centre, Deblin, Polish Air Force University, Poland g.jablonski@law.mil.pl

Mariusz Michalski, Faculty of Aviation, Polish Air Force University, Deblin, Poland, m.michalski@law.mil.pl

Norbert Grzesik, Faculty of Aviation, Polish Air Force University, Deblin, Poland, n.grzesik@law.mil.pl

Marcin Markiewicz, Faculty of Aviation Safety, Polish Air Force University, Deblin, Poland, m.markiewicz@law.mil.pl

Abstract: Unmanned aerial vehicles (UAVs), particularly small quadrotor platforms, are increasingly considered for applications in urban environments, including infrastructure inspection, environmental monitoring, and surveillance. One of the main challenges associated with their autonomous operation is the ability to avoid obstacles while maintaining safe and efficient flight. The aim of this study was to develop and evaluate a fuzzy logic-based obstacle avoidance controller for a quadrotor micro aerial vehicle (MAV). The controller was designed using MATLAB and evaluated through computational tests and flight simulation in the Simulink environment. The proposed fuzzy inference system uses three input variables describing the height, width, and depth of an obstacle, and four output variables corresponding to the control signals for the quadrotor motors. Each input variable was described by five fuzzy sets, which formed the basis for the development of fuzzy inference rules. Several defuzzification methods were investigated, including the centroid, bisector, and maximum-based methods. Based on the analysis of the obtained control responses, the centroid method was selected for further evaluation. The developed controller was tested using different obstacle dimensions and subsequently assessed in a 20-second simulated flight scenario involving four obstacles representative of an urban environment. The simulation results demonstrated that the controller generated appropriate motor control responses to the encountered obstacles, enabling the execution of avoidance manoeuvres in the considered scenario. The study indicates the potential of fuzzy logic-based control systems for supporting autonomous obstacle avoidance in small UAVs. Further experimental validation on a physical quadrotor platform is required to assess the performance of the proposed solution under real flight conditions.

Keywords: unmanned aerial vehicle, fuzzy logic controller, autonomous obstacle avoidance, quadrotor, MATLAB/Simulink

COMPUTATIONAL FLUID DYNAMICS (CFD)

NUMERICAL CFD ANALYSIS OF CATALYTIC BASKETS IN DUAL-BED CATALYTIC REACTORS

Paweł Capała, Industrial Technologies and Decarbonization Department, Łukasiewicz Research Network — New Chemical Syntheses Institute,
pawel.capala@ins.lukasiewicz.gov.pl

Monika Ruszak, Industrial Technologies and Decarbonization Department, Łukasiewicz Research Network — New Chemical Syntheses Institute,
monika.ruszak@ins.lukasiewicz.gov.pl

Zbigniew Czyż, Faculty of Aviation, Polish Air Force University, z.czyz@law.mil.pl

Anna Rudawska, Faculty of Mechanical Engineering, Lublin University of Technology, a.rudawska@pollub.pl

Abstract: Catalytic baskets used to support catalyst beds can have various designs that direct gas flow in different directions through a catalytic reactor. In industrial practice, axial- and radial-flow reactors are most commonly used. In this study, the influence of tail gas distribution in a dual-bed catalytic reactor on the distribution of linear gas velocity and pressure drop across the catalyst beds was analysed using CFD simulations with ANSYS FLUENT. The results of experimental studies and literature data indicate a significant effect of linear gas velocity in the catalyst bed on its performance efficiency. CFD numerical calculations were carried out for a model SCR-deNO_x/LT-deN₂O reactor used in the pilot nitric acid plant at Łukasiewicz – INS, for different catalytic basket designs. For each basket design, identical boundary conditions and operating parameters of the SCR reactor were assumed. The calculation results demonstrated a significant influence of the catalytic basket design on the distribution of linear gas velocity and gas pressure drops in a dual-bed catalytic system. The most favourable solution proved to be a coaxial arrangement of the catalyst beds in the reactor, without separating them by a space. The lowest values of linear gas velocity and flow resistance through the system of two catalyst beds were obtained for the axial-radial catalytic basket design, which ensures contact between the two catalyst beds through a porous partition.

Keywords: CFD, catalytic baskets, dual-bed catalytic reactors

A 1D-3D COUPLED NUMERICAL APPROACH TO INVESTIGATE WATER HAMMER IN A RESERVOIR PIPE VALVE SYSTEM USING REALISTIC VALVE CLOSURE MECHANISM

Armin Alavi, Faculty of Mechanical Engineering and Mechatronics, West Pomeranian University of Technology in Szczecin, as61302@zut.edu.pl

Kamil Urbanowicz, Faculty of Mechanical Engineering and Mechatronics, West Pomeranian University of Technology in Szczecin, Kamil.Urbanowicz@zut.edu.pl

Abstract: A transient flow phenomenon called water hammer, induced by sudden events such as valve opening or closure, pump start-up or shutdown, and load rejection in hydropower systems, is analyzed in this work. This event is investigated with the help of numerical methods of different spatial fidelity such as the one-dimensional Method of Characteristics (MoC) and three-dimensional Computational Fluid Dynamics (CFD) based on the Finite Volume Method (FVM). Full 3D CFD simulation of large hydraulic systems containing long pipelines and multiple hydraulic devices is computationally demanding and often impractical, so to overcome this limitation, 1D–3D coupled approaches have been proposed, in which the pipelines are modeled one-dimensionally while regions with complex geometry are resolved in full 3D. This hybrid strategy offers a practical compromise between computational efficiency and physical accuracy. In the present study, a coupled 1D–3D solver is developed within the open-source OpenFOAM framework. The 1D MoC model, incorporating a convolution-based unsteady friction formulation, is coupled to a 3D CFD model of a classical reservoir–pipe–valve (RPV) system, and a sliding mesh approach is employed in the 3D region to represent realistic valve closure. The coupling is two-way and explicit, with pressure and velocity exchanged between the 1D and 3D domains at every time step. The interface treatment is based on the characteristic equation and the Riemann invariant equation. The sensitivity of the coupled solution to interface location, 3D mesh resolution, and time-step size is investigated, in addition to the effect of valve geometry on transient behavior for ball and butterfly valves. The pressure attenuation at the valve section is compared with full 1D, full 3D, and experimental results for laminar and turbulent flow regimes in order to verify the coupling method.

Keywords: method of Characteristics, Computational Fluid Dynamics, Water Hammer, Unsteady Friction, Dynamic Mesh

CFD-BASED ANALYSIS OF LIFT AND DRAG CHARACTERISTICS OF A UAV SEAPLANE IN TRANSITIONAL FLOW REGIMES

Robert Babel, Faculty of Aviation, Polish Air Force University, r.babel@law.mil.pl

Abstract: This study presents a computational investigation of the aerodynamic performance of a small-scale unmanned aerial vehicle (UAV) configured as a seaplane operating in transitional flow regimes. The analysis focuses on the prediction of lift and drag characteristics at low Reynolds numbers representative of typical UAV flight conditions. A three-dimensional model of the seaplane, including wing, fuselage, and float assemblies, was developed and analyzed using Reynolds-Averaged Navier–Stokes (RANS) equations coupled with a transition-sensitive turbulence model. Numerical simulations were conducted over a range of angles of attack and freestream velocities to capture the onset and development of laminar–turbulent transition. Special attention was given to the aerodynamic interaction between the wing and floats, which significantly influences flow separation and drag penalties. Grid independence studies and validation against available experimental or empirical data were performed to ensure numerical accuracy. The results indicate that transitional effects play a critical role in determining aerodynamic efficiency, particularly in the pre-stall region. The presence of floats increases parasitic drag while also modifying the lift curve slope due to interference effects. The findings provide insight into the optimization of UAV seaplane configurations and highlight the importance of incorporating transition modeling in low Reynolds number aerodynamic analyses.

Keywords: CFD, UAV

DESIGN AND EXPERIMENTAL VALIDATION OF A PROPELLER FOR AN UNMANNED AERIAL VEHICLE WITH MTOW UP TO 25 KG

Izabela Żaczek, Polish Air Force University, i.zaczek7392@wsosp.edu.pl

Bernadetta Kowalczyk, Polish Air Force University, b.kowalczyk7295@wsosp.edu.pl

Abstract: This paper presents the design, manufacturing, and experimental validation of a propeller intended for an unmanned aerial vehicle (UAV) with a maximum take-off weight (MTOW) of up to 25 kg. The primary objective of the study was to develop a propeller geometry capable of delivering the required thrust characteristics at maximum rotational speed and to evaluate the agreement between computational predictions and experimental measurements. The design process was based on a proprietary computational algorithm, which enabled the determination of key geometric parameters of the propeller using propulsion system characteristics and predefined operating conditions. A two-bladed propeller with a diameter of 25 inches and fixed pitch was designed. Based on the obtained parameters, a detailed geometric model was developed, followed by the fabrication of a composite prototype. Experimental investigations were conducted using a dedicated test stand, where static thrust, torque, and selected operational parameters were measured. The obtained results enabled the assessment of the consistency between numerical predictions and experimental data, as well as the evaluation of the accuracy of the proposed design methodology. The developed approach, supported by experimental validation, contributes to the advancement of computational tools for rapid propeller selection and design in light UAV applications.

Keywords: CFD, UAV

MODELING AND ANALYSIS OF WING ICING ON A BOEING 737-800 AIRCRAFT USING ANSYS

Anna Olszewicz, Polish Air Force University, a.olszewicz7336@wsosp.edu.pl

Jakub Kordowski, Polish Air Force University, j.kordowski7292@wsosp.edu.pl

Abstract: This paper presents a numerical analysis of the icing process on the wing of a Boeing 737-800 aircraft and its impact on aerodynamic characteristics. A geometric model of a wing section was developed using a quasi-3D (2.5D) approach, followed by simulations of airflow and ice accretion using Computational Fluid Dynamics (CFD) methods in the ANSYS environment, including the FENSAP-ICE module. The analyses were performed under conditions corresponding to real cruise flight, with a freestream velocity of 216 m/s and an ambient temperature of -20°C . Two icing durations were considered: 300 s and 3000 s. In the case of short ice accretion time, the impact on aerodynamic performance was relatively minor, despite the presence of a noticeable ice mass. However, for the longer duration (3000 s), a significant ice layer accumulation (approximately 161 kg) was observed, leading to changes in airfoil geometry, increased surface roughness, and flow disturbances. The results demonstrated a substantial increase in drag coefficient and a reduction in lift generation efficiency. Icing was found to promote earlier flow separation, deterioration of aerodynamic efficiency, and a reduction in the safe operational envelope of the wing. The conducted study confirms the significant influence of icing on flight safety and aircraft performance characteristics.

Keywords: aircraft icing, ice accretion, aerodynamic performance, CFD simulation; ANSYS, FENSAP-ICE

CFD INVESTIGATION OF THERMAL MIXING ENHANCEMENT OF SHEAR-THINNING FLUIDS IN SHORT PASSIVE TLCCM MICROMIXERS

Amar Kouadri, Renewable Energy Systems Applications Laboratory, LASER,
University of Djelfa, Algeria, amar.kouadri@univ-djelfa.dz

Embarek Douroum, Renewable Energy Systems Applications Laboratory, LASER,
University of Djelfa, Algeria, embarek.douroum@univ-djelfa.dz

Mokhtar Zaitri, Renewable Energy Systems Applications Laboratory, LASER,
University of Djelfa, Algeria, zaitrimoh14@gmail.com

Sofiane Khelladi, Arts et Metiers Institute of Technology, CNAM, LIFSE, HESAM
University, Paris, France, sofiane.khelladi@ensam.eu

Samir Laouedj, Laboratory of materials and reactive systems, LMSR, Djillali Liabes
University, Algeria, s.laouedj@gmail.com

Juan Pedro Solano, Ing. Térmica y de Fluidos, Universidad Politécnica de Cartagena,
Spain, juanp.solano@upct.es

Abstract: Thermal mixing in chaotic microdevices holds significant promise across a wide range of applications, particularly in thermal engineering. Among microfluidic systems, the Two-Layer Crossing Channels Micromixer (TLCCM) has demonstrated notable effectiveness in thermal mixing of Newtonian fluids, which motivated the present study to examine its behavior with pseudoplastic fluids. A numerical comparative analysis was conducted to evaluate the thermal mixing performance of shear-thinning fluid flows across three TLCCM configurations: TLCCM-X, TLCCM-KX, and TLCCM-O. The governing equations, including Navier-Stokes, mass conservation, energy, and species transport, were solved numerically using a CFD code. The pseudoplastic fluids considered are carboxymethyl cellulose (CMC) solutions, modeled using the power-law approach, with flow behavior indices spanning from 0.49 to 1 and generalized Reynolds numbers ranging from 0.2 to 70. The setup involves injecting a hot fluid at 330 K and a cold fluid at 300 K through two distinct inlets of each micromixer. The study aims to provide both quantitative and qualitative insight into the combined influence of fluid rheology and Reynolds number on thermal mixing performance. A comparative assessment is also presented to identify which configuration achieves the highest mixing efficiency, with the probability density function (PDF%) evaluated at the outlet serving as the key indicator of thermal homogenization quality.

Keywords: CFD, TLCCM micromixer, pseudoplastic fluids, thermal mixing degree, probability density function.

COMPARATIVE ANALYSIS OF PASSIVE PLANAR MICROMIXERS FOR NEWTONIAN AND NON- NEWTONIAN FLUID MIXING: A NUMERICAL STUDY

Embarek Douroum, Renewable Energy Systems Applications Laboratory, LASER,
University of Djelfa, Algeria, embarek.douroum@univ-djelfa.dz

Amar Kouadri, Renewable Energy Systems Applications Laboratory, LASER,
University of Djelfa, Algeria, amar.kouadri@univ-djelfa.dz

Sofiane Khelladi, Arts et Metiers Institute of Technology, CNAM, LIFSE, HESAM
University, Paris, France, sofiane.khelladi@ensam.eu

Samir Llaouedj, Laboratory of materials and reactive systems, LMSR, Djillali Liabes
University, Algeria, s.laouedj@gmail.com

Abdelylah Benazza, University of Sidi Bel Abbes, abdel_benazza@yahoo.fr

Mokhtar Zaitri, Renewable Energy Systems Applications Laboratory, LASER,
University of Djelfa, Algeria, zaitrimoh14@gmail.com

Juan Pedro Solano, Ing. Térmica y de Fluidos, Universidad Politécnica de Cartagena,
Spain, juanp.solano@upct.es

Abstract: This study presents a numerical investigation of mixing performance in passive planar micromixers, with a focus on the flow behavior of both Newtonian and non-Newtonian fluids. The primary aim is to assess how channel geometry and flow conditions influence mixing efficiency through computational modeling using ANSYS Fluent 16.0. Three geometrically distinct passive micromixers: M1, M2, and M3 were designed and systematically evaluated based on key performance metrics, including mixing degree, pressure drop, mixing energy cost, residence time, and thermal mixing degree. The findings revealed that the M2 and M3 configurations surpassed the M1 design in mixing quality, particularly at elevated Reynolds numbers. While the M3 micromixer yielded the highest mixing degree, it incurred substantially greater pressure drops and energy consumption. In contrast, the M2 micromixer offered a favorable trade-off among mixing performance, energy efficiency, and residence time. A dedicated analysis of non-Newtonian fluid mixing was further conducted using the M2 micromixer, demonstrating its notable hydrodynamic efficiency. Two power-law indices were considered: $n = 0.49$ and $n = 0.75$. Results indicated that the fluid with near-Newtonian behavior ($n = 0.75$) reached a high mixing degree more rapidly, whereas the highly viscous fluid ($n = 0.49$) exhibited consistently poor mixing even at increased flow velocities. These findings underscore the critical role of geometric design and fluid rheology in optimizing mixing performance within microfluidic systems.

Keywords: CFD, Mixing degree, Mixing energy cost, Residence time, Pressure loss, Chaotic advection, Non-Newtonian fluid.

CFD MODELING OF WATER AEROSOL FLOW IN AN ICING WIND TUNNEL

Aleksandra Zarubajko, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, aleksandra.zarubajko@wat.edu.pl

Lukasz Omen, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, lukasz.omen@wat.edu.pl

Maciej Majcher, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, maciej.majcher@wat.edu.pl

Andrzej J. Panas, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, andrzej.panas@wat.edu.pl

Abstract: The present study concerns the numerical modeling of water aerosol flow in a subsonic wind tunnel adapted for icing studies. The work focuses on the numerical representation of aerosol flow generated by injector system, with particular attention paid to modeling assumptions, injection parameters, and behavior of the dispersed phase within the wind tunnel test section. The aim of the study is to develop a numerical model for determining aerosol flow parameters. In combination with experimental results, the theoretically determined characteristics may be used to assess the fidelity of reproducing atmospheric conditions conducive to icing in both model-scale experiments and CFD simulations. In the numerical model, gas phase was represented by air, while the dispersed phase consisted of water droplets introduced into the flow by means of injector system. The motion of the liquid-phase particles was described using the Discrete Phase Model, commonly applied in droplet transport analyses. The droplet diameter distribution was modeled using the Rosin–Rammler distribution. The model included wind tunnel geometry as well as the arrangement and shape of the injectors. The numerical analysis covered droplet motion in the air stream, influence of droplet diameter distribution on the dispersed-phase structure, and the formation of the aerosol field in the measurement region. The spatial distribution of the liquid phase was also evaluated, since aerosol-field non-uniformity affects the quality of icing-condition reproduction. The CFD modeling results made it possible to assess the suitability of Ansys Fluent for analyzing two-phase flow structures in a wind tunnel. The analysis indicates that the DPM model can support the assessment and calibration of water-injection systems used in icing wind tunnels. The results also confirm that injection parameters, droplet size distribution, and boundary conditions significantly influence the predicted granulometric parameters, such as MVD (Mean Volume Diameter), LWC (Liquid Water Content), and the spatial distribution of the aerosol.

Keywords: Computational Fluid Dynamics (CFD), Ansys Fluent, multiphase flow, water aerosol flow, Discrete Phase Model (DPM), Rosin–Rammler distribution, droplet size distribution, icing wind tunnel

ANALYSIS OF THE INFLUENCE OF THE GROUND EFFECT ON THE BASIC AERODYNAMIC CHARACTERISTICS OF A WIG CRAFT WING

Aneta Misiak-Zawadzka, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, aneta.misiak@wat.edu.pl

Maciej Majcher, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, maciej.majcher@wat.edu.pl

Abstract: This paper presents and discusses the results of numerical analyses of flow around a WIG craft airfoil (screen plane). Flow simulations were performed using RANS equations in the ANSYS Fluent environment for a fixed range of angles of attack and relative flight altitudes above the ground, expressed as the dimensionless ratio h/c , where c is the mean aerodynamic chord and h is the clearance between the airfoil and the ground surface. Numerical analyses included grid independence tests, which included the aerodynamic coefficients of lift CL , drag CD , pitching moment Cm , and the aerodynamic ratio L/D . The results showed that the influence of the near-surface effect on the aerodynamic characteristics of WIG craft airfoils is ambiguous and strongly dependent on angle of attack and relative flight altitude, contradicting common generalizations found in the literature regarding lift increase and drag decrease. The obtained results are presented in tables and in the form of characteristics of aerodynamic force coefficients and moments as a function of angle of attack. The research and its results presented in this article were carried out and accomplished as part of the implementation of the University Research Grant UGB 531-000040-W200-22 entitled "Optimization of aerodynamic aircraft systems using the near-surface effect," conducted at the Military University of Technology

Keywords: ground effect, ekranoplan, WIG craft, CFD, aerodynamic characteristics

NUMERICAL INVESTIGATION OF THE AERODYNAMIC CHARACTERISTICS OF THE LUBLIN R-XIIID AIRCRAFT

Rafał Kliza, Faculty of Production Engineering, University of Life Sciences in Lublin, Poland, rafal.kliza@up.edu.pl

Zbigniew Czyż, Faculty of Aviation, Polish Air Force University, z.czyz@law.mil.pl

Konrad Pietrykowski, Faculty of Mechanical Engineering, Lublin University of Technology, k.pietrykowski@pollub.pl

Paweł Magryta, Faculty of Mechanical Engineering, Lublin University of Technology, p.magryta@pollub.pl

Abstract: The reconstruction of historical aircraft requires not only an accurate reproduction of their geometry and structural configuration, but also a reliable assessment of their aerodynamic behaviour. In the case of the Lublin R-XIIID aircraft, the limited availability of complete aerodynamic documentation makes numerical modelling an important tool for recovering information on its original flight characteristics and for supporting subsequent experimental investigations. The aim of the present study was to determine the basic aerodynamic characteristics of the reconstructed Lublin R-XIIID aircraft using Computational Fluid Dynamics (CFD). A detailed three-dimensional CAD model of the aircraft was developed on the basis of available geometric and archival data and subsequently adapted for numerical analysis. Particular attention was paid to preserving the main aerodynamic features of the original configuration while ensuring appropriate computational quality of the model. The numerical simulations were carried out using ANSYS Fluent. A computational domain was developed and several meshes with different levels of refinement were generated. Prior to the final calculations, a grid-independence study was performed to assess the sensitivity of the aerodynamic results to spatial discretisation and to select a mesh providing an appropriate compromise between numerical accuracy and computational cost. The CFD analysis enabled the determination of the principal aerodynamic coefficients, including the lift coefficient, drag coefficient and pitching moment coefficient, as well as their variation with the selected flow conditions. The pressure and velocity fields around the aircraft were also analysed in order to identify characteristic flow structures and regions significantly affecting the aerodynamic behaviour of the configuration. The obtained results constitute an important stage in the reconstruction and aerodynamic assessment of the Lublin R-XIIID aircraft. The numerical model provides a basis for further comparison with wind-tunnel measurements and for the validation of the reconstructed aerodynamic characteristics. Such an approach contributes to preserving not only the geometric form of a historically significant aircraft, but also knowledge of its aerodynamic properties and operational behaviour.

Keywords: Lublin R-XIIID, computational fluid dynamics, CFD, ANSYS Fluent, aerodynamic characteristics, mesh independence, historical aircraft reconstruction

COMPUTER SIMULATIONS OF PROCESSES AND PHENOMENA

MACHINE LEARNING-BASED PREDICTION OF AERODYNAMIC CHARACTERISTICS OF AN ELECTRIC UAV PROPULSION SYSTEM

Lukasz Grabowski, Faculty of Mechanical Engineering, Lublin University of Technology, l.grabowski@pollub.pl

Jan Pytka, Faculty of Mechanical Engineering, Lublin University of Technology, jan.pytka@pollub.edu.pl

Zbigniew Czyż, Faculty of Aviation, Polish Air Force University, z.czyz@law.mil.pl

Krzysztof Skiba, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, k.skiba@pollub.pl

Abstract: This study investigates the application of machine learning techniques for the prediction of aerodynamic characteristics of an electric UAV prop. system. The research included experimental propeller tests in a wind tunnel and the development of three models: a classical multilayer perceptron (MLP), a deep neural network and dropout (DNN with BN/Dropout), and a Random Forest-based model. The models were trained on data including rotational speed, airflow velocity, and the advance ratio. The objective of the modeling was to predict thrust, torque, and efficiency. The quality of the models was assessed using MSE, MAE, RMSE, and the coefficient of determination R^2 , together with residual distribution analysis, autocorrelation functions (ACF/PACF), and linear regression with confidence intervals. The analysis of residuals and ACF/PACF functions revealed a random error character in the MLP model and the presence of systematic structures in the Random Forest model. The highest accuracy was achieved for the classical MLP network, which attained $R^2 \approx 0.98$ for both thrust and torque. The Random Forest model was characterized by a markedly greater error dispersion, especially for thrust (MAE = 2.306 N). The regularized DNN network exhibited intermediate performance, achieving its best fit for torque ($R^2 = 0.931$). A residual analysis verified the random error pattern in the MLP model and systematic structures in the RF model. Prediction of the dimensionless thrust and power coefficients C_T and C_P resulted in the lowest mean errors for the MLP model (MAE C_T = 6.35%, MAE C_P = 4.96%), while the RF method generated maximum errors of up to 38% for C_T and 24.5% for C_P . The results confirm that a classical neural network represents a reliable and robust tool for predictive modeling of aerodynamic parameters of an electric propeller propulsion system. It ensures acceptable systematic errors.

Keywords: Machine-learning, UAV, propeller, thrust, power

ANALYSIS OF FACTORS AFFECTING PRODUCT PRICE MARGINS IN THE DISTRIBUTION CHAIN

Michał Cioch, Faculty of Management, Lublin University of Technology,
m.cioch@pollub.pl

Arkadiusz Gola, Faculty of Mechanical Engineering, Lublin University of Technology,
a.gola@pollub.pl

Abstract: The objective of this article is to examine the impact of product characteristics (product category, package size) and the supplier on the percentage price margin in the alcoholic beverage distribution chain, as well as to assess the usefulness of machine learning models in predicting high margins. The analysis was conducted in the R environment on a dataset of 12,260 observations. One-way analysis of variance (ANOVA) with Tukey's post-hoc test and the nonparametric Kruskal-Wallis test were used to test the research hypotheses. Two classification models were built to predict high margins: logistic regression and a CART decision tree (75/25 data split), which were evaluated using AUC, balanced accuracy, and the DeLong test. The average percentage margin in the dataset was 52.78%. The analyses confirmed a significant effect of product classification (ANOVA $F = 1932.32$; $p < 0.001$; wine 58.96% vs. spirits 37.72%), package size (ANOVA $F = 37.10$; $p < 0.001$), and supplier (Kruskal-Wallis $\chi^2 = 3100.97$; $p < 0.001$) on the margin. Logistic regression achieved an AUC of 0.9388, while the decision tree achieved an AUC of 0.9079 and a higher balanced accuracy (0.8930 vs. 0.8811), indicating purchase price as the main determinant of high margin. The results indicate that the wine category and the appropriate selection of suppliers are key factors in optimizing a distributor's profitability. Decision trees eliminate the "black box" problem by generating understandable and easy-to-implement business decision rules that support product assortment management and pricing policy.

Keywords: margin prediction, CART classification, logistic regression, decision support systems, product assortment analysis, model interpretability

RESILIENCE ANALYSIS OF A WATER DISTRIBUTION NETWORK UNDER FAILURE SCENARIOS IN THE AQUARDIS VIRTUAL CITY

Pawel Suchorab, Faculty of Environmental Engineering and Energy, Lublin University of Technology, p.suchorab@pollub.pl

Ewa Jakowiecka, Faculty of Environmental Engineering and Energy, Lublin University of Technology, s98535@pollub.edu.pl

Abstract: The data of real water distribution networks are considered sensitive, as water supply systems constitute critical infrastructure. For research purposes, quasi-real networks located in so-called virtual cities are gaining increasing popularity. Virtual cities are publicly available spatial datasets that describe the geographical structure, technical infrastructure, and demographic characteristics of a hypothetical settlement. This paper presents a resilience analysis of a water distribution system in the proprietary virtual city AquaRDIS (Aqua Research and Design for Infrastructure Sustainability) under a range of failure scenarios. The aim of the study is to evaluate the network's ability to maintain service continuity and an acceptable level of performance in the face of disruptions such as pipe failures, increased water demand for firefighting, and water contamination incidents. A simulation-based approach was employed, combining hydraulic modelling with a set of resilience indicators, including, among others, continuity of water supply and the stability of hydraulic operating conditions. Various configurations of adverse events, differing in complexity, were analysed. The results indicate that the network's topological structure and the redundancy of key components play a crucial role in mitigating the impacts of disruptions. Vulnerable areas of the system were also identified, and their targeted modernization could significantly enhance the overall resilience of the network.

Keywords: water distribution network, resilience analysis, virtual city, AquaRDIS, failure scenarios, hydraulic modelling

ULTRA-WIDEBAND-BASED VELOCITY ESTIMATION WITH KALMAN FILTERING FOR FOLLOW-ME UNMANNED GROUND VEHICLE APPLICATIONS

Łukasz Rykała, Faculty of Mechanical Engineering, Military University of Technology,
lukasz.rykala@wat.edu.pl

Karol Cieślík, Faculty of Mechanical Engineering, Military University of Technology,
karol.cieslik@wat.edu.pl

Marcin Dejewski, Faculty of Mechanical Engineering, Military University of
Technology, marcin.dejewski@wat.edu.pl

Mirosław Przybysz, Faculty of Mechanical Engineering, Military University of
Technology, miroslaw.przybysz@wat.edu.pl

Abstract: Ultra Wideband (UWB) technology is a wireless radio communication technology used, among others, in location systems. This paper presents an experimental study on velocity estimation for Unmanned Ground Vehicles (UGVs) operating in a follow-me scenario using Ultra-Wideband technology. In follow-me applications, UGV is required to continuously track and follow a moving guide. The proposed approach utilizes Two Way Ranging (TWR) distance measurements from UWB modules to derive velocity estimates of the tracked object. All signal processing and estimation algorithms were developed and validated in the MATLAB software. Experimental tests were conducted outdoor using a dedicated MDEK TREK1000 hardware, and the results were compared against reference measurements using GNSS with RTK to assess estimation accuracy. The article evaluates the obtained results in terms of their applicability to a follow-me system.

Funding: This work was financed by the Military University of Technology under research project UGB 22-104/2026 (531-000104-W100-22).

Keywords: Ultra-Wideband, velocity estimation, Unmanned Ground Vehicle, UGV, follow-me system, signal filtering, Matlab

APPARATUS FOR FIELD TESTING AND VALIDATION OF NUMERICAL MODELS OF MINE-SOIL INTERACTION UNDER WHEEL OR TRACK PRESSURE

Dariusz Kalinko, Faculty of Mechanical Engineering, Military University of Technology, dariusz.kalinko@wat.edu.pl

Marian Łopatka, Faculty of Mechanical Engineering, Military University of Technology, marian.lopotka@wat.edu.pl

Piotr Krogul, Faculty of Mechanical Engineering, Military University of Technology, piotr.krogul@wat.edu.pl

Rafał Typiak, Faculty of Mechanical Engineering, Military University of Technology, rafal.typiak@wat.edu.pl

Jarosław Duda, ZEPWN, jaroslawduda@zepwn.com.pl

Abstract: This paper presents the design, implementation and application of a dedicated experimental test rig developed for the validation of numerical models describing the interaction between vehicle running gear (wheel or track) or a demining roller, and anti-tank mine embedded in deformable soil. The proposed measurement system represents a realistic physical simulator of an anti-tank mine, reproducing the geometry and functional characteristics of real devices. It enables simultaneous measurements of the vertical displacement of the embedded object relative to the surrounding soil and the contact load applied by a wheel or a track system acting on the pressure plate of the mine's fuse. The presented apparatus allows investigation of the influence of contact area on load transfer mechanisms and soil deformation response. This paper describes a series of tests conducted using the described apparatus in conditions representative of a soil with reduced bearing capacity, where excessive settlement and load redistribution significantly affect the interaction process. Preliminary experimental results obtained for both wheeled and tracked running gears indicate that the developed apparatus and measurement methodology provide a consistent experimental basis for calibration of constitutive models and validation of advanced numerical approaches, including finite element, discrete element, or multibody dynamics methods.

This work was financed by the Military University of Technology under research project UGB 22-104/2026 (531-000104-W100-22)

Keywords: mine-soil interaction, model validation

VALIDATION STUDIES OF EQUIVALENT STIFFNESS REPRESENTATION IN A SIMULATION MODEL OF A RIBBON PONTOON BRIDGE

Marcin Dejewski, Faculty of Mechanical Engineering, Military University of Technology, marcin.dejewski@wat.edu.pl

Tomasz Muszyński, Faculty of Mechanical Engineering, Military University of Technology, tomasz.muszynski@wat.edu.pl

Lucjan Śniezek, Faculty of Mechanical Engineering, Military University of Technology, lucjan.sniezek@wat.edu.pl

Dariusz Kalinko, Faculty of Mechanical Engineering, Military University of Technology, dariusz.kalinko@wat.edu.pl

Abstract: The focus of the study is determination of the structure's longitudinal stiffness, its implementation into the kinematic constraints of the simulation model, and the subsequent validation of the adopted approach. The main objective was to achieve a high-fidelity representation of the actual behavior of connections between pontoon blocks by accounting for both their angular compliance and joint clearance. The model parameters, including the bending stiffness of a pontoon block, the angular stiffness of block connections, and the limiting locking angle of the joints, were determined from an analysis of experimental results obtained on a real structure. The tests were performed by the Engineer Research and Development Center and published in a publicly available report. In the first stage, the bending stiffness of a single pontoon was determined from measurements of deflection under static load. Next, based on tests of two connected pontoon blocks, the angular stiffness coefficient of the connection was identified by separating the contributions of deformations in the load-bearing structure and in the joint components. In the final stage, a numerical model of the bridge was formulated to reproduce static loading conditions on a water obstacle, and the limiting locking angle of the joints was determined by minimizing differences between experimental and numerical results. Model accuracy was assessed by comparing vertical displacements of characteristic points obtained in simulations and experiments. The results confirmed that the adopted description and the identified parameters of equivalent stiffness and joint clearance enable an accurate representation of the static behavior of the IRB pontoon bridge.

Funding: This work was financed by the Military University of Technology under research project UGB 22-104/2026 (531-000104-W100-22).

Keywords: pontoon bridge, longitudinal stiffness, numerical model, multibody system

A DOMAIN-AGNOSTIC FRAMEWORK FOR UNCERTAINTY-GUIDED HYBRID SIMULATION IN DIGITAL TWINS

Monty J Singh, Indian Institute of Technology Ropar, monty.21csz0005@iitrpr.ac.in

Balwinder Sodhi, Indian Institute of Technology Ropar, sodhi@iitrpr.ac.in

Abstract: Virtual counterparts of digital twins use physics-based models, real-time data, and computational intelligence for analysis and decision support. All these approaches deploy surrogate models to approximate the behaviour of high-fidelity physics solvers such as the Finite Element Method (FEM) and Computational Fluid Dynamics (CFD), facilitating efficient prediction of complex systems governed by nonlinear differential equations. However, surrogate models are prone to significant epistemic uncertainty (a lack of knowledge due to limited data) when subjected to unpredictable operational scenarios, leading to silent failures and faulty predictions. Existing approaches to uncertainty quantification are typically passive, providing confidence estimates without influencing model execution. This paper introduces an uncertainty-gated hybrid digital twin framework in which epistemic uncertainty is actively used as a control signal for adaptive model selection. The framework consists of three components : (i) a physics-based solver that provides high-fidelity reference solutions; (ii) a surrogate model augmented with uncertainty estimation techniques to quantify epistemic uncertainty; and (iii) a gating mechanism that dynamically triggers fallback to the physics solver when uncertainty exceeds a predefined threshold. This helps to flexibly switch between fast surrogate predictions and accurate numerical simulations while maintaining computational efficiency. The framework is validated on multiple engineering benchmarks, including fluid flow, structural deformation, and heat transfer under varying operating conditions. Results demonstrate that uncertainty-triggered solver activation significantly improves predictive reliability while reducing computational cost compared to always-on high-fidelity simulations. The framework effectively prevents silent surrogate failures in out-of-distribution regimes while minimising unnecessary solver calls. The work highlights that epistemic uncertainty can be used as an active decision variable in hybrid simulation, enabling self-aware digital twins that balance efficiency and accuracy in real-time computational environments.

Keywords: Digital Twins, Epistemic uncertainty, CFD, FEM

THE USE OF DIGITAL VOLUME CORRELATION WITH COMPUTED TOMOGRAPHY TO ANALYZE DISPLACEMENT AND WALL THICKNESS OF MULTI- OPERATIONAL PRESSING OF CYLINDRICAL ALUMINUM EXTRUSIONS

Damian Bańkowski, Department of Materials Science and Materials Technology,
Faculty of Mechatronics and Mechanical Engineering, Kielce University of Technology,
al. 1000-lecia P.P. 7, 25-314 Kielce, Poland, damianbankowski1@gmail.com

Piotr Młynarczyk, Department of Materials Science and Materials Technology, Faculty
of Mechatronics and Mechanical Engineering, Kielce University of Technology, al.
1000-lecia P.P. 7, 25-314 Kielce, Poland, piotrm@tu.kielce.pl

Tomasz Milek, Department of Materials Science and Materials Technology, Faculty of
Mechatronics and Mechanical Engineering, Kielce University of Technology, al. 1000-
lecia P.P. 7, 25-314 Kielce, Poland, tmatm@tu.kielce.pl

Abstract: This paper presents the possibility of using computed tomography to determine displacements and stresses during controlled deformation. Tomographic examinations are most often used to assess the quality of castings, welded joints, 3D prints, and electronic systems. These non-destructive tests enable spatial imaging of even the smallest changes in the material, such as cracks, porosity, inclusions, and many other imperfections. Dedicated programs enable precise qualitative analysis, including analysis of porosity, inclusions of other materials, material division, creation of a digital twin, and other advanced options such as digital volume correlation or analysis of the state of displacements and stresses. The Digital Volume Correlation tool allows for the comparison of components in two states before and after deformation. The tests were conducted on aluminum samples. The samples were first extruded and then re-extruded in the next three stages. Single-voxel displacement tracking was used to determine the displacements and von Mises strain in the material. VG Studio software allows for visual representation of displacement and stress. The data obtained also enabled analysis of the thickness of the wall after deformation. The research results indicate that tomographic examinations and Digital Volume Correlation (DVC) assessment can be successfully used to monitor the condition of devices and structures. The scientific aim of the article is to reveal the magnitude of changes in material displacement in extruded elements and compare them with the change in the height of the extrudates. Moreover, the work aims to show changes in the wall thickness of the extrudates throughout their volume and to compare the results of CT tests with measurements using classical methods.

Keywords: computed tomography, Digital Volume Correlation, drawing, material deformation, wall thickness

STUDY OF THE INFLUENCE OF ESD PROCESS PARAMETERS AND A COMPARATIVE ANALYSIS OF MICROSCOPY AND COMPUTED TOMOGRAPHY IN THE QUALITATIVE ASSESSMENT OF COPPER COATINGS ON AN ALUMINIUM SUBSTRATE.

Piotr Mlynarczyk, Faculty of Mechatronics and Mechanical Engineering, Kielce
University of Technology, piotrm@tu.kielce.pl

Abstract: This article presents research into surface coatings produced by the electro-spark deposition (ESD) method on aluminium using a copper electrode. ESD is a surface modification technique that uses short current pulses (electrical discharges) to transfer material from the working electrode (anode) to the workpiece (cathode). The evaluation involved observing the effect of voltage and capacitor capacitance during the ESD process on the thickness of the ESD coating. To minimise the number of experiments required, a two-factor, five-level Hartley experimental design was selected. The study demonstrates the potential use of computed tomography to monitor the condition of the resulting ESD coating. VG Studio software enables visualisation of the resulting ESD coating, including measurement of its thickness or volume. Microscopic observations were then carried out on the prepared samples to analyse the thickness and structure of the coatings. The use of tomographic studies in the analysis of ESD coatings ensures significantly greater representativeness of the results compared to traditional microscopy. It allows for a spatial assessment of the coating's continuity, which eliminates the risk of misinterpreting quality based on individual cross-sections. Furthermore, the spatial data obtained from the basis for precise mathematical models, enabling a better understanding of the process's energy balance and more accurate prediction of ESD coating thickness as a function of process parameters.

Keywords: electro-spark deposition, computed tomography, microscopic examination, coatings

ENTROPY-BASED INDICES IN ECONOMIC AND SOCIAL RESEARCH

Daniel Plisau, Faculty of Environmental Engineering and Energy, Lublin University of Technology, dplisau@gmail.com

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University of Technology, g.lagod@pollub.pl

Abstract: Entropy-based indices, rooted in Shannon's information theory, have proven their value in the natural sciences as robust measures of diversity and structural complexity. However, their application in economics and the broader social sciences remains underexplored, despite considerable methodological potential. This article examined the possible ways of employing entropy-based indices, particularly the Shannon index and the related Theil index in economic and social research, and discussed the analytical gains such applications may offer. The paper reviewed existing cases where entropy measures have already found economic use: as indicators of sectoral diversification of regional and national economies, as measures of income inequality and distributional uncertainty, and as tools for assessing country competitiveness and export specialization in international trade. Building on these precedents, the elaboration advanced the argument that entropy-based indices could substantially enrich analyses in the tradition of Thomas Piketty's *Capital in the Twenty-First Century* (2013). Where Piketty relied primarily on aggregate wealth-to-income ratios and income shares of top deciles, entropy measures allow for a more granular decomposition of distributional structures across sectors, time periods, and countries. Applied to the data on the distribution of employment and GDP across economic sectors, the Shannon index reveals the patterns of structural convergence or divergence that conventional metrics may obscure. The work concluded that entropy-based indices constitute a promising and accessible complement to established social science tools, capable of capturing distributional complexity at multiple scales.

Keywords: Shannon entropy, entropy-based indices, Theil index, economic diversity, income inequality, structural change, sectoral analysis, information theory, social sciences

ANALYSIS OF MULTIDIMENSIONAL DATA CONTAINING PRECIPITATION VARIABILITY AND THE PRESENCE OF MICROORGANISMS IN THE BYSTRZYCA RIVER FOR ENVIRONMENTAL MONITORING PURPOSES

Albert Raczkiewicz, Faculty of Mathematics and Information Technology, Lublin
University of Technology, a.raczkiewicz@pollub.pl

Magdalena Pilat-Rożek, Faculty of Mathematics and Information Technology, Lublin
University of Technology, m.pilat-rozek@pollub.pl

Aleksandra Kozłowska, Doctoral School, Lublin University of Technology,
aleksandra.kozłowska1@pollub.edu.pl

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University
of Technology, g.lagod@pollub.pl

Abstract: The rapid growth of urban areas, industry, and agricultural activities contributes to increasing pressure on aquatic ecosystems. One of the key factors affecting surface water quality is precipitation, which can cause pollutants to be washed off from catchment areas and transported into rivers. Variability in precipitation, including both dry periods and heavy rainfall events, may influence environmental conditions and the abundance of microorganisms in flowing water bodies. The aim of this study was to analyze the relationship between precipitation variability and the occurrence of periphytic microorganisms in the Bystrzyca River in the Lublin area. The research material consisted of samples collected at selected monitoring sites located along the studied section of the river. Data on microorganism abundance were compared with precipitation records from a weather station located within the catchment area from which rainwater is drained into the stormwater system and subsequently discharged into the Bystrzyca River. Particular attention was paid to determining the correlation between precipitation intensity and the abundance of individual microorganism species. The analysis made it possible to assess the impact of precipitation variability over time on changes in the quantitative characteristics of periphytic algal communities in the Bystrzyca River. The results may support surface water quality monitoring and help identify periods and areas particularly vulnerable to deterioration in ecological status. The data were analysed using entropy-based indices derived from information theory (e.g. the Shannon Index) by R statistical programming language (RStudio), which made it possible to assess both diversity and the structural balance of the communities.

Keywords: Multidimensional data, precipitation variability, peryphyton, green algae

RECOGNIZING TESTACEA USING AUTOMATIC IMAGE ANALYSIS ALGORITHMS – EUGLYPHA AS AN EXAMPLE

Michał Staniszewski, Faculty of Environmental Engineering and Energy, Lublin University of Technology, m.staniszewski@pollub.pl

Aleksandra Kozłowska, Doctoral School, Lublin University of Technology, aleksandra.kozłowska1@pollub.edu.pl

Roman Babko, Schmalhausen Institute of Zoology, National Academy of Sciences of Ukraine, rbabko@ukr.net

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University of Technology, g.lagod@pollub.pl

Abstract: Single-celled eukaryotes from the Euglyphae family are a bioindicator in activated sludge wastewater treatment. Their condition can help determine the quality of the entire ecosystem responsible for the process, as well as detect irregularities and predict impending failure. This work focused on the application of various versions of the automatic image recognition algorithm (YOLO) to recognise Euglypha organisms obtained using a microscope, and the robustness of the algorithm to human errors made during image preparation using a previously trained algorithm. Particular emphasis was placed on changes in individual versions of the algorithm that have emerged with technological advancements and the requirements resulting from the recognition of specific types of objects.

Keywords: image analysis, object localisation and recognition, machine learning, Euglypha, activated sludge, treatment plant

GIS-BASED AUTOMATION OF INPUT DATA PREPARATION FOR HYDRODYNAMIC STORMWATER SYSTEM MODELING

Beata Surma, Faculty of Environmental Engineering and Energy, Lublin University of Technology, beata.surma@pollub.edu.pl

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University of Technology, g.lagod@pollub.pl

Abstract: The study proposes a methodology for automating the preparation of a hydrodynamic stormwater sewer network model using a GIS environment. The developed algorithm employs QGIS tools to automatically determine and assign the parameters required for individual model elements. The greatest benefit of the proposed automation was achieved in generating the parameters that are not directly available in the source data, but are derived from object geometry and spatial relationships. The final stage of the developed algorithm consisted of generating an SWMM input file using a dedicated QGIS plugin. The proposed methodology was applied to develop a hydrodynamic model of a selected section of the stormwater network in Lublin. The simulation results were used to evaluate the hydraulic performance of the stormwater network in terms of pavement maintenance and road traffic safety, as well as to develop an operational risk classification supporting the planning of monitoring, maintenance, and rehabilitation of the stormwater system infrastructure.

Keywords: Geographic Information System, QGIS, SWMM, hydrodynamic modeling, input data preparation, pavement maintenance, road traffic safety

THE USE OF SELECTED DEEP LEARNING METHODS FOR THE DETECTION AND CLASSIFICATION OF BIOLOGICAL OBJECTS ON DIGITAL IMAGES

Diana Morzhak, Faculty of Mathematics and Information Technology, Lublin
University of Technology, s101804@pollub.edu.pl

Magdalena Pilat-Rożek, Faculty of Mathematics and Information Technology, Lublin
University of Technology, m.pilat-rozek@pollub.pl,

Aleksandra Kozłowska, Doctoral School, Lublin University of Technology
aleksandra.kozlowska1@pollub.edu.pl

Grzegorz Łagód, Faculty of Environmental Engineering and Energy, Lublin University
of Technology, g.lagod@pollub.pl

Abstract: This study investigated the use of selected deep learning methods for the detection and classification of biological objects – testate amoebae, which play a significant role in the bioindication process due to their sensitivity to environmental changes in water quality. Traditional detection of such organisms is time-, work-, and cost-intensive, as it requires an analysis to be carried out by a qualified specialist. Consequently, the use of deep learning models for this purpose makes it possible to speed up the selected species identification process during bioindication assessment of technological lines of treatment or evaluation of natural environment quality. The data used in this study were prepared using a transmitted light microscope in bright field observation mode coupled with a digital camera mounted on the third optical line. Collected environmental samples were divided into three separate sets for model training, validation, and testing. The approach to training included fine-tuning and the use of adjusted hyperparameters for the target dataset. The architectures were evaluated and compared based on their effectiveness in detecting the testate amoebas. The comparison was made on the basis of standard metrics specified for assessing models' quality of detection, sensitivity, specificity, and accuracy of predictions.

Keywords: deep learning methods, detection and classification of objects, automatic analysis of digital images, testate amoebae

STABLE CLASS-CONDITIONED QUANTISED VAE FOR SYNTHETIC LUNG DISEASE VOLUMES

Barbara Stefaniak, Research and Development Center, Netrix S.A.,
barbara.stefaniak@netrix.com.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of
Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Abstract: This study evaluates autoencoder (AE), variational autoencoder (VAE), and class-conditioned quantised variational autoencoder (QVAE) architectures for controllable generation of synthetic lung-disease volumes. Data were produced by a numerical physiological model as $128 \times 128 \times 128$ voxel grids; each case was described by up to 22 parameters and assigned to one of seven categories spanning healthy lungs and six respiratory conditions. The QVAE uses nearest-codebook quantisation, a straight-through estimator, exponential-moving-average codebook updates, and affine latent modulation from learned class embeddings. To counter instability at higher latent dimensions, training combines Group Normalisation, LeakyReLU, variance safeguards, automatic mixed precision with gradient scaling, gradient clipping, KL annealing, VQ-loss warmup, AdamW optimisation, adaptive learning-rate reduction, and early stopping. Comparison shows that the AE reconstructs efficiently but cannot support reliable latent sampling, while the VAE yields smoother interpolation but limited discrete semantic control. At $z = 512$, the QVAE converged stably. Despite transient KL-term growth, reconstruction loss stabilised and decreased after annealing, no NaN excursions were observed, and class conditioning enabled disease-guided synthesis. These results demonstrate that controllable volumetric generation depends jointly on structured latent coding, sufficient representational capacity, and explicit numerical-stability engineering. The framework supports targeted synthesis and future augmentation of synthetic lung-imaging datasets, and motivates ablation studies of loss weighting and codebook utilisation.

Keywords: quantised variational autoencoder, class-conditioned generation, lung disease imaging, synthetic volumetric data, vector quantisation, numerical stability

AOA SENSORS AND CLUSTER TRIANGULATION FOR 3D INDOOR LOCALIZATION

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Paweł Kaleta, WSEI University, Pawel.Kaleta@wsei.pl

Marcin Dziadosz, Faculty of Mathematics and Information Technology, Lublin University of Technology, m.dziadosz@pollub.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Michał Oleszek, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, michal.oleszek@netrix.com.pl

Michał Styła, Information Technology Research & Development Centre (CBRTI sp. z o. o.), michal.styla@cbrti.pl

Abstract: This study presents a simulation framework for tracking a moving transmitter in three-dimensional indoor space by combining multi-anchor angle-of-arrival (AoA) sensing with spatial triangulation. Ceiling-mounted anchors are represented by eight-element antenna arrays. For each trajectory sample, the model generates IQ observations from the transmitter-to-array geometry and independently estimates azimuth and elevation at every anchor using the Multiple Signal Classification (MUSIC) algorithm. Parabolic interpolation of the MUSIC pseudospectrum refines the directional estimate beyond the angular scan-grid resolution. Pairwise anchor rays then produce candidate positions. To limit the influence of inconsistent intersections, the solution identifies the dominant group using DBSCAN, averages its points, and applies a median-based fallback when triangulation is unstable or data are sparse. Simulations reproduce horizontal motion together with small height variations and compare configurations with three, four, and five anchors. The mean localization errors were 56.576 cm, 41.194 cm, and 2.573 cm, respectively. The results show that increased measurement redundancy can substantially improve both localization accuracy and robustness to individual AoA errors, although performance remains dependent on anchor geometry and angular-estimation quality. Under the analyzed scenario, the five-anchor configuration achieved centimeter-level accuracy. The framework provides a reproducible basis for studying error propagation, optimizing anchor deployment, and developing resilient indoor localization systems before hardware implementation.

Keywords: three-dimensional indoor localization, angle of arrival, music algorithm, antenna arrays, spatial triangulation, DBSCAN clustering, moving-object tracking, localization error

MONTE CARLO MODELLING OF LIGHT TRANSPORT FOR OPTICAL TOMOGRAPHY IN HETEROGENEOUS MEDIA

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Marcin Dziadosz, Faculty of Mathematics and Information Technology, Lublin University of Technology, m.dziadosz@pollub.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Mariusz Mazurek, Institute of Philosophy and Sociology, Polish Academy of Sciences, mmazurek@ifispan.edu.pl

Paweł Tchorzewski, Research and Development Center, Netrix S.A.,
pawel.tchorzewski@netrix.com.pl

Abstract: This paper presents a Monte Carlo framework for simulating photon transport in heterogeneous absorbing and scattering media as a simplified forward model for optical tomography. The method tracks individual photons through spatial maps of the absorption coefficient, scattering coefficient, and local light-propagation velocity, thereby allowing inclusions with optical properties different from the background to be represented. Photons are initialized at the boundary of the computational domain and propagated iteratively. At each step, survival is governed by $\exp[-(\alpha + \sigma)\Delta s]$, whereas scattering events and changes in direction are sampled stochastically. Photons reaching the detector are counted and removed, and a density map of visited grid points is accumulated to characterize transport paths. The implementation supports both CPU and GPU execution. In an illustrative experiment, 20,000 photons were launched into a medium containing a spherical inclusion. The background coefficients were $\alpha = 0.02 \text{ m}^{-1}$ and $\sigma = 0.005 \text{ m}^{-1}$, while both coefficients within the inclusion were set to 0.1 m^{-1} . The inclusion produced marked changes in the spatial distribution of photons and in detector statistics, with 8,776 photons ultimately registered. The results confirm that the model captures the influence of localized optical heterogeneity on photon propagation and detection. The proposed framework can support synthetic-data generation, detector-configuration studies, and subsequent development of reconstruction algorithms for optical tomography.

Keywords: Monte Carlo simulation, photon transport, optical tomography, heterogeneous media, optical absorption, multiple scattering, GPU computing

FINITE ELEMENT METHOD (FEM)

THE EFFECT OF TRANSITION RADIUS ON DRY ICE FLOW AND BOUNDARY FORCE DURING THE EXTRUSION PROCESS: AN ANALYTICAL-NUMERICAL- EXPERIMENTAL STUDY

Jan Górecki, Faculty of Mechanical Engineering, Poznań University of Technology,
jan.gorecki@put.edu.pl

Krzysztof Wałęsa, Faculty of Mechanical Engineering, Poznań University of
Technology, krzysztof.walesa@put.poznan.pl

Abstract: The study examines the influence of the transition radius on dry ice flow behavior and boundary extrusion force in the compaction–extrusion process using single-channel conical–cylindrical dies. An original analytical model is proposed to describe the relationship between die geometry and material flow kinematics, with particular emphasis on the role of the convex transition radius in shaping velocity value and force conditions within the die channel. The analytical predictions are validated through numerical simulations and experimental investigations. Numerical analyses are conducted using the Drucker–Prager Cap model combined with the Smoothed Particle Hydrodynamics method to capture the compressible behavior of dry ice and large deformation flow in the transition region. Experimental tests are performed using a dedicated test rig, and the results are evaluated statistically to ensure reliability. The results demonstrate that increasing the transition radius improves flow uniformity and reduces stress concentrations. Good agreement between analytical, numerical, and experimental results confirms the validity of the proposed approach. The developed framework provides a physically consistent basis for the design and optimization of extrusion dies, thereby improving process efficiency and enhancing tool durability in dry ice pellet production.

Keywords: dry ice extrusion, extrusion velocity, limit extrusion force, transition section geometry, energy consumption

COMPOSITE FOAM BASED SANDWICH STRUCTURE SUBJECTED TO LOW-VELOCITY IMPACT

Michał Rogala, Faculty of Mechanical Engineering, Lublin University of Technology,
m.rogala@pollub.pl

Abstract: This study presents an experimental-numerical investigation of the low-velocity impact (LVI) response of composite sandwich structures incorporating a metal-ceramic foam core and carbon fiber reinforced polymer (CFRP) face sheets with different stacking sequences. The primary objective is to evaluate the influence of fiber architecture on damage initiation, propagation mechanisms, and overall impact resistance. LVI tests were conducted under controlled energy levels, enabling quantitative assessment of force-displacement response, energy absorption, and peak load characteristics. The experimental campaign was complemented by finite element simulations developed in an explicit dynamic framework. The numerical model incorporates advanced material descriptions, including strain-rate sensitive plasticity for metallic constituents, Hashin-based damage criteria for composite plies, and cohesive zone modeling for interfacial debonding. The results demonstrate that the stacking sequence of CFRP layers significantly affects both the damage tolerance and energy absorption capability of the sandwich structure. Hybrid configurations exhibit improved impact performance, characterized by delayed damage initiation and enhanced dissipation of impact energy.

Keywords: fiber composite, metal-ceramic foam, low-velocity impact, damage analysis, finite element method

MODEL SIMPLIFICATIONS INFLUENCE ON A SMALL-CALIBRE PROJECTILE ARMOUR PENETRATION SIMULATIONS RESULTS

Radosław Kiciński, Mechanical and Electrical Engineering Faculty, Polish Naval Academy, r.kicinski@amw.gdynia.pl

Bogdan Szturomski, Mechanical and Electrical Engineering Faculty, Polish Naval Academy, b.szturomski@amw.gdynia.pl

Jamal Hamoud, PGZ Naval Shipyard, jhamoud@pgzsw.com.pl

Michał Grylewicz, Mechanical and Electrical Engineering Faculty, Polish Naval Academy, m.grylewicz@amw.gdynia.pl

Abstract: This paper presents an analysis of the perforation process of a steel armor plate by a small-caliber projectile using the finite element method (FEM) in a dynamic approach. The study aimed to determine the impact of simplifications in the numerical modeling of the projectile on the obtained results and to verify these through experimental field tests. The research involved simulations employing various projectile models: perfectly rigid, elastic, plastic, and plastic with a failure criterion. The simulation results were compared with actual values of projectile velocity after perforating a 1.3964 steel sample and with the morphology of deformations. It was found that including the plastic properties and failure criterion of the projectile significantly influences the accuracy of the results, particularly regarding the final velocity and deformation of the sample. Experimental tests were carried out for impact angles ranging from 0° to 35°, measuring the projectile velocity before and after passing through the sample and analysing the perforation process using a high-speed camera. Based on the results, the critical ricochet angle for 1.3964 steel and 7,62 MSC bullet was between 60° and 70°. The results demonstrate that numerical simulations are an effective and economical tool for designing anti-armor protection. It was also shown that the appropriate selection of material parameters and the projectile model is crucial for achieving agreement between simulation results and experimental data.

Keywords: FEM, shooting, ricochet, rapid change process, dynamic explicit

FANCY FENCE - A NEW TYPE OF ANTI-TERRORIST RETRACTABLE GATE - DESIGN AND REAL CRASH TEST

Daniel Bronisław Nycz, JP NOVATION SP. Z O.O., daniel@fancyfence.eu

Rafał Gajda, JP NOVATION SP. Z O.O., rafal@fancyfence.eu

Jacek Kühnl-Kinel, JP NOVATION SP. Z O.O., jacek@fancyfence.eu

Adam Spurtacz, JP NOVATION SP. Z O.O., adam@fancyfence.eu

Abstract: In recent years, increasing demand has been observed for effective and modern infrastructure protection systems, particularly in response to vehicle-ramming terrorist threats. Fancy Fence has developed a dedicated anti-terrorist gate designed to protect critical facilities against such attacks. The solution meets the stringent requirements of ASTM F2656 and IWA 14-1 standards with respect to vehicle impact resistance. A key feature distinguishing the Fancy Fence gate is its fully retractable design, allowing the structure to be completely concealed below ground level in the open position. This paper presents the engineering development process, including Finite Element Method (FEM) analyses, as well as the manufacturing and certification of a prototype of a novel anti-terrorist gate. The primary design objective was to stop an N2B-class vehicle with a mass of 7.2 t traveling at speeds up to 48 km/h. A critical performance requirement was achieving penetration class P1 (penetration ≤ 1 m), ensuring that the vehicle is immobilized and prevented from passing beyond the gate line after impact. The design process required balancing resistance to extreme dynamic loading with structural compatibility within the existing Fancy Fence product portfolio. Additional requirements included operational ergonomics, architectural aesthetics, and integration with surrounding infrastructure. SolidWorks was used for mechanical design and linear static strength verification, while ANSYS LS-DYNA was applied for explicit dynamic simulations of vehicle impact. Experimental validation was performed through a full-scale crash test conducted at the CTS Crash Test Service GmbH facility in Germany. Due to high logistical and organizational costs, the test was performed only once. Performance assessment was based on penetration measurements and evaluation of post-impact structural integrity. After the crash test, the impacting vehicle was classified as non-operational, confirming the effectiveness of the developed anti-terrorist gate.

Keywords: anti-terrorist gate, FEM simulations, vehicle impact, crash test, LS-DYNA, SolidWorks Simulation, infrastructure security, Fancy Fence, underground gates

FEM-BASED ANALYSIS OF SOIL SUFFOSION TRIGGERED BY PIPELINE LEAKAGE

Malgorzata Iwanek, Faculty of Environmental Engineering and Energy, Lublin
University of Technology, m.iwanek@pollub.pl

Abstract: Failures and damage to pipelines, along with associated leakages, occur in water supply systems throughout their entire service life. Such events entail economic costs resulting from water losses and the need to repair the damaged network. Moreover, water leakages may induce suffosion processes, during which the washing out of soil particles can lead to the formation of voids beneath the ground surface and, consequently, ground subsidence. These phenomena pose a threat to the safety of people and property, particularly in urban areas. For suffosion to occur, two fundamental conditions must be satisfied: a geometric condition, related to the soil grain size distribution, and a hydraulic condition, associated with the velocity of water flow through soil pores. The aim of this paper is to analyze the influence of hydraulic pressure in the water supply system, groundwater table position, and soil permeability on the velocity at which water spreads within the soil, with particular emphasis on the possibility of fulfilling the hydraulic condition for suffosion. The study is based on numerical simulations of water supply system failures carried out for various computational scenarios using FEFLOW v. 5.3, based on the finite element method. The simulation results were experimentally verified through a controlled water supply failure conducted under real conditions.

Keywords: water pipes, leakages, FEFLOW, FEM, suffosion

EFFECT OF THE CROSS-SECTION ON THE ENERGY ABSORPTION AND BENDING BEHAVIOR OF BENT TUBES

Quirino Estrada, Instituto de Ingeniería y Tecnología, Universidad Autónoma de Ciudad Juárez, Mexico, quirino.estrada@uacj.mx

Jose Manuel Cuenca Delgado, Departamento de Ingeniería Mecánica, TecNM/CENIDET, Mexico, d14ce002@cenidet.tecnm.mx

Eladio Martinez Rayon, Departamento de Ingeniería Mecánica, TecNM/CENIDET, Mexico, eladio.mr@cenidet.tecnm.mx

Elva Reynoso, Instituto de Ingeniería y Tecnología, Universidad Autónoma de Ciudad Juárez, Mexico, elva.reynoso@uacj.mx

Alejandro Rodriguez-Mendez, Departamento de Ingeniería Mecánica, Tecnológico Nacional de México campus Ciudad Guzmán, Mexico, alejandro.rm@cdguzman.tecnm.mx

Aztlan Bastarrachea, Departamento de Ciencias Básicas, Tecnológico Nacional de México campus Ciudad Juárez, Mexico, aztlan.ba@itcj.edu.mx

Jesus Silva, Instituto de Ingeniería y Tecnología, Universidad Autónoma de Ciudad Juárez, Mexico, jesilva@uacj.mx

Manuel Nandayapa, Instituto de Ingeniería y Tecnología, Universidad Autónoma de Ciudad Juárez, Mexico, mnandaya@uacj.mx

Abstract: When a bent tube is subjected to transverse load, it has the capacity to resolve this load into both axial and bending components, allowing the structure to obtain a combined stress state. This confers a higher structural efficiency respect to straight tubes. The crashworthiness performance of bent tubes depends on multiple factors such as material, configurations, and geometrical parameters. However, studies on the cross-section of bent tubes has been scarcely reported despite presenting a better performance than their straight counterparts when subjected to bending loads. In this sense, the current article, firstly evaluated the mechanical response of straight versus bent tube. Lately, a second analysis evaluates numerically the effect of the cross-section on bending resistance and energy absorption of bent tubes. For this purpose, five bent tubes with different cross-sections including circular, triangular, square and rectangle shapes were numerically evaluated by three-point bending test. In all cases, the bent tubes presented the same geometric characteristics and mass. During the simulation, the tubes were conferred with elastoplastic models for aluminum alloy 6063-T5. The feasibility of numerical results was guaranteed since an experimental validation of a circular straight tube under three-point test was presented. According to results, the effectiveness of bent tube respect to straight tube was obtained since and improvement on E_a up to 22.84% was computed. On the other hand, the importance of the cross-section of the crashworthiness performance of bent tube was confirmed. A better crashworthiness performance is obtained when a circular cross-section is used. From this, a CFE value of 0.87 was computed, yielding 13.14% respect to the lowest CFE obtained for the rectangular bent profile

Keywords: bent tubes; structural strength; energy absorption; thin-walled tubes; finite element analysis

CMES'26 draft version

EQUIVALENT STATIC FINITE ELEMENT ANALYSIS OF HUMAN SKULL LOADING UNDER CONDITIONS REPRESENTATIVE OF MOTORCYCLE COLLISIONS

Jarosław Zubrzycki, Faculty of Mathematics and Information Technology, Lublin
University of Technology, j.zubrzycki@pollub.pl

Quirinio Estrada, Instituto de Ingeniería y Tecnología, Universidad Autónoma de
Ciudad Juárez, Mexico, quirino.estrada@uacj.mx

Magda Wlazlo, Faculty of Mathematics and Information Technology, Lublin University
of Technology, m.wlazlo@pollub.pl

Abstract: Motorcycle accidents are a major cause of severe head injuries, and numerical modelling provides a useful approach for investigating the mechanical response of cranial structures under collision-related loading. This study presents a comparative equivalent static finite element analysis of a patient-specific human skull reconstructed from computed tomography data. The novelty of the study lies in the use of an anatomically reconstructed CT-derived skull model to systematically compare cranial stress and displacement responses under equivalent static loading conditions corresponding to a consistent series of motorcycle collision velocities from 40 to 140 km/h. The skull was represented as a homogeneous, isotropic, linearly elastic structure, and equivalent resultant forces corresponding to 40, 60, 100, and 140 km/h were distributed over the superior cranial surface. The model was constrained at the occipital condyles. The calculated peak von Mises stress reached approximately 146 MPa at 40 km/h and increased to approximately 902 MPa at 140 km/h. The highest stress concentrations occurred near the occipital constraint region and in the frontal cranial area, whereas the largest displacements occurred in regions distant from the fixation points. Because the model did not include damage initiation or post-failure behaviour, stresses exceeding the literature-based cranial bone fracture threshold were interpreted as comparative indicators of potential structural failure rather than realistic post-fracture stresses. The proposed approach provides a simplified framework for identifying loading conditions and anatomical regions in which cranial bone strength criteria may be exceeded and establishes a basis for future nonlinear and transient analyses.

Keywords: finite element analysis; human skull; equivalent static loading; motorcycle collision; cranial biomechanics; fracture initiation; computed tomography.

DESIGNING VEHICLE STRUCTURES USING MATERIALS WITH A LOW CARBON FOOTPRINT

Bartosz Łata, Lublin University of Technology, s99456@pollub.edu.pl

Jacek Czarnigowski, Faculty of Mechanical Engineering, Lublin University of Technology, j.czarnigowski@pollub.pl

Miłosz Chwiejczak, Lublin University of Technology, s99422@pollub.edu.pl

Wiktor Iskra, Lublin University of Technology, s99434@pollub.edu.pl

Iga Kopec, Lublin University of Technology, s106243@pollub.edu.pl

Abstract: The development of vehicle designs is currently focused on energy optimisation with a view to reducing their negative impact on the environment. One area of development involves the use of renewable or naturally based materials. This article presents simulation analyses of the monocoque structure of a prototype vehicle designed for the Shell EcoMarathon competition. The new vehicle structure was analysed, considering both conventional materials (carbon fibre) and natural materials (linen). The research was conducted on the new monocoque structure of the vehicle, utilising material tests carried out by the authors. The results of FEM analyses of the structure loaded with the driver's weight are presented. Analyses were presented showing that the use of linen reduces the structural strength compared to a carbon fibre structure. With the same material thickness, the deformation and load on the structure increase significantly when natural materials are used. It was also demonstrated that, in order to maintain deformation at the same level, it is necessary to increase the thickness of the structure by 30%, which results in a 10% increase in the vehicle's mass. However, it was shown that the use of natural materials will allow for the achievement of a correct structure.

Keywords: vehicle, composites, FEM, simulations

DEVELOPMENT OF A DIGITAL CAD MODEL OF THE LUBLIN R-XIIID AIRCRAFT

Paweł Wysmulski, Faculty of Mechanical Engineering, Lublin University of Technology, Poland, p.wysmulski@pollub.pl

Konrad Pietrykowski, Faculty of Mechanical Engineering, Lublin University of Technology, k.pietrykowski@pollub.pl

Hubert Dębski, Faculty of Mechanical Engineering, Lublin University of Technology, Poland, h.debski@pollub.pl

Michał Rogala, Faculty of Mechanical Engineering, Lublin University of Technology, Poland, m.rogala@pollub.pl

Jakub Paśnik, Faculty of Mechanical Engineering, Lublin University of Technology, Poland, j.pasnik@pollub.pl

Mirosław Ferdynus, Faculty of Mechanical Engineering, Lublin University of Technology, Poland, m.ferdynus@pollub.pl

Kuba Roslaniec, Faculty of Mechanical Engineering, Lublin University of Technology, Poland,

Abstract: The reconstruction of historical aircraft often requires combining limited archival data with modern engineering tools. This challenge is particularly evident in the case of the Polish pre-war reconnaissance and liaison aircraft Lublin R-XIIID, for which no complete technical documentation has survived. The objective of the presented work is the development of a comprehensive digital CAD model of the Lublin R-XIIID aircraft as a basis for the construction of a full-scale flying replica. The modelling process was carried out in the CATIA V5 environment using contemporary computer-aided design techniques. Available archival drawings, photographs, and surviving technical information were collected and analysed. Historical drawings were imported into the CAD system and scaled to the known overall dimensions of the aircraft using the Sketch Tracer module, enabling the reconstruction of the external geometry and creation of a conceptual model. Based on the reconstructed outer shape, detailed structural models of the fuselage, wing, empennage, and landing gear were developed. One of the principal challenges was the recreation of the original design philosophy of a 1930s aircraft while simultaneously adapting the structure to modern engineering practices and manufacturing requirements. Particular attention was devoted to the wing structure. The original wooden spars and ribs were replaced by metallic counterparts while preserving the number, arrangement, and aerodynamic geometry of the original components. The redesigned wing incorporates metallic spars consisting of a web reinforced by pairs of angle sections, while the ribs were designed as thin-walled sheet-metal structures. Composite materials were used only in selected non-structural fairings, such as wingtip fairings and aerodynamic covers. The resulting CAD model represents the primary structural configuration of the Lublin R-XIIID aircraft and provides a foundation for further development activities, including control system integration, technical documentation preparation and finite element structural analyses. The presented methodology demonstrates how modern CAD tools can support the reconstruction and preservation of historical aerospace heritage while meeting contemporary engineering standards.

Keywords: historical aircraft reconstruction, CAD modelling, CATIA V5, Lublin R-XIIID, aerospace heritage, digital engineering

CMES'26 draft version

MATERIAL PROPERTIES AND STRUCTURE RESEARCH METHODS

THE ROLE OF CARBON ADDITIVES IN SHAPING THE MECHANICAL PROPERTIES OF ABS AND ASA POLYMER FILAMENTS IN THE FDM PROCESS

Robert Szczepaniak, Faculty of Aviation, Polish Air Force University,
r.szczepaniak@law.mil.pl

Zuzanna Wilkosz, Faculty of Aviation, Polish Air Force University,
z.wilkosz7112@wsosp.edu.pl

Robert Bąbel, Faculty of Aviation, Polish Air Force University, r.babel@law.mil.pl

Grzegorz Woroniak, Faculty of Civil Engineering and Environmental Sciences,
Białystok University of Technology, g.woroniak@pb.edu.pl

Abstract: This study examines the influence of carbon additives on selected mechanical properties of ABS and ASA filaments used in fused deposition modeling (FDM). Test specimens with varying infill densities (10–30%) and print orientations were fabricated and analyzed using tensile, flexural, and dynamic mechanical analysis (DMA) to assess both static and viscoelastic behavior. The results show that the effect of carbon reinforcement strongly depends on the polymer matrix. For ABS, the addition of carbon generally did not improve mechanical performance and often led to deterioration, likely due to reduced interlayer adhesion, increased delamination, and non-optimized processing parameters. In contrast, ASA-based composites demonstrated clear improvements in strength and stiffness. ASA with carbon additive (ASA CF) exhibited the highest and most stable elastic modulus values, along with favorable viscoelastic properties over a wide temperature range. DMA results supported findings from tensile and bending tests. ASA CF showed superior stability of the storage modulus (E'), while ABS CF displayed greater variability and a less distinct glass transition region. The impact of infill density on mechanical properties was relatively minor compared to material type and carbon addition. Print orientation also had limited influence, except for ASA CF, where the Y orientation improved performance. Overall, the study indicates that carbon modification in FDM filaments requires careful material selection and process optimization. While carbon additives enhance ASA performance, they do not provide expected benefits for ABS under unchanged processing conditions.

Keywords: ABS, ASA, FDM, tensile test, dynamic mechanical analysis, viscoelastic, carbon additive

PRELIMINARY RESEARCH OF DENSITY INFILL INFLUENCE ON THE TENSILE STRENGTH OF THERMOPLASTIC POLYURETHANE (TPU) 3D PRINTED ELEMENTS IN FUSED DEPOSITION MODELING (FDM) METHOD

Damian Jokiel, Poznań University of Technology, damian.jokiel@student.put.poznan.pl

Jan Górecki, Faculty of Mechanical Engineering, Poznań University of Technology,
jan.gorecki@put.poznan.pl

Abstract: Thermoplastic polyurethane (TPU) belongs to the group of elastomers, which are characterized by high elasticity and resistance to mechanical loading. The combination of elastomeric properties with the capability to be processed using methods typical for thermoplastic materials. In this case, TPU makes an attractive alternative to typical materials used in injection molding processes. Due to its wide range of applications, TPU is used, among others, in the automotive, medical, and footwear industries, as well as in automation systems. This study aimed to determine the ultimate tensile stress value and the elastic deformation characteristics of TPU material subjected to uniaxial tensile loading. The specimens used in the study were prepared in accordance with the ISO 37:2017 standard, using the Fused Deposition Modeling (FDM) technique. Based on established methods and the obtained stress–strain curves, the following mechanical properties were determined: tensile strength, elongation at break, elasticity modulus, sum of strain energy, and yield strength. The results presented in this paper made it possible to determine the variation of ultimate tensile stress as a function of infill density.

Keywords: thermoplastic polyurethane, fused deposition modeling, strain test, mechanical properties, elastomers

DEGRADATION BEHAVIOR OF RESIN-BASED COMPOSITES UNDER SIMULATED ORAL CONDITIONS: A COMPARATIVE STUDY OF MICROHARDNESS, SURFACE ROUGHNESS, AND WATER-RELATED PROPERTIES

Żaneta Anna Mierzejewska, Faculty of Mechanical Engineering, Białystok University of Technology, a.mierzejewska@pb.edu.pl

Nataša Trtić, Faculty of Medicine, University of Banja Luka, natasa.trtic@med.unibl.org

Radmila Arbutina, Faculty of Medicine, University of Banja Luka, radmila.arbutina@med.unibl.org

Abstract: Resin-based composites are widely used in direct restorative dentistry; however, their long-term performance depends on the interaction between material composition, surface condition, and exposure to chemically diverse oral environments. Experimental characterization of these degradation processes is important for clinical material selection, but also for the development, calibration, and validation of numerical models describing the mechanical and physicochemical stability of restorative materials. This study evaluated six commercially available RBCs representing different material classes: conventional, bulk-fill, flowable, and bioactive composites. Disc-shaped specimens were assigned to polished or unpolished groups and aged in distilled water, artificial saliva, acidic solution ($\text{pH} \approx 4$), or oxidative solution (3% hydrogen peroxide) for 24 hours, 7 days, and 30 days. Microhardness, surface roughness, SEM morphology, water sorption, solubility, and contact angle were assessed. Statistical analysis was performed using three-way ANOVA with Tukey's post hoc test ($\alpha = 0.05$). All materials showed time- and medium-dependent degradation, expressed as a progressive decrease in microhardness and an increase in surface roughness. After 30 days, hardness loss ranged from 4–6% in distilled water to over 30% in oxidative medium. The highest susceptibility to degradation was observed in ACTIVA BioACTIVE and SDR Flow+. Surface roughness exceeded the clinical threshold of $R_a = 0.2 \mu\text{m}$ under acidic and oxidative conditions, while water sorption ranged from 18 to $43 \mu\text{g}/\text{mm}^3$ and was greater in bioactive and flowable materials. The obtained dataset provides experimentally determined degradation parameters that may be used as material input data, boundary-condition references, or validation benchmarks for computational analyses of dental composite behavior. In particular, hardness loss, roughness evolution, sorption-related changes, wettability, and surface morphology may support numerical modelling of environmentally induced material degradation. These results may further help parameterize finite element models and verify simulations predicting stiffness loss, surface deterioration, and failure risk.

Keywords: resin-based composites (RBCs), dental composites aging, microhardness, surface roughness, water sorption, wettability, oxidative degradation

INFLUENCE OF SKIN MATERIAL AND SURFACE TREATMENT ON AERODYNAMIC PERFORMANCE

Piotr Maciak, Polish Air Force University, p.maciak7312@wsosp.edu.pl

Eryc Witkowski, Polish Air Force University, e.witkowski7386@wsosp.edu.pl

Abstract: This paper presents an analysis of the influence of material properties and surface treatment of wing skin on aerodynamic characteristics, based on experimental investigations conducted in a wind tunnel. The subject of the study was a 1:10 scale wing model with a geometry closely resembling the NACA 64A203 airfoil, which is applied, among others, in the design of the F-35 aircraft. The experiments were carried out in the wind tunnel of the Polish Air Force University. To evaluate the effect of skin type, two wing models with different structural configurations were manufactured. The first model consisted of a wooden frame covered with modeling film, while the second was a self-supporting structure made of carbon fiber composite. The study focused on identifying differences in aerodynamic characteristics resulting from the applied materials and surface finishing quality. The obtained results allowed for the assessment of the influence of structural stiffness and surface roughness on key aerodynamic parameters, such as lift and drag. The experimental findings revealed significant differences between the analyzed configurations, highlighting the importance of proper material selection and surface treatment in the design of both model-scale and full-scale wing structures.

Keywords: aerodynamic performance, wing skin, surface roughness, composite materials

RESULTS OF LABORATORY TESTS OF THE STATIC AND DYNAMIC FRICTION COEFFICIENTS OF FERTILIZER GRANULES AGAINST THE STRUCTURAL MATERIALS OF SEED DRILLS USING A ROTARY TEST STAND

Wiktor Łykowski, Faculty of Mechanical Engineering, Poznań University of Technology, wiktor.lykowski@doctorate.put.poznan.pl

Lukasz Gierz, Faculty of Mechanical Engineering, Poznań University of Technology, lukasz.gierz@put.poznan.pl

Abstract: The paper presents the results of laboratory investigations of static and dynamic friction coefficients of mineral fertilizer granules (urea) against structural materials used in agricultural seed drills. The experiments were carried out using an original rotary test stand enabling the analysis of tribological phenomena under conditions similar to the actual operating conditions of fertilizer metering systems. The scope of the study included the analysis of interactions between fertilizer granules and contact surfaces made of structural steel and polymer materials. The influence of motion parameters and the type of contact material on the values of static and dynamic friction coefficients was evaluated. The obtained results, subsequently implemented in simulation studies, indicate a significant influence of the working surface properties on the transport process of granular material and the stability of material flow. The developed research stand may constitute a useful tool supporting the design of fertilizer metering systems and the selection of materials limiting motion resistance and adhesion phenomena in the working elements of agricultural seed drills.

Keywords: friction coefficient, fertilizer granules, rotary test stand, agricultural engineering, simulation studies

THE INFLUENCE OF THE MOLD SIZE ON PROPERTIES OF GFRP MADE BY INFUSION METHOD

Jacek Janiszewski, Faculty of Aviation, Polish Air Force University,
j.janiszewski@law.mil.pl

Andrzej Komorek, Faculty of Aviation, Polish Air Force University,
a.komorek@law.mil.pl

Rafał Bieńczak, Faculty of Aviation, Polish Air Force University,
r.bieniczak@law.mil.pl

Daniel Śliwiński, Faculty of Aviation, Polish Air Force University,
d.sliwinski5704@wsosp.edu.pl

Abstract: The aim of the work is to investigate the influence of the mold size on the properties of a layered composite produced by the infusion method, i.e. how the form affects the propagation of the resin composition and the strength characteristics of the laminate. The scope of the work includes the following activities: production of one composite by the infusion method (which was divided into twelve research sectors), examination of individual samples from each sector under a microscope (in terms of the content of air voids in the material structure), examination of the internal and external structure of the laminates under a microscope, tests of the mechanical properties of samples prepared from the produced composite (bending strength test, impact strength test and tensile strength test). For the purpose of this work the nine layers composite was made with reinforcement of glass fiber roving fabric with a weight of 390 g/m^2 and a saturation of 370 g/m^2 and a "twill" weave. MGS L285 epoxy resin and H287 hardener were used for production. The resin and hardener were mixed in a 100:40 ratio (according to the manufacturer's recommendations). In order to facilitate the removal of the composite from the mold, a delamination fabric was used. In addition, a special mesh was used to facilitate the propagation of the resin mixture and its even flow through the mold. The final dimensions of the composite were $100 \times 100 \text{ cm}$. The composite was divided into 12 zones and tested. The highest bending strength was demonstrated by samples from sector five. In the tensile test, the best result was achieved by zone seven. The ambiguous results show the high influence of the mold (especially its size) on the propagation of the resin mixture in the infusion process.

Keywords: layered composites, composite manufacturing processes, infusion method, GFRP (glass fiber reinforced polymer).

NON-DESTRUCTIVE ANCHOR CONDITION CLASSIFICATION IN UNDERGROUND MINING USING FFT ANALYSIS AND TRANSFER LEARNING

Filip Wątopek, Faculty of Mechanical Engineering and Robotics, AGH University of Kraków, watorek@agh.edu.pl

Patryk Lorenc, AGH University of Kraków, patryklorenc@student.agh.edu.pl

Ireneusz Dominik, Faculty of Mechanical Engineering and Robotics, AGH University of Kraków, dominik@agh.edu.pl

Abstract: In underground mining, ensuring the integrity of roof support systems is critical for operational safety. Traditional methods of assessing the condition of mining anchors, such as pull-out tests, are destructive, costly, and provide limited spatial coverage. This paper introduces a non-destructive approach based on feature-level transfer learning, where anchor condition data collected in the geomechanically stable Wieliczka Salt Mine are used to support classification in the more dynamically challenging environment of the KWK Piast-Ziemowit Ruch Ziemowit coal mine. The proposed system integrates a self-excited vibration measurement setup with a Random Forest classification algorithm. Anchors subjected to different installation and boundary conditions generate distinct frequency-domain responses, which are captured through high-resolution signal acquisition and analyzed using Fast Fourier Transform (FFT). During the initial phase, reference data were collected in Wieliczka, where anchors were known to be correctly or incorrectly installed. These labeled datasets enabled the construction of a structured feature space based on selected spectral and harmonic descriptors related to anchor tension, installation quality, and vibration stability. Transfer learning was then employed to adapt diagnostic information extracted from the salt mine data to the more corrosive and mechanically heterogeneous setting of the Ziemowit coal mine. This was done using feature-level adaptation and limited target-domain calibration rather than retraining the model from scratch. Additional testing was used to evaluate whether the classifier could distinguish between properly and improperly installed anchors under varying environmental and installation conditions. The approach shows potential for transferable, in-situ anchor assessment without the need for destructive testing or extensive recalibration. This technique addresses an important challenge in mining engineering by evaluating whether non-destructive vibration-based diagnostics can be transferred between mining environments with different geological, structural, and mechanical conditions.

Keywords: transfer learning, non-destructive testing, string anchors, underground mining, vibration diagnostics, frequency-domain analysis, machine learning, structural health monitoring

EVALUATION OF MOISTURE CONTENT IN 600 AERATED CONCRETE USING TDR SENSORS WITH POLYLACTIDE HOUSING

Magdalena Paśnikowska-Lukaszuk, Faculty of Mathematics and Information
Technology, Lublin University of Technology, m.pasnikowska@pollub.pl

Zbigniew Suchorab, Faculty of Environmental Engineering and Energy, Lublin
University of Technology, z.suchorab@pollub.pl

Abstract: This paper analyzes the environmental parameters of aerated concrete 600 using a TDR (Time Domain Reflectometry) meter. The application of 3D printing in non-invasive measurements of environmental parameters of building envelopes is presented. The operating principle of the prepared meters is demonstrated. Probes with polylactide housings were developed for the meter. Previous measurements using PLA (polylactide) in scientific research on moisture content and permittivity of this material are presented. Non-invasive measurements of aerated concrete 600 samples were performed to determine the moisture content in the tested samples. The construction of the non-invasive TDR sensor is presented and the properties of the materials used in the tests are discussed. The permittivity and permittivity of the material were calculated and the root mean square error (RMSE) was determined using classical computational methods and machine learning techniques, focusing on GPR and SVM models. Final conclusions are presented along with an analysis of the obtained test results.

Keywords: TDR, moisture content, 600 aerated concrete, 3D printing, PLA

MECHANICAL PROPERTIES OF FLAX FIBRE- REINFORCED BIO-COMPOSITES

Jacek Czarnigowski, Faculty of Mechanical Engineering, Lublin University of Technology, j.czarnigowski@pollub.pl

Jakub Jarosz, Lublin University of Technology, s95000@pollub.edu.pl

Magda Drożdziel-Jurkiewicz, Faculty of Mechanical Engineering, Lublin University of Technology, m.drozdzziel@pollub.pl

Adrian Wróbel, Lublin University of Technology, s98395@pollub.edu.pl

Abstract: One of the main directions of development in automotive engineering is reducing the environmental impact of vehicle production and operation. Consequently, structural solutions with the lowest possible carbon footprint, particularly those based on renewable resources, are highly sought after. This paper presents the results of mechanical property tests (flexural and tensile strength) on composite laminates made of a bio-epoxy matrix reinforced with flax fiber fabric (linen). The laminates were intended as a material for the monocoque of a prototype ultra-efficient vehicle developed for the Shell EcoMarathon competition. The aim of the study was to determine the tensile and flexural strength limits and the modulus of elasticity for various configurations of a flax-fibre-based composite, and to determine the statistical variation in these values. The experiments were conducted to compare laminates based on three fabric types differing in areal weight (152, 230, and 300 g/m²) and two reinforcement architectures (0°/90° and ±45°). The data gathered during standardized tensile and three-point bending tests were analyzed using Student's t-test. The results demonstrate that Young's modulus is statistically independent of fabric weight but strongly depends on fiber orientation, and ranges from 3.61 GPa for the ±45° angle-ply layout to 5.68 GPa for the 0°/90° cross-ply arrangement. The fiber orientation significantly affects the ultimate tensile and flexural strengths, yielding up to 32% higher values for the orthotropic 0°/90° configuration. Statistical analysis highlights notable data dispersion (with the tensile strength coefficient of variation reaching 24.2%) attributable to the structural non-uniformity of natural fibers. Despite this variance, the analyzed bio-composites exhibit high specific stiffness and can be considered a candidate material for lightweight, low-carbon automotive components.

Keywords: biocomposites, flax fiber, mechanical testing, statistical analysis, sustainable automotive

NUMERICAL ANALYSIS OF HEAT TRANSPORT IN DISPERSIVE COMPOSITES WITH MICROENCAPSULATED PCMS: INFLUENCE OF VOLUME FRACTION, ELEMENTARY CELL SIZE AND MODEL DIMENSIONALITY

Maciej Kowalski, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, maciej.kowalski@wat.edu.pl

Lukasz Omen, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, lukasz.omen@wat.edu.pl

Andrzej J. Panas, Faculty of Mechatronics, Armament and Aerospace, Military University of Technology, andrzej.panas@wat.edu.pl

Abstract: Dispersive composites are widely used in materials engineering and industrial applications, therefore, the reliable determination of their effective thermal properties is essential for the analysis, modelling and design of this group of materials. The thermal response of such composites is governed not only by the inherent properties of their components, but also by their microstructure, the volume fraction of the dispersed phase and the geometrical representation adopted in numerical models. Composites containing phase change materials (PCM) are of particular interest, as their ability to store and release latent heat may significantly affect heat transport at both local and global scales, especially under transient thermal conditions. Although many analytical homogenization models for estimating the effective thermal conductivity of dispersed composites exist, phase change effects are still not fully represented in most classical analytical formulations. Therefore, the incorporation of a PCM into the dispersed phase introduces an additional modelling challenge. This study presents a numerical investigation of heat transport in a polymer type matrix composite containing uniformly distributed spherical polymer inclusions filled with a phase change material. Two-dimensional and three-dimensional models were developed and compared, considering different volumes fractions of inclusions and different sizes of the representative elementary cell. The simulations were performed under both steady-state and transient conditions in order to assess the effects of model dimensionality and elementary cell size on effective thermal properties. The obtained results make it possible to identify a compromise between computational accuracy and numerical cost, as well as to indicate the range in which two-dimensional models may serve as an effective simplification of three-dimensional models. The presented analysis provides a basis for selecting the size of the representative elementary cell in simulations of heat transport in dispersive composites containing phase change material-filled inclusions.

Keywords: dispersive composites, phase change material, effective thermal properties, numerical modelling, representative volume element

MICROHARDNESS–TOUGHNESS TRADE-OFF AND ANISOTROPY REDUCTION IN DMLS Ti₆Al₄ VINDUCED BY POST-PROCESSING HEAT TREATMENT

Żaneta Anna Mierzejewska, Faculty of Mechanical Engineering, Białystok University of Technology, a.mierzejewska@pb.edu.pl

Stanisław Dzielałak, Faculty of Mechanical Engineering, Białystok University of Technology, stanislaw.dzielałak@pb.edu.pl

Anna Falkowska, Faculty of Mechanical Engineering, Białystok University of Technology, a.falkowska@pb.edu.pl

Abstract: Direct Metal Laser Sintering (DMLS) of Ti6Al4V enables the fabrication of complex structural and biomedical components, but the resulting microstructure, residual stresses and build-orientation effects strongly influence damage initiation and fracture resistance. Experimentally determined material characteristics are therefore essential not only for mechanical assessment, but also as reference data for numerical modelling aimed at reducing repeated fabrication and destructive testing. This study investigated the influence of post-processing heat treatment on the microhardness, Charpy impact toughness, anisotropy and fracture mechanisms of DMLS Ti6Al4V. Specimens were fabricated in two build orientations, XY and XZ, using optimized parameters corresponding to a volumetric energy density of 127 J/mm³, and were annealed at 650, 750, 850 and 950 °C for 2 h under argon. Vickers microhardness testing, instrumented Charpy impact testing and SEM fractography were used to evaluate mechanical response and fracture behaviour. Heat treatment caused a progressive decrease in hardness from 401.7 to 326.0 HV₅, while mean impact toughness increased from 14.29 to 52.41 J/cm². The hardness anisotropy coefficient decreased from 1.078 to 1.015, and the impact-toughness anisotropy coefficient from 1.397 to approximately 1.03 after high-temperature annealing. SEM observations revealed a transition from quasi-brittle fracture with cleavage-like facets and defect-assisted crack initiation to predominantly ductile fracture governed by microvoid coalescence. These changes are consistent with α' martensite decomposition, residual stress relaxation and microstructural homogenisation. The obtained dataset may be used as input, calibration and validation material for finite element analyses, damage models and computer-aided assessment of heat-treated DMLS Ti6Al4V. Such experimentally grounded numerical models may support prediction of hardness–toughness relationships, anisotropic response and fracture risk without manufacturing and destructively testing numerous additional specimens. Therefore, the results constitute a practical basis for predictive numerical workflows aimed at optimizing heat-treatment conditions and limiting further trial-and-error testing.

Keywords: Ti6Al4V, DMLS, heat treatment, microhardness, Charpy impact toughness, anisotropy

INFLUENCE OF DEPOSITION RATE ON MICROSTRUCTURE AND MECHANICAL PROPERTIES OF TIN LAYERS: EXPERIMENT AND SIMULATION

Szymon Karski, Doctoral School, Lublin University of Technology,
s95779@pollub.edu.pl

Dariusz Chocyk, Faculty of Mechanical Engineering, Lublin University of Technology,
d.chocyk@pollub.pl

Mirosław Szala, Faculty of Mechanical Engineering, Lublin University of Technology,
m.szala@pollub.pl

Abstract: The development of high-performance functional surfaces relies heavily on magnetron sputtering, a precise physical vapor deposition technique that enables atomic-scale layer deposition. This study focuses on the structure and morphology evolution of samples deposited on substrates with different rates and samples of different total thickness deposited at the same rate. We used TiN targets and DC sputtering. Deposition rates for the TiN layers were varied from 0.5 Å/s to 1.5 Å/s, while the total thickness varied from 20 nm to 100 nm. As a substrate, we use tool steel. The resulting layers were characterized by X-ray diffraction (XRD) and atomic force microscopy (AFM) to assess their crystalline structure, phase composition, and surface topography. Additionally, we determined some mechanical properties using the nanoindentation method. The aim of the study is to connect the microstructure, morphology, and friction factor of TiN thin films with technological parameters. To support the interpretation of X-ray analysis, a computer program based on numerical simulations was used to calculate X-ray profiles from thin films. Software generates a model of thin layers with crystalline structure and calculates XRD patterns for comparison with experimental results. As initial simulation parameters, we used those obtained from phase and structure analysis. These tools, with rigorous empirical validation, could be used in the initial stages of predicting the future structure of thin films for DC sputtering deposition technology. The hardness and elastic modulus were determined from nanoindentation load-displacement curves.

Keywords: magnetron sputtering, PVD, thin layers, TiN, Titanium, Nitrogen, X-ray diffraction, tribology

APPLICATION OF IMAGE ANALYSIS FOR THE ASSESSMENT OF CAVITATION EROSION PHENOMENA FOR THE THERMAL SPRAYED COATINGS

Michał Cajzner, Wrocław University of Science and Technology,
michal.cajzner@wp.pl

Leszek Łatka, Faculty of Mechanical Engineering, Wrocław University of Science and
Technology, leszek.latka@pwr.edu.pl

Abstract: Cavitation erosion is a major degradation mechanism affecting structural materials operating in liquid environments, particularly components of fluid-flow machinery such as pumps, hydraulic turbines, valves, and marine propellers. The collapse of vapour-gas bubbles generates localized shock waves and high-velocity microjets, causing surface damage in the form of pits, craters, and microcracks. These processes lead to material loss, reduced service life, and increased maintenance costs, making the assessment of cavitation resistance an important issue in materials engineering. This study investigates the applicability of digital image processing and analysis for the quantitative assessment of cavitation-induced surface degradation. The proposed methodology enables the determination of damaged surface areas, comparison of the cavitation resistance of protective coatings, and monitoring of damage evolution with increasing cavitation exposure time. The theoretical part outlines the fundamentals of cavitation erosion, degradation mechanisms, and their effects on engineering materials, highlighting the role of digital image analysis as a complementary tool to conventional evaluation methods. The experimental investigation included cavitation testing, microscopic image acquisition, and the development of an original image-processing algorithm for automated detection and quantification of damaged areas. Cermets coatings were evaluated after identical exposure times, whereas ceramic coatings were examined after different cavitation durations. The results demonstrate that digital image analysis is a repeatable, objective, and effective method for assessing cavitation erosion. The proposed approach enables comparative evaluation of coating performance and monitoring of surface degradation, providing valuable support for durability assessment and lifetime prediction of protective coatings under service conditions.

Keywords: experiment, energy harvesting, modelling

EFFECTIVENESS OF SELECTED NDT METHODS FOR INSPECTION OF A 12-PLY AEROSPACE CFRP LAMINATE

Wojciech Pudło, Polish Air Force University, w.pudlo7090@wsosp.edu.pl

Grzegorz Kozłowski, Polish Air Force University, g.kozlowski@law.mil.pl

Mateusz Mucha, Polish Air Force University, m.mucha@law.mil.pl

Abstract: The increasing use of carbon fiber reinforced polymers (CFRP) in the primary structures of modern aircraft necessitates advanced diagnostic techniques for Barely Visible Impact Damage (BVID). Such damage, typically caused by low-velocity impacts like tool drops, poses a significant threat to flight safety because it remains undetectable during routine visual inspections while causing hidden degradation of the laminate's mechanical properties. This study utilized aviation-certified materials: a Twill weave carbon fabric (285 g/m²) and a specialized aerospace-grade epoxy resin system. Specimens were fabricated with 12 plies in a symmetric stacking sequence, where layers were rotated relative to one another to ensure balanced multidirectional reinforcement. Samples (80x60 mm) were produced via hydraulic pressing (30 tons), waterjet cutting, and thermal curing at 80°C for 10 hours. Controlled impact damage was induced using an Instron CEAST 9340 drop-weight tester at energies ranging from 1.0 J to 3.0 J. Technical evaluation utilized an Olympus BX53M microscope, a Woodpecker WP-632 digital tap tester, and a Dolphicam 2 ultrasonic system. Microscopy proved insufficient, identifying only surface-level cracks. While the tap test enabled rapid localization of defective areas, ultrasonic testing provided the highest precision for subsurface delamination visualization and accurate area measurement. A critical finding is that manufacturing inconsistencies significantly impact damage resistance, providing essential experimental data for computational modeling. Local thickness variations directly determined damage extent; a thickness deviation as small as 0.26 mm led to an almost twofold increase in the delamination area under the same impact energy. These results provide vital benchmarks for validating numerical models, demonstrating that predictive tools must account for manufacturing tolerances rather than assuming uniform laminate thickness. Integrating high-precision NDT mapping with numerical modeling is essential for accurately predicting the structural integrity of aerospace composites.

Keywords: carbon composites, NDT, BVID, ultrasonography, delamination

PORTABLE MULTICHANNEL ULTRASONIC TOMOGRAPHY FOR THREE-DIMENSIONAL IMAGING OF CONCRETE DEFECTS

Barbara Stefaniak, Research and Development Center, Netrix S.A.,
barbara.stefaniak@netrix.com.pl

Michał Gołabek, Research and Development Center, Netrix S.A.,
michal.golabek@netrix.com.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Monika Kulisz, Faculty of Management, Lublin University of Technology,
m.kulisz@pollub.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Abstract: This paper presents a portable multichannel ultrasonic tomography system for non-destructive three-dimensional imaging of internal heterogeneities in concrete structures. The instrument combines a modular matrix probe based on dry-contact DPC transducers with 32 independent transmit-receive channels, parallel acquisition, FPGA control, 12-bit conversion, and an embedded CM5 computing platform. The probe architecture supports beam steering and focusing without a coupling agent, which facilitates field inspection of rough surfaces. The reconstruction workflow removes baseline drift, derives an analytic representation of the transmitted pulse, applies regularized frequency-domain matched filtering, and detects arrival peaks after suppression of the direct sensor-to-sensor path. Detected time-of-flight values are associated with voxels using a precomputed propagation-distance model, while a voting scheme integrates evidence from multiple transmitter-receiver pairs. This aggregation reduces sensitivity to individual waveform amplitudes and highlights locations repeatedly confirmed by independent propagation paths. Measurements performed on a concrete block containing steel reinforcement and a PEX pipe demonstrate the feasibility of volumetric localization of embedded discontinuities. The developed platform integrates excitation, acquisition, processing, visualization, battery operation, and a touchscreen interface in a compact architecture, providing a practical basis for rapid on-site diagnostics of concrete structures.

Keywords: ultrasonic tomography, non-destructive testing, concrete diagnostics, direct point contact transducers, time-of-flight, matched filtering, beamforming, voxel reconstruction

EFFECT OF MATERIAL COMPOSITION AND EMBOSSING PROCESS PARAMETERS ON THE PUNCTURE RESISTANCE OF THREE-LAYER POLYETHYLENE FILMS WITH RECYCLED CONTENT

Michał Sasiadek, Instytut Inżynierii Mechanicznej, Uniwersytet Zielonogórski,
m.sasiadek@iim.uz.zgora.pl

Maciej Niedziela, Instytut Matematyki, Uniwersytet Zielonogórski,
M.Niedziela@im.uz.zgora.pl

Waldemar Woźniak, Instytut Inżynierii Materiałowej i Biomedycznej, Uniwersytet Zielonogórski, W.Wozniak@iimb.uz.zgora.pl

Tomasz Jachowicz, Katedra Technologii i Przetwórstwa Tworzyw Polimerowych, Politechnika Lubelska, t.jachowicz@pollub.pl

Jarosław Jajczyk, Zakład Elektrotechniki Teoretycznej i Stosowanej, Politechnika Poznańska, jaroslaw.jajczyk@put.poznan.pl

Arkadiusz Koziol, Instytut Matematyki, Uniwersytet Zielonogórski,
A.Koziol@wmie.uz.zgora.pl

Tomasz Tramś, Polipak Sp. z o.o., Środa Wielkopolska, t.trams@polipak.com.pl

Abstract: The increasing use of recycled polyethylene in multilayer films requires maintaining adequate mechanical performance under industrial processing conditions. This study investigates the puncture resistance of three-layer polyethylene films containing different proportions and types of recycled material and subjected to mechanical embossing. Three material groups were analysed: films containing approximately 54% recycled LDPE, approximately 54% recycled material with HDPE as the predominant component, and approximately 65% recycled material with a substantial HDPE fraction. The experimental programme included different embossing patterns, embossing intensity settings represented by the embossing roller axis distance parameter, and industrial film line speeds. Puncture resistance was evaluated using the mass required to damage the film. The analysis focused on determining the effects of material composition, embossing pattern, embossing intensity, and line speed, as well as their interactions. The results indicate that puncture behaviour cannot be explained solely by the total recycled content. Material composition and embossing conditions are important factors determining puncture performance, while the influence of line speed is substantially smaller. The study identifies material–process configurations providing increased puncture resistance and demonstrates the need for joint optimisation of recycled material composition and embossing conditions.

Keywords: multilayer polyethylene films, recycled polyethylene, mechanical embossing; puncture resistance; process parameters

DIRECTIONAL ANISOTROPY OF TEAR RESISTANCE IN EMBOSSSED THREE-LAYER POLYETHYLENE FILMS CONTAINING RECYCLED MATERIAL

Waldemar Woźniak, Instytut Inżynierii Materiałowej i Biomedycznej, Uniwersytet Zielonogórski, W.Wozniak@iimb.uz.zgora.pl

Maciej Niedziela, Instytut Matematyki, Uniwersytet Zielonogórski, M.Niedziela@im.uz.zgora.pl

Michał Sasiadek, Instytut Inżynierii Mechanicznej, Uniwersytet Zielonogórski, m.sasiadek@iim.uz.zgora.pl

Tomasz Jachowicz, Katedra Technologii i Przetwórstwa Tworzyw Polimerowych, Politechnika Lubelska, t.jachowicz@pollub.pl

Jarosław Jajczyk, Zakład Elektrotechniki Teoretycznej i Stosowanej, Politechnika Poznańska, jaroslaw.jajczyk@put.poznan.pl

Arkadiusz Koziol, Instytut Matematyki, Uniwersytet Zielonogórski, A.Koziol@wmie.uz.zgora.pl

Tomasz Tramś, Polipak Sp. z o.o., Środa Wielkopolska, t.trams@polipak.com.pl

Abstract: Mechanical anisotropy is an important characteristic of blown polyethylene films because their properties in the machine direction and cross direction may respond differently to material composition and subsequent processing. This study investigates the tear resistance of embossed three-layer polyethylene films containing high proportions of recycled material, with particular emphasis on differences between the machine direction (MD) and cross direction (CD). Three groups of films differing in recycled polyethylene content and type were analysed. The experimental variables included embossing pattern, embossing intensity represented by the embossing roller axis distance setting, and film line speed. Tear resistance was evaluated separately in MD and CD, and the effects of material and processing factors and their interactions were assessed using non-parametric multifactorial methods. The analysis demonstrates pronounced differences in tear behaviour among the material groups and confirms that the response to embossing is direction-dependent. The effects of embossing pattern and embossing intensity differ between MD and CD, whereas changes in industrial line speed have a comparatively limited influence. The results show that tear performance should not be represented by a single averaged mechanical characteristic. Separate consideration of MD and CD provides a more reliable basis for selecting recycled material compositions and embossing parameters for industrial multilayer film production.

Keywords: multilayer polyethylene films, recycled polyethylene, mechanical embossing, tear resistance, directional anisotropy

IDENTIFICATION OF A ROBUST EMBOSSING PROCESS WINDOW FOR THREE-LAYER RECYCLED POLYETHYLENE FILMS BASED ON MULTIPLE MECHANICAL PERFORMANCE CRITERIA

Maciej Niedziela, Instytut Matematyki, Uniwersytet Zielonogórski,
M.Niedziela@im.uz.zgora.pl

Waldemar Woźniak, Instytut Inżynierii Materiałowej i Biomedycznej, Uniwersytet Zielonogórski, W.Wozniak@iimb.uz.zgora.pl

Michał Sasiadek, Instytut Inżynierii Mechanicznej, Uniwersytet Zielonogórski,
m.sasiadek@iim.uz.zgora.pl

Tomasz Jachowicz, Katedra Technologii i Przetwórstwa Tworzyw Polimerowych,
Politechnika Lubelska, t.jachowicz@pollub.pl

Jarosław Jajczyk, Zakład Elektrotechniki Teoretycznej i Stosowanej, Politechnika Poznańska, jaroslaw.jajczyk@put.poznan.pl

Arkadiusz Koziol, Instytut Matematyki, Uniwersytet Zielonogórski,
A.Koziol@wmie.uz.zgora.pl

Tomasz Tramś, Polipak Sp. z o.o., Środa Wielkopolska, t.trams@polipak.com.pl

Abstract: Industrial optimisation of embossed multilayer polyethylene films cannot be based on a single mechanical property because processing conditions that improve one failure mode may adversely affect another. This study proposes a multi-response approach for identifying a robust embossing process window for three-layer polyethylene films containing high proportions of recycled material. Experimental data from three complementary laboratory studies were integrated, covering tensile strength in the machine and cross directions, puncture resistance, and tear resistance in both directions. The analysed factors included recycled material composition, embossing pattern, embossing intensity represented by the embossing roller axis distance setting, and industrial film line speed. Mechanical responses were normalised relative to corresponding reference films or technological requirements to enable comparison of properties expressed in different units. The objective was not to maximise an individual response but to identify material–process configurations that provide simultaneously stable tensile, puncture, and tear performance. The integrated analysis indicates that material composition and embossing intensity are the key variables requiring joint consideration, whereas production speed within the investigated industrial range is less critical. The proposed approach enables identification of processing regions in which high recycled content can be combined with balanced mechanical performance without relying on optimisation of a single strength characteristic.

Keywords: multilayer polyethylene films, recycled polyethylene, mechanical embossing, multi-response optimization, process window

IMPLEMENTATION OF ADDITIVE MANUFACTURING TECHNOLOGY IN THREADED FASTENERS

Mariusz Klonica, Faculty of Mechanical Engineering, Lublin University of Technology, m.klonica@pollub.pl

Oskar Sarnecki, Faculty of Mechanical Engineering, Lublin University of Technology

Abstract: The research paper aimed to evaluate the feasibility of utilizing 3D printing technology via the FDM (Fused Deposition Modeling) method in the manufacturing process of threaded components. The scope of the study included analyzing the impact of printing orientation on the dimensional accuracy of external metric threads produced in accordance with the International Organization for Standardization ISO 4014 standard, within the 6g accuracy class. Three materials with distinct mechanical properties and applications were used in the study: Hyper PLA, UV ABS, and PETG-CF. These materials were selected due to their varying performance characteristics, such as strength, thermal resistance, and the presence of reinforcing additives. The samples were fabricated in three different orientations relative to the printer's build plate: the Z orientation, where the thread axis was perpendicular to the working surface; the XY orientation, where the thread axis was parallel to the bed; and the 45° orientation, where the thread axis was positioned at a 45-degree angle to the build plate. The analysis focused on the effect of model positioning on the reproduction accuracy of key geometric parameters of the thread, including pitch, thread profile angle, minor diameter, pitch diameter, and major diameter. Measurements were conducted using two measuring devices. Preliminary geometric analysis was performed using a measuring microscope, while full testing was carried out using a Mitutoyo PJ-Plus profile projector, enabling a precise evaluation of the fabricated threads' geometry. The obtained results allowed for determining the influence of both the material type and printing orientation on the quality and manufacturing accuracy of FDM-printed threads.

Keywords: 3D printing, fused deposition modeling (FDM), threaded fasteners

LASER SURFACE TREATMENT OF ALSI11CUNIMG PISTON ALLOY

Jaroslav Piątkowski, Silesian University of Technology, Faculty of Materials Engineering and Digitalization of Industry, 44-100 Gliwice, Akademicka 2A, Poland, jaroslaw.piatkowski@polsl.pl

Abstract: In order to increase the power output and operational reliability, as well as to maximize the thermal efficiency of the piston-ring-cylinder (PRC) system, pistons used in modern internal combustion engines are continuously improved. These improvements mainly concern increasing the surface resistance of areas exposed to high thermo-mechanical loads. One of the latest methods used for this purpose is laser surface melting (LSM). This process enables, among other things, the formation of fine-grained surface structures with a thickness of up to approximately 600 μm , characterized by high microhardness and strength. The aim of the study was to determine the effect of selected laser parameters, i.e. laser beam power P ; energy density E_d ; and laser melting time t_L on the microstructure of a typical piston alloy. The microstructural changes were assessed on the basis of the laser beam radius r_b and the surface melt depth z_p . The AlSi11CuNiMg alloy was selected for the investigation, and the samples were taken from the piston crown. Using laser powers of 80, 500, 1000, and 1500 W and two beam travel speeds of 0.5 and 1.0 $\text{m} \cdot \text{min}^{-1}$, it was found that the most favorable laser power range for obtaining the desired surface microstructural changes is 500 to 1000 W. This range ensures effective refinement of the $\alpha(\text{Al})$ solid-solution dendrites. The microhardness of the melted layer reaches approximately 300 HV0.1 and is 4.0 times higher than the HV0.1 value for $\alpha(\text{Al})$ and approximately 2.4 times higher than the HV0.1 value for the unmelted $\alpha(\text{Al})+\beta(\text{Si})$ structure. The use of higher laser power for Al-Si-Cu-Ni-Mg alloys leads to a loss of material integrity, as well as increased porosity and surface roughness. It was found that the remelted zone contains no eutectic silicon crystals or $\alpha(\text{Al})+\beta(\text{Si})$ eutectic precipitates, while the $\alpha(\text{Al})$ solid-solution dendrites are refined and retain a texture oriented perpendicular to the direction of laser beam action.

Keywords: Al-Si piston alloys, laser surface melting, microstructure, microhardness

STAINLESS STEEL WELD OVERLAYS PROPERTIES AND ABRASIVE WEAR RESISTANCE

Mikolaj Sowa, Doctoral School, Lublin University of Technology,
s98388@pollub.edu.pl

Mirosław Szala, Faculty of Mechanical Engineering, Lublin University of Technology,
m.szala@pollub.pl

Abstract: The improvement of the surface durability of structural steels is an important issue in applications involving abrasive wear conditions. This study investigates the properties and abrasive wear resistance of stainless steel weld overlays deposited on S235JR steel substrates using the Tungsten Inert Gas (TIG) welding process. The overlays were produced with ER308LSi filler metal and subsequently characterized by a combination of microstructural, hardness, and tribological investigations. The microstructure and chemical composition of characteristic regions were analyzed using scanning electron microscopy (SEM) and energy-dispersive spectroscopy (EDS). Hardness distribution across the weld overlay, dilution and substrate was determined by Vickers hardness measurements. To support the quantitative assessment of the metallurgical bonding, a dedicated machine vision script developed in Python was used to evaluate the fusion line geometry and selected geometric characteristics of the deposited layers. Abrasive wear resistance was evaluated using the rubber-wheel abrasion test and benchmarked against AISI 304 stainless steel. Furthermore, SEM observations of the worn surfaces enabled identification of the dominant wear mechanisms and their relation to the microstructural features of the overlays. The results demonstrate that TIG-deposited ER308LSi weld overlays provide effective protection of low-carbon steel substrates against abrasive wear and exhibit favorable mechanical properties, making them a promising solution for regeneration and surface engineering applications.

Keywords: weld overlay, TIG, microstructure, abrasive wear, SEM

PRODUCTION ENGINEERING, MANAGEMENT AND QUALITY CONTROL

AN AUDITABLE LLM-RAG DIGITAL QUALITY TWIN SUPPORTING SIMULATION-BASED VALIDATION AND SAFER DEFECT CONTROL IN INDUSTRY 4.0 AND 5.0 FOR PRODUCTION AND TECHNOLOGY MANAGEMENT

Jakub Pizoń, Faculty of Management, Lublin University of Technology,
j.pizon@pollub.pl

Abstract: Generative artificial intelligence (GenAI), and large language models (LLMs) in particular, have rapidly moved from experimental tools to solutions deployed as copilots for production and technology management processes. In manufacturing environments, the potential of LLMs primarily concerns reducing the cognitive cost of defect analysis, accelerating root-cause diagnostics, and automating work with quality documentation. At the same time, a key limitation becomes apparent: LLMs may generate seemingly credible content that is not supported by evidence, which in Industry 4.0/5.0 settings translates into a risk of erroneous process interventions, loss of traceability, and non-compliance with AI governance requirements. The aim of this paper is to propose an auditable “LLM-augmented Digital Quality Twin” (LDQT) architecture that combines an LLM with Retrieval-Augmented Generation (RAG), a digital quality twin, and the human-in-the-loop principle, and then to quantitatively assess its potential benefits in a computational study. We use discrete-event simulation at the level of a production stream with stochastic process-drift events and an intervention policy (manual, rule-based, and LLM-RAG with a governance layer). A Monte Carlo experiment ($R=400$ replications, $N=4000$ items per replication) shows that the LDQT scenario reduces the mean unit cost of quality and downtime by approximately 20% relative to the manual approach, while simultaneously increasing first-pass yield. The contribution of the paper is methodological: we propose a coherent architectural model and a set of metrics for assessing the trade-off between efficiency and decision safety in industrial GenAI deployments.

Keywords: generative AI; large language models; RAG; digital twin; quality engineering; Industry 4.0; Industry 5.0; human–AI teaming; AI governance; discrete-event simulation.

AN INTEGRATED BWM- FUZZY TOPSIS MODEL FOR STEEL STRUCTURE MANUFACTURER SELECTION: A CASE STUDY

Adam Deptuła, Faculty of Production Engineering and Logistics, Opole University of Technology, a.deptula@po.edu.pl

Patryk Machnik, Opole University of Technology, patryk.machnik@student.po.edu.pl

Abstract: The selection of reliable steel structure manufacturers is a critical decision-making problem that directly affects production continuity, project profitability, quality performance, and long-term business cooperation. This challenge becomes particularly significant in engineer-to-order environments, where technical documentation quality, communication efficiency, technological capabilities, and delivery reliability play a key role in project execution. The aim of this study is to develop and apply an integrated Best-Worst Method (BWM) and Fuzzy TOPSIS framework for the evaluation and selection of steel structure manufacturers in an enterprise specialising in steel structure production. First, BWM was employed to determine the relative importance of the evaluation criteria based on expert assessments. Subsequently, Fuzzy TOPSIS was used to rank the analysed manufacturers under conditions of uncertainty and subjective judgement. The proposed framework enables the simultaneous consideration of technical, organisational, and economic criteria affecting supplier performance. The results identify the most influential criteria in the manufacturer selection process and indicate the alternatives that provide the highest potential for long-term cooperation. The findings demonstrate that criteria related to technical documentation quality, communication effectiveness, technological competence, and order profitability have a substantial impact on the final ranking of manufacturers. The study contributes to the supplier selection literature by providing an integrated multi-criteria decision-making framework tailored to the steel structure industry. The proposed approach supports managerial decision-making and offers a practical tool for reducing selection risk and improving the effectiveness of strategic cooperation with manufacturing partners.

Keywords: steel structure manufacturers, supplier selection, Best-Worst Method, BWM, Fuzzy TOPSIS, multi-criteria decision-making

THE LUBLIN R-XIIID AIRCRAFT – HISTORICAL BACKGROUND AND STRUCTURAL CHARACTERISTICS

Jarosław Mądro, Lublin University of Technology, Poland, j.madro@pollub.pl

Hubert Dębski, Faculty of Mechanical Engineering, Lublin University of Technology,
Poland, h.debski@pollub.pl

Abstract: The presentation will focus on the history of the Plage & Laśkiewicz Mechanical Works in Lublin, a company that played a pivotal role in the development of the Polish aviation industry during the interwar period. It will cover the company's origins and growth, as well as its transition from manufacturing industrial equipment to aircraft production.

Particular attention will be paid to the Lublin R-XIII aircraft—its origins, design process, construction, and the development of subsequent variants. The presentation will also discuss its technical capabilities, its service in the Polish military air force, and its role in the September Campaign of 1939.

Furthermore, the talk will highlight the career of engineer Jerzy Rudlicki—the chief designer associated with the Lublin plant—and the significance of his work for the advancement of Polish engineering. The presentation will conclude with an overview of the contemporary initiative to build a flying replica of the Lublin R-XIII, an effort aimed at preserving and promoting the aviation heritage of Lublin and the surrounding region.

Keywords: Plage & Laśkiewicz, aircraft, replica, Poland's first aircraft factory

ENERGY-EFFICIENT UWB LOCALIZATION WITH MULTILATERATION FOR WAREHOUSE ASSET TRACKING

Michał Styła, Information Technology Research & Development Centre (CBRTI sp. z o. o.), michal.styla@cbrti.pl

Przemysław Adamkiewicz, Information Technology Research & Development Centre (CBRTI sp. z o. o.); Institute of Computer Science and Innovative Technologies, WSEI University, przemyslaw.adamkiewicz@cbrti.pl

Abstract: This paper presents a miniaturized, energy-efficient ultra-wideband (UWB) localization platform developed for real-time tracking of assets in warehouse management systems (WMS). The system combines custom, highly integrated hardware with a deterministic position-estimation pipeline. The infrastructure comprises STM32 F7-based anchors with Ethernet and Power over Ethernet connectivity and battery-powered tags based on the nRF52832 microcontroller, environmental sensors, and an accelerometer. Inter-device ranges are acquired through double-sided two-way ranging (DS-TWR). Tag coordinates are then estimated by linearizing the quadratic distance equations and solving the resulting overdetermined system in the least-squares sense. Localization quality is evaluated using the root-mean-square residual between measured and reconstructed anchor-to-tag distances, while the rank of the system matrix is used to verify geometric solvability. The approach requires at least three non-coplanar anchors for three-dimensional positioning and positive range observations. Experimental reconstruction with real measurements was assessed by comparing the estimated tag location with its position in a camera image and a three-dimensional model of the test room. The results demonstrate the feasibility of integrating compact, low-power UWB devices and computationally efficient multilateration into a comprehensive warehouse localization solution. The proposed platform provides a practical foundation for real-time asset visibility, WMS support, and further development of robust positioning algorithms for industrial indoor environments.

Keywords: ultra-wideband, indoor localization, warehouse management systems, double-sided two-way ranging, multilateration, asset tracking

NAR AND LSTM-DEPENDENT PREDICTION FOR EARLY WARNING OF ERRORS IN PROCESS TOMOGRAPHY

Mariusz Mazurek, Institute of Philosophy and Sociology, Polish Academy of Sciences, mmazurek@ifispan.edu.pl

Krzysztof Król, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, krzysztof.krol@netrix.com.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, tomasz.rymarczyk@netrix.com.pl

Monika Kulisz, Faculty of Management, Lublin University of Technology, m.kulisz@pollub.pl

Edward Kozłowski, Faculty of Management, Lublin University of Technology, e.kozlovski@pollub.pl

Grzegorz Kłosowski, Faculty of Management, Lublin University of Technology, g.klosowski@pollub.pl

Abstract: Reliable early warning in industrial tomography requires forecasts that capture process dynamics rather than merely extrapolate stationary behavior. This study evaluates how input-window length and feedback updating affect short-term prediction of a nonstationary measurement signal for the predictive layer of a multimodal process-tomography system. A real sequence of 3000 samples, containing steady, declining, and rising regimes with fluctuations lasting 100 to 200 samples, was modeled using nonlinear autoregressive (NAR) and long short-term memory (LSTM) networks. Each model predicted the next 100 samples from base windows of 100, 200, 300, 500, and 1250 observations. Closed-loop forecasting was evaluated both without measurement updates and with updates based on actual observations, while performance was quantified using the root mean square error (RMSE). On steady intervals, NAR slightly outperformed LSTM for the 100- and 200-sample windows, obtaining RMSE values of 0.0068 versus 0.0089 and 0.0066 versus 0.0089, respectively. Under trend changes, LSTM with actual-data updating was more accurate than NAR for the 300-sample window, with RMSE values of 0.0110 and 0.0185. The best overall result was achieved by the updated LSTM using the 1250-sample window, which yielded an RMSE of 0.0050 compared with 0.0143 for NAR. The findings demonstrate that effective early fault warning depends on selecting a history window that spans at least one complete cycle of process variability. Integrating window-aware LSTM forecasts with electrical and ultrasound tomographic reconstruction can strengthen industrial monitoring and support earlier detection of emerging downtime.

Keywords: process tomography, time-series forecasting, long short-term memory, nonlinear autoregressive network, early fault warning, predictive maintenance

TECHNOLOGY MANAGEMENT IN ENERGY ACQUISITION PROCESSES

REVIEW OF THE USE OF EMG SIGNALS IN ENGINE CONTROL SYSTEMS FOR ENERGY EFFICIENCY IMPROVEMENT

Aleksandra Świadek, Faculty of Mechanical Engineering, Poznań University of Technology, aleksandra.swiadek@put.poznan.pl

Lukasz Wargula, Faculty of Mechanical Engineering, Poznań University of Technology, lukasz.wargula@put.poznan.pl

Weronika Wiatrowska, Faculty of Mechanical Engineering, Poznań University of Technology, weronika.wiatrowska@put.poznan.pl

Bartosz Wieczorek, Faculty of Mechanical Engineering, Poznań University of Technology, bartosz.wieczorek@put.poznan.pl

Abstract: Improving the precision of internal combustion engine control—particularly through better matching of engine rotational speed to the conditions under which maximum torque can be generated—enables reliable machine operation while also reducing fuel consumption and harmful exhaust emissions. One promising approach to enhancing engine speed matching involves the use of electromyographic (EMG) signals to predict machine load or to regulate engine speed based on the operator's physiological effort. Operating at lower rotational speeds, when appropriate to the actual load conditions, may contribute to reduced fuel consumption and lower emissions. In the case of wood chippers, existing solutions typically rely on optical sensors located in the feeding channel or on indirect measurements such as the rotational speed of the working mechanism. However, a novel concept is emerging that utilizes EMG signals as a control input, as proposed in patent application No. P.455047. This approach introduces a human-centered control paradigm, in which the operator's neuromuscular activity is directly incorporated into the control loop. Nevertheless, the implementation of such systems requires comprehensive research, including the identification of representative muscle groups, signal processing strategies, and validation of the relationship between EMG activity and machine load. This paper provides an overview of current approaches and outlines the challenges and potential of EMG-based control systems in combustion engine-driven machinery.

Keywords: combustion engine control, adaptive control systems, biomechanical signals, electromyography (EMG), fuel consumption reduction, exhaust emission reduction.

SEASONAL VARIATIONS OF RENEWABLE ENERGY IN POLAND

Olga Orynycz, Faculty of Engineering Management, Białystok University of Technology, o.orynycz@pb.edu.pl

Abstract: The renewable energy sources may be easily named as the energy of the European future. The ambition of the European Parliament is that renewable energy sources must make up at least 40% of the energy consumed within the EU by 2030. It is not only a political statement, but the reality. In 2023, in Germany, 55 percent of electric energy was created by renewable energy sources, including over 31% produced by wind turbines (both inland and offshore). Poland goes the same path – in 2023, renewables produced 27% of total energy. Recent turbulences in the worldwide market of fossil fuels show clearly that such an approach is a must. The amount of wind-produced energy in Poland has grown over the years, it is not the perfect solution. Its key disadvantage is a variation in time due to the weather changes. It is roughly estimated that the equivalent time of energy generation by a power plant is between 25% and 33%. Our previous studies covered the amount of wind energy over Poland, based on multiannual weather reports. The data show clearly that in a mesoscale, amount of wind energy is moderate, but sufficient to be successfully utilized. However, this energy is not equally distributed in time. It is a well-known fact that the wind speed in winter is higher than in summer, and its variation is the greatest in autumn and spring. Also, the temperature and pressure of the air vary, which leads to changes in wind energy.

Keywords: the usefulness of wind energy, amount of energy, seasonal variation of energy, equivalent time of power plant work

EXPERIMENTAL ANALYSIS OF CURRENT-VOLTAGE CHARACTERISTICS AND STATISTICAL PARAMETERS OF THE EMISSION CURRENT AS A FUNCTION OF TEMPERATURE AND ANODE WORK FUNCTION IN A THERMIONIC ENERGY CONVERTER

Adam Kuśmierowski, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, a.kusmierowski@pollub.pl

Krzysztof Skiba, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, k.skiba@pollub.pl

Dariusz Kuś, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, d.kus@pollub.pl

Jarosław Sikora, Faculty of Electrical Engineering and Computer Science, Lublin University of Technology, jaroslaw.sikora@pollub.pl

Abstract: In vacuum thermionic energy converters, one of the key parameters is the anode work function and its selection relative to the set cathode work function. This paper presents the results of experimental studies on the influence of temperature and anode work function on the static current-voltage characteristic $I_e=f(U_{k-a})$ of a thermionic energy converter and on the statistical parameters of the electron thermionic emission current I_e at specified operating points of the static characteristic. To ensure repeatable measurement conditions, i.e., conducting the tests with the same anode material, dispenser-type cathodes were used in the design of the converter electrodes. Continuous changes in temperature and anode work function were achieved by controlling the heating power supplied to the anode and using the empirical relationship between work function and temperature.

Keywords: thermionic energy converter, experimental

COMPUTER SIMULATIONS AND APPLICATIONS IN ELECTRICAL ENGINEERING

ADAPTIVE TRAFFIC SIGNAL CONTROL WITH A PPO-TRANSFORMER ARCHITECTURE IN COMPLEX TRAFFIC SYSTEMS

Jakub Drzał, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, j.drzal@prz.edu.pl

Daniel Kleczyński, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, d.kleczynski@prz.edu.pl

Bartosz Pawłowicz, Faculty of Electrical and Computer Engineering, Rzeszów University of Technology, barpaw@prz.edu.pl

Abstract: Coordinated traffic signal control in complex urban networks remains a challenging control problem due to strong spatiotemporal coupling between adjacent nodes and dynamically varying traffic demand. An adaptive control framework based on Proximal Policy Optimization (PPO) integrated with a Transformer architecture is proposed to address network-level traffic management across multiple signalized junctions. Traffic conditions are represented as distributed time-series describing aggregated vehicle flows within short intervals. Transformer-based model is used to extract temporal features and capture dependencies between various parts of the network, enabling the control layer to account for propagation effects such as queue spillback and flow interactions. Based on this representation, the PPO agent determines phase transition decisions, balancing local responsiveness with global coordination while satisfying operational constraints. The control objective is formulated at the network level and focuses on minimizing cumulative delay, queue lengths, and congestion while maintaining balanced traffic distribution. The approach is evaluated in the SUMO (Simulation of Urban MObility) simulation environment using a multi-node traffic scenario and compared with a fixed-time control strategy and the adaptive Miller algorithm under identical traffic demand and signal constraints. The results show that the PPO-Transformer framework consistently demonstrates superior performance, adaptability, and scalability, establishing it as the most effective approach for coordinated urban traffic signal control.

Keywords: complex systems, DRL, ITS, PPO, SUMO, transformer

ADAPTIVE INDUSTRIAL TOMOGRAPHIC RECONSTRUCTION THROUGH BIDIRECTIONAL LSTM- GUIDED ENSEMBLE SELECTION

Mariusz Mazurek, Institute of Philosophy and Sociology, Polish Academy of Sciences,
mmazurek@ifispan.edu.pl

Krzysztof Król, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, krzysztof.krol@netrix.com.pl

Edward Kozłowski, Faculty of Management, Lublin University of Technology,
e.kozlovski@pollub.pl

Monika Kulisz, Faculty of Management, Lublin University of Technology,
m.kulisz@pollub.pl

Konrad Niderla, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, konrad.niderla@netrix.com.pl

Grzegorz Klosowski, Faculty of Management, Lublin University of Technology,
g.klosowski@pollub.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of
Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Abstract: Industrial process tomography requires stable reconstruction from incomplete, noise-sensitive measurements. This study proposes a method-oriented ensemble (MOE) in which a bidirectional long short-term memory (BiLSTM) network selects the best reconstruction method for each electrical impedance tomography (EIT) measurement vector. The framework was assessed using a 200 mm tank with 16 electrodes and variable 20 mm inclusions. MATLAB/EIDORS simulations generated 35,000 three-dimensional training cases. Elastic Net, least-squares linear regression, SVM-based linear regression, support vector machine, and artificial neural network models were trained independently for 2,883 pixels, yielding 14,415 predictors. A two-layer BiLSTM classifier with 128 hidden units per layer processed sequences of 96 voltage measurements and selected the method with the lowest mean root-mean-square error. Adaptive selection increased robustness to disturbances and improved representation of inclusion visibility, shape, number, and position relative to homogeneous reconstruction methods. The concept was also transferred to ultrasound tomography. The framework supports intelligent industrial process monitoring and provides a basis for multimodal EIT-UST reconstruction integrated with autonomous sensor networks.

Keywords: electrical impedance tomography, industrial process tomography, bidirectional LSTM, method-oriented ensemble, adaptive image reconstruction, machine learning, inverse problems, industrial process monitoring

MEASUREMENT-CONSISTENT HYBRID NEURAL RECONSTRUCTION FOR ELECTRICAL IMPEDANCE TOMOGRAPHY

Grzegorz Kłosowski, Faculty of Management, Lublin University of Technology,
g.klosowski@pollub.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of
Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Monika Kulisz, Faculty of Management, Lublin University of Technology,
m.kulisz@pollub.pl

Konrad Niderla, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, konrad.niderla@netrix.com.pl

Michał Oleszek, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, michal.oleszek@netrix.com.pl

Paweł Olszewski, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, pawel.olszewski@netrix.com.pl

Abstract: Electrical impedance tomography (EIT) offers non-invasive monitoring of industrial and laboratory reactors, but image reconstruction remains strongly ill-posed because sparse boundary-voltage measurements must be mapped to high-dimensional conductivity distributions. This paper proposes a hybrid deep-learning and physics-informed reconstruction pipeline that combines a transformer-based inverse model, residual Attention U-Net refinement, and optional Plug-and-Play measurement feedback. A normalized 96-element voltage vector is first converted by the primary reconstructor into a logarithmic finite-element conductivity estimate. The estimate is interpolated onto a 128 x 128 grid and refined by an Attention U-Net that preserves the global structure while correcting local artefacts, inclusion boundaries, and contrast. In the optional iterative stage, a differentiable forward surrogate predicts boundary voltages from the current image. The resulting voltage residual drives successive image updates and promotes consistency with the acquired measurements. Qualitative comparisons for three representative EIT cases show progressive improvement from the primary reconstruction through U-Net refinement to Plug-and-Play correction, with clearer inclusion localization, reduced artefacts, improved contrast, and closer visual agreement with the reference conductivity maps. The framework therefore couples the computational efficiency of direct neural inversion with image-domain enhancement and physics-guided consistency control, providing a modular approach to fast and measurement-consistent EIT reconstruction.

Keywords: electrical impedance tomography, inverse problem, transformer, attention U-Net, plug-and-play reconstruction, differentiable forward surrogate, physics-informed deep learning

MULTI-HEAD NEURAL RECONSTRUCTION OF 2D EIT IMAGES FOR INDUSTRIAL REACTOR MONITORING

Monika Kulisz, Faculty of Management, Lublin University of Technology,
m.kulisz@pollub.pl

Grzegorz Kłosowski, Faculty of Management, Lublin University of Technology,
g.klosowski@pollub.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of
Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Konrad Niderla, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, konrad.niderla@netrix.com.pl

Abstract: Electrical impedance tomography (EIT) offers non-invasive, low-cost and high-temporal-resolution monitoring of multiphase processes, but image reconstruction remains constrained by an ill-posed, nonlinear inverse mapping and a large disparity between measurement and image dimensions. This study proposes a multi-head fully connected neural architecture for reconstructing two-dimensional conductivity distributions in industrial reactor cross-sections. The task is formulated as supervised regression from a 96-element boundary-voltage vector to a 2883-element conductivity vector. A shared feature-extraction core feeds 31 parallel output heads, each predicting 93 conductivity values; layer normalization, dropout and L2 regularization are used to stabilize training and limit overfitting. The concatenated head outputs form the final 2D conductivity map. Performance was assessed against a conventional fully connected network with a single output branch using mean squared error (MSE), Pearson correlation coefficient (PCC) and visual inspection of reconstructed maps. In two representative cases, the proposed architecture reduced MSE from 0.0111 to 0.0049 and from 0.0083 to 0.0048, corresponding to reductions of approximately 56% and 42%. PCC increased from 0.6974 to 0.8810 and from 0.8268 to 0.9067, respectively. The multi-head model also yielded more spatially coherent reconstructions, fewer background artifacts and better preservation of the principal conductivity regions. These results indicate that decomposing the high-dimensional output space into localized regression heads improves reconstruction accuracy and stability, providing a promising basis for data-driven EIT monitoring of industrial reactors.

Keywords: electrical impedance tomography, industrial reactor monitoring, inverse problem, multi-head neural network, image reconstruction, supervised regression, conductivity mapping

DIRECT NEURAL RECONSTRUCTION OF URINARY BLADDER IMAGES FROM WEARABLE ELECTRICAL IMPEDANCE TOMOGRAPHY DATA

Mariusz Mazurek, Institute of Philosophy and Sociology, Polish Academy of Sciences,
mmazurek@ifispan.edu.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of
Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Marcin Dziadosz, Faculty of Mathematics and Information Technology, Lublin
University of Technology, m.dziadosz@pollub.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Michał Oleszek, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, michal.oleszek@netrix.com.pl

Abstract: Electrical impedance tomography (EIT) enables non-ionizing, low-cost and continuous imaging, making it suitable for wearable monitoring of urinary bladder filling. This study investigates a direct neural reconstruction method for a textile EIT system in which conductivity images are estimated from boundary measurements without an intermediate deterministic reconstruction. The proposed measurement concept uses 16 textile electrodes integrated into underwear, while the reconstruction model maps a 96-element EIT vector to a 64×64 -pixel image. The fully connected multilayer perceptron comprises layers of 96, 256, 512, 1024, 2048 and 4096 neurons and uses ReLU activation, batch normalization and dropout. The model was trained for 50 epochs using the Adam optimizer and mean squared error loss, with the dataset divided into training, validation and test subsets in a 70:15:15 ratio. Evaluation on the independent test set produced an MSE of 0.005, an RMSE of 0.068, a PSNR of 21.44 dB and an SSIM of 0.783. The results show that the direct MLP preserves object geometry while maintaining low reconstruction error, which is relevant to tracking bladder shape and position. The model therefore provides a computationally simple baseline for rapid reconstruction in wearable EIT systems. Future work should validate the method using measurements from the textile prototype and expand the dataset with anatomically representative lower urinary tract scenarios.

Keywords: electrical impedance tomography, urinary bladder monitoring, wearable medical imaging, multilayer perceptron, image reconstruction, textile electrodes

MULTIMODAL NEURAL RECONSTRUCTION FOR HYBRID ULTRASOUND-IMPEDANCE TOMOGRAPHY OF THE LOWER URINARY TRACT

Mariusz Mazurek, Institute of Philosophy and Sociology, Polish Academy of Sciences,
mmazurek@ifispan.edu.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of
Computer Science and Innovative Technologies, WSEI University,
tomasz.rymarczyk@netrix.com.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A.; Institute of Computer
Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Marcin Dziadosz, Faculty of Mathematics and Information Technology, Lublin
University of Technology, m.dziadosz@pollub.pl

Abstract: This study presents a multimodal neural reconstruction framework for a hybrid ultrasound-impedance tomograph designed for non-invasive examination of the lower urinary tract. The system integrates a 16-channel electrical impedance tomography (EIT) module with a 32-channel ultrasound tomography (UST) module expandable to 64 channels and supports separate or simultaneous acquisition. Three Multi-Layer Perceptron (MLP) architectures were developed to reconstruct 64×64 tomographic images from EIT measurements, UST measurements, and fused EIT-UST features. The EIT and UST models used 96- and 120-element input vectors, respectively. The multimodal model employed parallel modality-specific branches whose 512-dimensional representations were concatenated and processed by a fusion block. The data were divided into training, validation, and test subsets in a 70:15:15 ratio. All models were trained for 50 epochs using the Adam optimizer, a learning rate of 10^{-4} , mean squared error loss, batch normalization, ReLU activation, and dropout. Reconstruction quality was assessed using MSE, RMSE, MAE, peak signal-to-noise ratio (PSNR), and structural similarity index (SSIM), supplemented by visual comparison with reference images. The fused EIT-UST model achieved the best test performance, with an MSE of 0.004227, RMSE of 0.0645, PSNR of 21.86 dB, and SSIM of 0.7860, outperforming both single-modality networks. These results demonstrate that complementary electrical and acoustic measurements improve the fidelity and structural consistency of neural tomographic reconstructions. The proposed approach supports non-invasive, repeatable lower urinary tract assessment and provides a basis for further validation in multimodal bladder monitoring.

Keywords: electrical impedance tomography, ultrasound tomography, multimodal imaging, image reconstruction, multi-layer perceptron, neural networks, lower urinary tract, urinary bladder

MULTIMODAL EITS AND OPTICAL SENSING FOR NON-INVASIVE GLUCOSE MONITORING

Dominik Gnaś, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, dominik.gnas@netrix.com.pl

Tomasz Rymarczyk, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, tomasz.rymarczyk@netrix.com.pl

Dariusz Wójcik, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, dariusz.wojcik@netrix.com.pl

Michał Oleszek, Research and Development Center, Netrix S.A.; Institute of Computer Science and Innovative Technologies, WSEI University, michal.oleszek@netrix.com.pl

Abstract: This study presents a modular hardware platform for investigating non-invasive glucose monitoring through electrical bioimpedance and glucose-induced osmotic phenomena, complemented by optical near-infrared spectroscopy and photoplethysmography (NIRS/PPG). The measurement principle does not rely on direct electrical detection of glucose molecules. Instead, it exploits water redistribution between intracellular and extracellular compartments caused by changes in osmolarity. The resulting variations in cell geometry, membrane capacitance, and extracellular conduction paths produce frequency-dependent shifts in tissue impedance. The proposed platform implements Electrical Impedance Tomography Spectroscopy (EIT-S) for controlled current excitation, voltage acquisition, and impedance analysis over a selected frequency range. Its modular architecture comprises a signal-generation stage, analog front-end, data-acquisition circuitry, and an STM32WBA-based control board responsible for processing and wireless transmission. A dedicated sensing board integrates gold-plated electrodes, optical emitters, and reflected-light detectors, enabling electrical and optical signals to be acquired from the same tissue region. Measurement data are transmitted via Bluetooth Low Energy to a mobile application that functions as both the user interface and a local node of a distributed diagnostic system. The developed device constitutes an experimental testbed for studying correlations among glucose concentration, osmotic effects, bioimpedance spectra, and optical features. Its multimodal architecture provides a basis for future calibration, feature-fusion, and validation studies toward comfortable and continuous glucose monitoring.

Keywords: non-invasive glucose monitoring, electrical bioimpedance spectroscopy, EIT-S, osmotic phenomena, NIRS, PPG, multimodal sensing, biomedical instrumentation, bluetooth low energy